



SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
Date of first issue: 04/18/2017

Print Date 06/25/2020

SECTION 1. IDENTIFICATION

Product name : ARALDITE® 2031-1 RESIN

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980
The Woodlands,
TX 77387
United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : SDS@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Epoxy constituents

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

GHS label elements

Hazard pictograms



Signal word

Warning

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
 Date of first issue: 04/18/2017

Print Date 06/25/2020

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P391 Collect spillage.

Storage:

Not available

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	90 - 100
Glass, oxide, chemicals	65997-17-3	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Treat symptomatically.
 Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
Date of first issue: 04/18/2017

Print Date 06/25/2020

- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Halogenated compounds
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.1	05/15/2019	400001009653	Date of first issue: 04/18/2017

Print Date 06/25/2020

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Ensure adequate ventilation.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 36 - 104 °F / 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines
Recommended Filter type:
Combined particulates and organic vapour type

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
Date of first issue: 04/18/2017

Print Date 06/25/2020

- Filter type : Filter type A-P
- Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
- Hand protection
 - Material : butyl-rubber
 - Material : Ethyl Vinyl Alcohol Laminate (EVAL)
 - Break through time : > 8 h
- Material : Nitrile rubber
- Break through time : 10 - 480 min
- Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Colour : black
- Odour : slight
- Odour Threshold : No data is available on the product itself.

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.1	05/15/2019	400001009653	Date of first issue: 04/18/2017

Print Date 06/25/2020

pH	:	ca. 7 (68 °F / 20 °C) Concentration: 500 g/l
Freezing point	:	No data is available on the product itself.
Melting point	:	No data is available on the product itself.
Boiling point	:	> 392 °F / > 200 °C
Flash point	:	392 °F / 200 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data is available on the product itself.
Flammability (solid, gas)	:	No data is available on the product itself.
Flammability (liquids)	:	No data is available on the product itself.
Upper explosion limit / Upper flammability limit	:	No data is available on the product itself.
Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Vapour pressure	:	ca. 0.01 hPa (68 °F / 20 °C)
Relative vapour density	:	No data is available on the product itself.
Relative density	:	No data is available on the product itself.
Density	:	ca. 1.16 g/cm ³ (77 °F / 25 °C)
Solubility(ies)	:	
Water solubility	:	practically insoluble (68 °F / 20 °C)
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	No data is available on the product itself.
Auto-ignition temperature	:	No data is available on the product itself.
Decomposition temperature	:	> 392 °F / > 200 °C
Self-Accelerating decomposition temperature (SADT)	:	No data is available on the product itself.
Viscosity	:	No data is available on the product itself.
Explosive properties	:	No data is available on the product itself.
Oxidizing properties	:	No data is available on the product itself.
Particle size	:	No data is available on the product itself.

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
 Date of first issue: 04/18/2017

Print Date 06/25/2020

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.
 No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : None known.

Incompatible materials : None known.

Hazardous decomposition products : carbon dioxide
 carbon monoxide
 Halogenated compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Acute oral toxicityComponents : LD50 (Rat, female): > 2,000 mg/kg
 Method: OECD Test Guideline 420
 Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Acute dermal toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
 Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Species: Rabbit
 Assessment: Mild skin irritant
 Method: OECD Test Guideline 404
 Result: Irritating to skin.

Glass, oxide, chemicals:
 Species: Rabbit

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.1	05/15/2019	400001009653	Date of first issue: 04/18/2017

Print Date 06/25/2020

Assessment: No skin irritation
 Method: OECD Test Guideline 404
 Result: Normally reversible injuries

Serious eye damage/eye irritation**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Result: Irritating to eyes.

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: Causes sensitisation.

Glass, oxide, chemicals:

Exposure routes: Skin

Species: Other

Result: Does not cause skin sensitisation.

Assessment: No data available

Germ cell mutagenicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Concentration: 0 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Cell type: Germ

Application Route: Oral

Method: OECD Test Guideline 478

Result: negative

Cell type: Somatic

Application Route: Oral

Dose: 0 - 5000 mg/kg

Method: OPPTS 870.5395

Result: negative

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
Date of first issue: 04/18/2017

Print Date 06/25/2020

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1 mg/kg

Frequency of Treatment: 3 days/week

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 1 mg/kg

Frequency of Treatment: 5 days/week

Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - Assessment : No data available

IARC Group 2A: Probably carcinogenic to humans
Glass, oxide, chemicals
(glass)

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: >750 milligram per kilogram

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.1	05/15/2019	400001009653	Date of first issue: 04/18/2017

Print Date 06/25/2020

General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
 General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
 Symptoms: No adverse effects
 Method: OECD Test Guideline 416
 Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development

: Species: Rabbit, female
 Application Route: Dermal
 General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
 Method: Other guidelines
 Result: No teratogenic effects

Species: Rabbit, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level: 60 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Species: Rat, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level: 180 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female
 NOAEL: 50 mg/kg
 Application Route: Ingestion
 Exposure time: 14 Weeks
 Number of exposures: 7 d
 Method: Subchronic toxicity

Species: Rat, male and female
 NOEL: 10 mg/kg

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
Date of first issue: 04/18/2017

Print Date 06/25/2020

Application Route: Skin contact
Exposure time: 13 Weeks
Number of exposures: 5 d
Method: Subchronic toxicity

Species: Mouse, male
NOAEL: 100 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks
Number of exposures: 3 d
Method: Subchronic toxicity

Glass, oxide, chemicals:
Species: Rat, male
LOEC: 2.4 mg/m³
Test atmosphere: dust/mist
Exposure time: 2,160 h
Number of exposures: 6 h
Method: Directive 67/548/EEC, Annex, B.29
Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
 Date of first issue: 04/18/2017

Print Date 06/25/2020

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 203

Glass, oxide, chemicals:
 Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l
 Exposure time: 96 h
 Test Type: Other guidelines
 Test substance: Fresh water
 Method: OECD Test Guideline 203

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: Fresh water

Glass, oxide, chemicals:
 Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
 Exposure time: 72 h
 Test Type: semi-static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
 Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: EPA-660/3-75-009

Glass, oxide, chemicals:
 Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 1,000 mg/l
 Exposure time: 72 h
 Test Type: semi-static test
 Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic) : No data available

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
Date of first issue: 04/18/2017

toxicity)

Print Date 06/25/2020

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
 Date of first issue: 04/18/2017

Print Date 06/25/2020

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Stability in water : Degradation half life(DT50): 4.83 d (77 °F / 25 °C) pH: 4
 Method: OECD Test Guideline 111
 Remarks: Fresh water

Degradation half life(DT50): 7.1 d (77 °F / 25 °C) pH: 9
 Method: OECD Test Guideline 111
 Remarks: Fresh water

Degradation half life(DT50): 3.58 d (77 °F / 25 °C) pH: 7
 Method: OECD Test Guideline 111
 Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
 Remarks: Does not bioaccumulate.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Partition coefficient: n-octanol/water : log Pow: 3.242 (77 °F / 25 °C)
 pH: 7.1
 Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

ARALDITE® 2031-1 RESIN

Version 1.1	Revision Date: 05/15/2019	SDS Number: 400001009653	Date of last issue: 04/18/2017 Date of first issue: 04/18/2017
----------------	------------------------------	-----------------------------	---

Print Date 06/25/2020

Distribution among environmental compartments : Koc: 445
Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Can be landfilled or incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal or incineration.
Send to a licensed waste management company.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 04/18/2017
1.1	05/15/2019	400001009653	Date of first issue: 04/18/2017

Print Date 06/25/2020

Dispose of as unused product.
Do not re-use empty containers.

Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA**

UN/ID No.	: UN 3082
Proper shipping name	: Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 964
Packing instruction (passenger aircraft)	: 964
Environmentally hazardous	: yes

IMDG

UN number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**DOT Classification**

UN/ID/NA number	: UN 3082
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
 Date of first issue: 04/18/2017

Print Date 06/25/2020

Marine pollutant : yes(BISPHENOL A EPOXY RESIN)
 Remarks : Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act**

SARA 311/312 Hazards : Skin corrosion or irritation
 Serious eye damage or eye irritation
 Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

The components of this product are reported in the following inventories:

CH INV : The formulation contains substances listed on the Swiss Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 05/15/2019 SDS Number: 400001009653 Date of last issue: 04/18/2017
 Date of first issue: 04/18/2017

Print Date 06/25/2020

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 05/15/2019

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.1	05/15/2019	400001009653	04/18/2017
			Date of first issue: 04/18/2017

Print Date 06/25/2020

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SDS_US-AM – EN – 400001009653

19 / 19



1-800-375-0605
Option 8 for 24/7 Service



6550 Oley Speaks Way
Canal Winchester, OH 43110



www.RudolphBros.Com
RBCsupport@RudBro.Com