



Dynasolve™ M-35

Uncured Epoxy Flushing Solvent



Dynasolve M-35 is a formulated solvent which is used for flushing uncured epoxy in a broad range of applications. It is also very effective at removing cured cyanoacrylate adhesives.

CLEANING APPLICATIONS:

Flushing epoxy metering and mixing equipment
Removal of cyanoacrylate adhesives from parts

ADVANTAGES:

More efficient than acetone, MEK & other solvents
Noncorrosive and has a low vapor pressure
High flash point
Can be used at room temperature
High loading capacity allows for reuse and reduced cost of ownership

SPECIFICATIONS:

Specific gravity:	1.20
Boiling point:	374°F (190°C)
Flash point:	221°F (105°C)

MATERIALS REMOVED:

Uncured epoxy
Cured cyanoacrylate adhesive

PRODUCT USAGE GUIDELINES

(SEE SDS FOR EH&S INFORMATION)

1. Dynasolve M-35 is typically used at room temperature. Heat to 140°– 170°F (60°– 76°C) for faster results.
2. Flush equipment of uncured epoxy.

MATERIAL COMPATIBILITY:

Recommended materials including:

All metals
Teflon®
Polyethylene & polypropylene

Avoid materials including:

Viton®
PVC
Neoprene



The information contained herein is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto.

Versum and the Versum Materials logo are trademarks of Versum Materials, Inc. © 2017 Versum Materials, Inc.

325-17-051-GLOBAL



1-800-375-0605
Option 8 for 24/7 Service



6550 Oley Speaks Way
Canal Winchester, OH 43110



www.RudolphBros.Com
RBCsupport@RudBro.Com