



Certificate of Analysis

DATE
PAGE

12 September 2016
1 of 1

YOUR ORDER:
DATE OF ORDER:
DELIVERY NOTE:
DELIVERY POSITION:
CUSTOMER NO:

1023672
09/09/2016
87237832
900001
435687

Attention of:
Rudolph Brothers & Co
6550 Oley Speaks Way
Canal Winchester OH 43110-8272

Material: TECHNOMELT PA 7460 PSHT25LB
Known as: LOCTITE HYS SYPAC 7460 25LB EN
Material-No: 420368
Item number: 83308
Batch no: LN6HAA6105
Manufacture date: 08/2016
Use by: 08/2019
Corresponding LMS:
LMS Edition:
Storage Conditions: 46-82F/8-28C
Customer material number 83308

Product Property	Analysis	Specification	Unit of Measure
Appearance COLOR, (EOB) TO STANDARD	OK	-	-
Viscosity Brookfield @ 350 deg.F (BOB)	10162	4000 - 10500	cp
softening point R & B	265	265 - 298	°F
Viscosity Brookfield @ 350 deg.F (EOB)	9100	4000 - 10500	cp

It is hereby certified that, at the time of manufacture, all materials herewith furnished were tested to the appropriate specification requirements - Loctite, military and/or customer.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

*** This certificate was electronically generated based upon Henkel internal controls and does not include a signature. ***