



Safety Data Sheet



Revision Number: 007.0

Issue date: 06/23/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric	IDH number:	199012
Product type/use:	Lubricant	Item number:	76732
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: w ww.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
DANGER:	CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1

PICTOGRAM(S)

Precautionary Statements

Prevention:	Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 60
Graphite	7782-42-5	10 - 30
Calcium oxide	1305-78-8	10 - 30
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	10 - 30
Aluminum not powder, dust or fume	7429-90-5	5 - 10
White mineral oil (petroleum) (not cmr)	8042-47-5	1 - 5
Quartz (SiO2) respirable particulates (RCS) >=10%	14808-60-7	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. HANDLING AND STORAGE

Handling:	Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.
Storage:	Keep in a cool, well ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ TWA Inhalable fraction.	5 mg/m ³ PEL Mist. 500 ppm (2,000 mg/m ³) PEL	None	None
Graphite	2 mg/m ³ TWA Respirable fraction.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust. 5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Calcium oxide	2 mg/m ³ TWA	5 mg/m ³ PEL	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m ³ TWA Inhalable fraction.	5 mg/m ³ PEL Mist. 500 ppm (2,000 mg/m ³) PEL	None	None
Aluminum not powder, dust or fume	1 mg/m ³ TWA Respirable fraction.	None	None	None
White mineral oil (petroleum) (not cmr)	Included in the regulation but with no data values. See regulation for further details Exposure by all routes should be carefully controlled to levels as low as possible. 5 mg/m ³ TWA Inhalable fraction.	5 mg/m ³ PEL Mist.	None	None
Quartz (SiO ₂) respirable particulates (RCS) >=10%	0.025 mg/m ³ TWA Respirable fraction.	0.05 mg/m ³ TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m ³ OSHA_ACT (Respirable dust.) 0.05 mg/m ³ PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable.	None	None

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Paste

Color:

Silver

Odor:

Hydrocarbon-like

Odor threshold:

Not available.

pH:

Not applicable

Vapor pressure:

< 5 mm hg

Boiling point/range:

Not available.

Melting point/ range:

Not available.

Specific gravity:

1.25

IDH number: 199012

Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric
Page 3 of 6

Vapor density:	Not available.
Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 3 %
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents. Acids. Water. Alkalis. Hydrogen fluoride. Phosphorus Compounds.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion



Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.

Skin contact: Causes skin irritation.

Eye contact: Causes serious eye damage.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l	Irritant
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3	Lung
Calcium oxide	Inhalation LC50 (Rat, 4 h) = 40 mg/m3 Inhalation LC50 (Rat, 4 h) = 160 mg/m3	Irritant, Corrosive, Eyes
Petroleum distillates, hydrotreated, light naphthenic	Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = 9.6 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = > 5 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l	Irritant
Aluminum not powder, dust or fume	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l	Central nervous system, Irritant, Lung
White mineral oil (petroleum) (not cmr)	Inhalation LC50 (Rat, 4 h) = > 5 mg/l	No Data
Quartz (SiO2) respirable particulates (RCS) >=10%	None	No Data

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Graphite	No	No	No
Calcium oxide	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
Aluminum not powder, dust or fume	No	No	No
White mineral oil (petroleum) (not cmr)	No	No	No
Quartz (SiO2) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None



International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Immediate Health
CERCLA/SARA Section 313:	None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---------------------------------------------------------------------------------------------------

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,8,11,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/23/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.