

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

SECTION 1. IDENTIFICATION

Product name : EPOCAST® 1636 A US

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980

The Woodlands,
TX 77387

United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : MSDS@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Epoxy constituents

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Skin irritation : Category 2

Serious eye damage : Category 1


Skin sensitisation : Category 1

Acute aquatic toxicity : Category 2

Chronic aquatic toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
 Date of first issue: 08/01/2015

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Storage:

Not available

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
aluminium	7429-90-5	20 - 30
Bisphenol A epoxy resin	25068-38-6	25 - 30
limestone	1317-65-3	10 - 20
Epoxyphenol Novolac Resin	28064-14-4	10 - 20
aluminium hydroxide	21645-51-2	5 - 10
1,4-bis(2,3-epoxypropoxy)butane	2425-79-8	3 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.
If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.

In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

Protect unharmed eye.
Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed : None known.

Notes to physician : No information available.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Hazardous combustion products : No hazardous combustion products are known

Specific extinguishing methods : No data is available on the product itself.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Not applicable for product as supplied.

Environmental precautions : No special environmental precautions required.

Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : For personal protection see section 8.
No special handling advice required.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

Materials to avoid : Strong acids

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
 Date of first issue: 08/01/2015

Strong bases
 Strong oxidizing agents

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
aluminium	7429-90-5	TWA (total dust)	15 mg/m3 (Aluminium)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminium)	OSHA Z-1
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
		TWA (total dust)	15 mg/m3 (Aluminium)	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3 (Aluminium)	OSHA Z-1
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
aluminium hydroxide	21645-51-2	TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH
		TWA (Respirable fraction)	1 mg/m3 (Aluminium)	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Material : butyl-rubber
 Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)
 Material : Nitrile rubber
 Break through time : 10 - 480 min

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

Remarks : For prolonged or repeated contact use protective gloves.

Eye protection : Safety glasses

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : grey

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Melting point/freezing point : No data available

Boiling point/boiling range : No information available.

Flash point : > 137 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : 1.65 - 1.8

Density : 1.73 g/cm³ (25 °C)

Solubility(ies)

Water solubility : practically insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity
Viscosity, dynamic : ca. 38,000 mPa.s

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Molecular weight : No data available

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition products : Carbon oxides
Burning produces noxious and toxic fumes.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate: > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute toxicity (other routes of exposure) : No data available

EPOCAST® 1636 A US

Version 1.1	Revision Date: 10/31/2017	SDS Number: 400001009893	Date of last issue: 08/01/2015 Date of first issue: 08/01/2015
----------------	------------------------------	-----------------------------	---

administration)

Skin corrosion/irritation**Components:**

Bisphenol A epoxy resin:

Species: Rabbit

Assessment: Mild skin irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

Epoxyphenol Novolac Resin:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

Serious eye damage/eye irritation**Components:**

Bisphenol A epoxy resin:

Species: Rabbit

Result: Irritating to eyes.

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

limestone:

Species: Rabbit

Result: Mechanical irritation of the eyes is possible.

Assessment: No eye irritation

Epoxyphenol Novolac Resin:

Species: Rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rabbit

Result: Risk of serious damage to eyes.

Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Assessment:

No data available

Germ cell mutagenicity**Components:**

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

Bisphenol A epoxy resin:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Epoxyphenol Novolac Resin:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Result: positive

Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Result: positive

1,4-bis(2,3-epoxypropoxy)butane:
Genotoxicity in vitro : Concentration: 10 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Concentration: 1 - 100 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive

Components:

Bisphenol A epoxy resin:
Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

Epoxyphenol Novolac Resin:
Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Result: negative

1,4-bis(2,3-epoxypropoxy)butane:
Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

Cell type: Somatic
Application Route: Oral
Exposure time: 4 d
Dose: 187.5 - 750 mg/kg
Method: OECD Test Guideline 474
Result: negative

Test Type: unscheduled DNA synthesis assay
Species: Rat
Cell type: Liver cells
Application Route: Oral
Method: OECD Test Guideline 486
Result: negative

Components:

1,4-bis(2,3-epoxypropoxy)butane:

Germ cell mutagenicity-
Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Germ cell mutagenicity-
Assessment : No data available

Carcinogenicity

Components:

Bisphenol A epoxy resin:
Species: Rat, (male and female)
Application Route: Oral
Exposure time: 24 month(s)
Dose: 15 mg/kg
Frequency of Treatment: 7 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, (male)
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Rat, (female)
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 days/week
Method: OECD Test Guideline 453
Result: negative

Epoxyphenol Novolac Resin:
Species: Rat, (male and female)
Application Route: Oral
Exposure time: 24 month(s)

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

Dose: 15 mg/kg
Frequency of Treatment: 7 daily
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, (male)
Application Route: Dermal
Exposure time: 24 month(s)
Dose: .1 mg/kg
Frequency of Treatment: 3 daily
Method: OECD Test Guideline 453
Result: negative

Species: Rat, (female)
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 daily
Method: OECD Test Guideline 453
Result: negative

Carcinogenicity - Assessment : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

Bisphenol A epoxy resin:
Effects on fertility

: Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: >750 milligram per kilogram
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

Epoxyphenol Novolac Resin:

Species: Rat, male and female
 Application Route: Oral
 Method: OECD Test Guideline 416
 Result: No effects on fertility and early embryonic development were detected.

Components:

Bisphenol A epoxy resin:
 Effects on foetal development

Species: Rabbit, female
 Application Route: Dermal
 General Toxicity Maternal: No observed adverse effect level:
 30 mg/kg body weight
 Method: Other guidelines
 Result: No teratogenic effects

Species: Rabbit, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 60 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Species: Rat, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 180 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Epoxyphenol Novolac Resin:

Species: Rabbit, female
 Application Route: Dermal
 General Toxicity Maternal: No observed adverse effect level:
 30 mg/kg body weight
 Result: No teratogenic effects

Species: Rabbit, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 60 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Species: Rat, female
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 180 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Reproductive toxicity -
 Assessment

: No data available

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

Bisphenol A epoxy resin:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks

Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 3 d

Method: Subchronic toxicity

Epoxyphenol Novolac Resin:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks

Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks

Number of exposures: 3 d

Method: Subchronic toxicity

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

1,4-bis(2,3-epoxypropoxy)butane:

Species: Rat, male and female

NOAEL: 200 mg/kg

Application Route: Ingestion

Exposure time: 28 d

Number of exposures: 7 d

Method: Subacute toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bisphenol A epoxy resin:

Toxicity to fish.

: LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
Exposure time: 96 h
Test Type: static test

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

Test substance: Fresh water
Method: OECD Test Guideline 203

limestone:
Toxicity to fish : LC50: > 56,000 mg/l
Exposure time: 96 h

Epoxyphenol Novolac Resin:
Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

aluminium hydroxide:
Toxicity to fish : LC50: > 10,000 mg/l
Exposure time: 96 h

1,4-bis(2,3-epoxypropoxy)butane:
Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 24 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Components:

Bisphenol A epoxy resin:
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Epoxyphenol Novolac Resin:
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

EC50 (Daphnia magna (Water flea)): 2.7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

aluminium hydroxide:
Toxicity to daphnia and other aquatic invertebrates : EC50: > 10,000 mg/l
Exposure time: 48 h

1,4-bis(2,3-epoxypropoxy)butane:
Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 75 mg/l
Exposure time: 24 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

Components:

Bisphenol A epoxy resin:
Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Epoxyphenol Novolac Resin:
Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water

1,4-bis(2,3-epoxypropoxy)butane:
Toxicity to algae : EL50: > 160 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : No data available

Components:

Epoxyphenol Novolac Resin:
Toxicity to fish (Chronic toxicity) : GLP: yes

Components:

Bisphenol A epoxy resin:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

limestone:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): > 350 mg/l
Exposure time: 125 d
Test Type: semi-static test
Test substance: Fresh water

Epoxyphenol Novolac Resin:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : No data available

Components:

Bisphenol A epoxy resin:

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water

Epoxyphenol Novolac Resin:
 Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water

1,4-bis(2,3-epoxypropoxy)butane:
 Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
 Exposure time: 3 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 209

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment
 Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability**Components:**

Bisphenol A epoxy resin:
 Biodegradability : Inoculum: Sewage (STP effluent)
 Concentration: 20 mg/l
 Result: Not readily biodegradable.
 Biodegradation: 5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

Epoxyphenol Novolac Resin:
 Biodegradability : Inoculum: Sewage (STP effluent)
 Concentration: 20 mg/l
 Result: Not readily biodegradable.
 Biodegradation: 5 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301F

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

1,4-bis(2,3-epoxypropoxy)butane:

Biodegradability : Inoculum: activated sludge
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 43 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

Bisphenol A epoxy resin:

Stability in water : Degradation half life(DT50): 4.83 d (25 °C) pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 7.1 d (25 °C) pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 3.58 d (25 °C) pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Epoxyphenol Novolac Resin:

Stability in water : Degradation half life(DT50): 4.83 d (25 °C) pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 7.1 d (25 °C) pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 3.58 d (25 °C) pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

Bisphenol A epoxy resin:
Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Epoxyphenol Novolac Resin:
Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Components:

Bisphenol A epoxy resin:
Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)
pH: 7.1
Method: OECD Test Guideline 117

limestone:
Partition coefficient: n-octanol/water : log Pow: < 1

Epoxyphenol Novolac Resin:
Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)
pH: 7.1
Method: OECD Test Guideline 117

1,4-bis(2,3-epoxypropoxy)butane:
Partition coefficient: n-octanol/water : log Pow: -0.269 (25 °C)
pH: 6.7
Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Components:

Bisphenol A epoxy resin:
Distribution among environmental compartments : Koc: 445
Epoxyphenol Novolac Resin:
Distribution among environmental compartments : Koc: 445
1,4-bis(2,3-epoxypropoxy)butane:
Distribution among environmental compartments : Koc: 12.59
Method: OECD Test Guideline 121

Stability in soil : No data available

Other adverse effects

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information - Product : There is no data available for this product.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA
UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN, EPOXY PHENOL NOVOLAC RESIN)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo) : 964

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

aircraft)
Packing instruction : 964
(passenger aircraft)

IMDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, EPOXY PHENOL NOVOLAC RESIN)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**DOT Classification**

UN/ID/NA number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(BISPHENOL A EPOXY RESIN, EPOXY PHENOL NOVOLAC RESIN)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(BISPHENOL A EPOXY RESIN, EPOXY PHENOL NOVOLAC RESIN)

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act**

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

SAFETY DATA SHEET



Enriching lives through innovation

EPOCAST® 1636 A US

Version 1.1 Revision Date: 10/31/2017 SDS Number: 400001009893 Date of last issue: 08/01/2015
Date of first issue: 08/01/2015

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

- CH INV : The formulation contains substances listed on the Swiss Inventory, On the inventory, or in compliance with the inventory
- DSL : This product contains one or several components listed in the Canadian NDSL.
- AICS : On the inventory, or in compliance with the inventory
- NZIoC : Not in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS® IV:

HEALTH		3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Revision Date : 10/31/2017

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

EPOCAST® 1636 A US

Version	Revision Date:	SDS Number:	Date of last issue: 08/01/2015
1.1	10/31/2017	400001009893	Date of first issue: 08/01/2015

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1
Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
OSHA Z-1 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

Authorized Distributor



1-800-375-0605 www.rudolphbros.com