

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

SECTION 1. IDENTIFICATION

Product name : ARALDITE® 2051 RESIN

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
 Address : P.O. Box 4980
 The Woodlands,
 TX 77387
 United States of America (USA)
 Telephone : Non-Emergency: (800) 257-5547
 E-mail address of person responsible for the SDS : SDS@huntsman.com
 Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

Authorized Distributor

RUDOLPH

BROS. & CO.
 ADHERING TO QUALITY
 1-800-375-0605 www.rudolphbros.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 2
 Skin irritation : Category 2
 Serious eye damage : Category 1
 Skin sensitisation : Category 1
 Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
 Short-term (acute) aquatic hazard : Category 3
 Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements**: Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 11/17/2018 SDS Number: 400000006586 Date of last issue: -
 Date of first issue: 11/17/2018

Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	50 - 70
methacrylic acid	79-41-4	5 - 10
2,6-di-tert-butyl-p-cresol	128-37-0	1 - 2.5
Silicon, amorphous	7631-86-9	1 - 5
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	14807-96-6	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Consult a physician.
 Show this safety data sheet to the doctor in attendance.
 Treat symptomatically.
 Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
 If on skin, rinse well with water.
 If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
 In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 Continue rinsing eyes during transport to hospital.
 Remove contact lenses.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
 Do NOT induce vomiting.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
 Carbon dioxide (CO₂)

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Dry chemical

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
Sulphur oxides
Hydrogen chloride
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Refer to protective measures listed in sections 7 and 8.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

- Advice on safe handling** : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage** : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Keep in properly labelled containers.
- Materials to avoid** : For incompatible materials please refer to Section 10 of this SDS.
- Recommended storage temperature** : 36 - 46 °F / 2 - 8 °C
- Further information on storage stability** : Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m ³	OSHA Z-1
methacrylic acid	79-41-4	TWA	20 ppm	ACGIH
2,6-di-tert-butyl-p-cresol	128-37-0	TWA (Inhalable fraction and vapor)	2 mg/m ³	ACGIH
Silicon, amorphous	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 11/17/2018 SDS Number: 400000006586 Date of last issue: -
Date of first issue: 11/17/2018

		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : off-white

Odour : like methacrylic acid

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Freezing point	:	No data is available on the product itself.
Melting point	:	No data is available on the product itself.
Boiling point	:	No data is available on the product itself.
Flash point	:	50 °F / 10 °C Method: estimated
Evaporation rate	:	No data is available on the product itself.
Flammability (solid, gas)	:	No data is available on the product itself.
Flammability (liquids)	:	No data is available on the product itself.
Upper explosion limit / Upper flammability limit	:	No data is available on the product itself.
Lower explosion limit / Lower flammability limit	:	No data is available on the product itself.
Vapour pressure	:	No data is available on the product itself.
Relative vapour density	:	No data is available on the product itself.
Relative density	:	No data is available on the product itself.
Density	:	1.02 - 1.05 g/cm3
Solubility(ies)	:	
Water solubility	:	insoluble
Solubility in other solvents	:	No data is available on the product itself.
Partition coefficient: n-octanol/water	:	No data is available on the product itself.
Auto-ignition temperature	:	No data is available on the product itself.
Thermal decomposition	:	No data is available on the product itself.
Self-Accelerating decomposition temperature (SADT)	:	No data is available on the product itself.
Viscosity	:	
Viscosity, dynamic	:	40 - 70 Pas
Explosive properties	:	No data is available on the product itself.
Oxidizing properties	:	No data is available on the product itself.
Particle size	:	No data is available on the product itself.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	None known.
Hazardous decomposition products	:	carbon dioxide carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity - Product : Acute toxicity estimate: 39.02 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity - Product : Acute toxicity estimate : 4,111 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Components:**

methyl methacrylate:
Species: Rabbit
Method: OPPTS 870.2500
Result: Skin irritation

methacrylic acid:
Species: Rabbit
Method: OECD Test Guideline 404
Result: Extremely corrosive and destructive to tissue.

2,6-di-tert-butyl-p-cresol:
Species: Rabbit
Assessment: No skin irritation

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Result: slight irritation

Silicon, amorphous:

Species: Rabbit

Assessment: No skin irritation

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation**Components:**

methacrylic acid:

Species: Rabbit

Result: Irreversible effects on the eye

2,6-di-tert-butyl-p-cresol:

Species: Rabbit

Assessment: No eye irritation

Silicon, amorphous:

Species: Rabbit

Result: No eye irritation

Assessment: No eye irritation

Method: OECD Test Guideline 405

Respiratory or skin sensitisation**Components:**

methyl methacrylate:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

methacrylic acid:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

2,6-di-tert-butyl-p-cresol:

Exposure routes: Skin

Species: Humans

Result: Does not cause skin sensitisation.

Assessment: No data available

Germ cell mutagenicity**Components:**

methyl methacrylate:

Genotoxicity in vitro

: Test Type: Microbial mutagenesis assay (Ames test)

Test system: Salmonella typhimurium

Method: OECD Test Guideline 471

Authorized Distributor

RUDOLPH

BROS. & CO.
 ADHERING TO QUALITY



1-800-375-0605 www.rudolphbros.com

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Result: negative

methacrylic acid:
Genotoxicity in vitro

: Concentration: 33 - 4000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

2,6-di-tert-butyl-p-cresol:
Genotoxicity in vitro

: Metabolic activation: with and without metabolic activation
Result: negative

Metabolic activation: Metabolic activation
Result: negative

Concentration: 100 - 1000 ug/plate
Metabolic activation: with and without metabolic activation
Result: negative

Silicon, amorphous:
Genotoxicity in vitro

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Components:

methacrylic acid:
Genotoxicity in vivo

: Cell type: Somatic
Application Route: Inhalation
Exposure time: 2 h
Dose: 100 - 1000 ppm
Method: OECD Test Guideline 475
Result: Not classified due to inconclusive data.

Application Route: Inhalation
Exposure time: 6 h
Dose: 100 - 9000 ppm
Method: OECD Test Guideline 478
Result: negative

2,6-di-tert-butyl-p-cresol:
Genotoxicity in vivo

: Application Route: Intraperitoneal injection
Dose: 75 mg/kg
Result: negative

Application Route: Oral
Exposure time: 9 Months
Dose: ca 750 mg/kg

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 11/17/2018 SDS Number: 400000006586 Date of last issue: -
Date of first issue: 11/17/2018

Result: negative

Silicon, amorphous:
Genotoxicity in vivo : Application Route: Inhalation
Dose: 50 mg/m3
Result: negative

Carcinogenicity**Components:**

methyl methacrylate:
Species: Rat, male and female
Application Route: Oral
Exposure time: 2 Years
Dose: 6, 60, 2000 ppm
Frequency of Treatment: once daily
NOAEL: 90.3 mg/kg bw/day

Result: negative

methacrylic acid:
Species: Rat, male and female
Application Route: Inhalation
Exposure time: 24 month(s)
Dose: 250 - 1000 ppm
Frequency of Treatment: 5 daily
Method: OECD Test Guideline 453
Result: negative

Species: Rat, male and female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 12 - 3300 ppm
Frequency of Treatment: 7 daily
Result: negative

2,6-di-tert-butyl-p-cresol:
Species: Rat, male and female
Application Route: Oral
Result: negative
Target Organs: Liver

Silicon, amorphous:
Species: Rat, male and female
Application Route: Oral
Exposure time: 103 weeks
Dose: 1800 - 3200 mg/kg
Frequency of Treatment: 7 daily
Method: OECD Test Guideline 453
Result: negative

Carcinogenicity - Assessment : No data available

IARC

No component of this product present at levels greater than or

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

Known to be human carcinogen
Talc (Mg₃H₂(SiO₃)₄)
(Silica, Crystalline (Respirable Size))

Reproductive toxicity**Components:**

methacrylic acid:
Effects on fertility

: Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: 0, 50, 150, 400 milligram per kilogram
Fertility: No observed adverse effect level F1: 400 mg/kg body weight
Symptoms: Reduced body weight
Method: OPPTS 870.3800

2,6-di-tert-butyl-p-cresol:

Species: Rat, male and female
Application Route: Oral
Result: negative

Components:

methyl methacrylate:
Effects on foetal
development

: Species: Rat
Application Route: Inhalation
Dose: 99, 304, 1178 ppm
Teratogenicity: No observed adverse effect concentration F1: 8,300 mg/m³
Embryo-foetal toxicity: No observed adverse effect concentration F1: 8,300 mg/m³
Method: OECD Test Guideline 414
Result: No teratogenic effects

methacrylic acid:

Test Type: Pre-natal
Species: Rat, male and female
Application Route: Inhalation
Dose: 200, 300 ppm
Embryo-foetal toxicity: No observed adverse effect concentration F1: 300 ppm
Method: OECD Test Guideline 414
Result: No effects on fertility and early embryonic development were detected.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Test Type: Pre-natal
 Species: Rabbit, male and female
 Application Route: Oral
 Dose: 50, 150, 450 milligram per kilogram
 General Toxicity Maternal: No observed adverse effect level:
 50 mg/kg body weight
 Developmental Toxicity: No observed adverse effect level F1:
 450 mg/kg body weight
 Result: No effects on fertility and early embryonic
 development were detected.

2,6-di-tert-butyl-p-cresol:

Species: Rat
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 100 mg/kg body weight
 Result: No teratogenic effects

Silicon, amorphous:

Species: Mouse
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 1,340 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Species: Rabbit
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 1,600 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Species: Rat
 Application Route: Oral
 General Toxicity Maternal: No observed adverse effect level:
 1,350 mg/kg body weight
 Method: OECD Test Guideline 414
 Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

Components:

methyl methacrylate:
 Exposure routes: Inhalation
 Target Organs: Respiratory Tract
 Assessment: May cause respiratory irritation.

methacrylic acid:
 Target Organs: Respiratory system
 Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

methyl methacrylate:

Species: Rat, male and female

NOAEL: 124.1 mg/kg

Application Route: oral (drinking water)

Exposure time: 2 years

Number of exposures: daily

Dose: 6, 60, 2000 ppm

methacrylic acid:

Species: Rat, male and female

NOEC: 500 ppm

Test atmosphere: vapour

Exposure time: 2 yr

Number of exposures: 5 d

Method: OECD Test Guideline 453

2,6-di-tert-butyl-p-cresol:

Species: Rat, male and female

NOAEL: 25 mg/kg/d

Application Route: Ingestion

Method: Chronic toxicity

Silicon, amorphous:

Species: Rat, male and female

NOAEL: 7950 - 8980 mg/kg

Application Route: Ingestion

Exposure time: 4,320 h

Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEC: 4000 - 4500 mg/m3

Application Route: Ingestion

Test atmosphere: dust/mist

Exposure time: 13 Weeks

Number of exposures: 7 d

Method: OECD Test Guideline 413

Repeated dose toxicity - : No data available
Assessment

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information**Product:**

Remarks: Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:**

methyl methacrylate:

Toxicity to fish

: LC50: 191 mg/l
Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: Fish Early-life Stage Toxicity Test

methacrylic acid:

Toxicity to fish

: LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l
Exposure time: 96 h

Test Type: flow-through test

Test substance: Fresh water

Method: Fish Acute Toxicity Test

Remarks: Toxic to aquatic organisms.

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Silicon, amorphous:
 Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

Talc (Mg₃H₂(SiO₃)₄):
 Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l
 Exposure time: 24 h

Components:

methyl methacrylate:
 Toxicity to daphnia and other aquatic invertebrates : EC50: 69 mg/l
 Exposure time: 48 h

methacrylic acid:
 Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 130 mg/l
 Exposure time: 48 h
 Test Type: flow-through test
 Test substance: Fresh water
 Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids

2,6-di-tert-butyl-p-cresol:
 Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.61 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

Silicon, amorphous:
 Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l
 Exposure time: 24 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 202

Components:

methyl methacrylate:
 Toxicity to algae : EC50: > 110 mg/l
 Exposure time: 72 h

methacrylic acid:
 Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 45 mg/l
 Exposure time: 72 h
 Test Type: static test
 Test substance: Fresh water
 Method: OECD Test Guideline 201

2,6-di-tert-butyl-p-cresol:
 Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 0.4 mg/l
 Exposure time: 72 h
 Test Type: static test

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Method: Directive 67/548/EEC, Annex V, C.3.

Silicon, amorphous:
Toxicity to algae

: EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Components:

2,6-di-tert-butyl-p-cresol:
M-Factor (Acute aquatic toxicity) : 1

Components:

methacrylic acid:
Toxicity to fish (Chronic toxicity) : NOEC (Brachydanio rerio (zebrafish)): 10 mg/l
Exposure time: 35 d
Test Type: flow-through test
Test substance: Fresh water
Method: OECD Test Guideline 210

2,6-di-tert-butyl-p-cresol:
Toxicity to fish (Chronic toxicity) : LC0 (Brachydanio rerio (zebrafish)): >= 0.57 mg/l
Exposure time: 96 hrs
Test Type: semi-static test
Method: Directive 67/548/EEC, Annex V, C.1.

Components:

methyl methacrylate:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 37 mg/l
Exposure time: 21 d
Test Type: flow-through test
Method: OECD Test Guideline 211

methacrylic acid:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 53 mg/l
Exposure time: 21 d
Test Type: flow-through test
Test substance: Fresh water
Method: OECD Test Guideline 211

2,6-di-tert-butyl-p-cresol:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.32 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 202

EC0 (Daphnia magna (Water flea)): >= 0.31 mg/l
Exposure time: 48 hrs
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.2.

NOEC (Daphnia magna (Water flea)): 0.23 mg/l

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Exposure time: 48 hrs
 Test Type: static test
 Method: OECD Test Guideline 202

NOEC (Daphnia magna (Water flea)): 0.316 mg/l
 Exposure time: 21 d
 Test Type: semi-static test
 Method: OECD Test Guideline 202

M-Factor (Chronic aquatic toxicity) : No data available

Components:

methacrylic acid:

Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l
 Exposure time: 17 h
 Test Type: static test
 Test substance: Fresh water
 Method: DIN 38 412 Part 8

2,6-di-tert-butyl-p-cresol:

Toxicity to microorganisms : IC50 (activated sludge): > 500 mg/l
 Exposure time: 0.5 h
 Method: Directive 67/548/EEC, Annex V, C.11

: EC50 (activated sludge): > 10,000 mg/l
 Exposure time: 3 h
 Test Type: static test
 Method: Directive 67/548/EEC, Annex, B.15

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment
 Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability**Components:**

methyl methacrylate:

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

methacrylic acid:
Biodegradability : Inoculum: activated sludge
Concentration: 3 mg/l
Result: Readily biodegradable.
Biodegradation: 86 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

2,6-di-tert-butyl-p-cresol:
Biodegradability : Inoculum: activated sludge
Result: Inherently biodegradable.
Biodegradation: 5.2 %
Exposure time: 112 d

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Stability in water : No data available

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

methyl methacrylate:
Bioaccumulation : Bioconcentration factor (BCF): 3

2,6-di-tert-butyl-p-cresol:
Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 330 - 1,800
Exposure time: 28 d
Method: flow-through test

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

Components:

methyl methacrylate:
Partition coefficient: n-octanol/water : log Pow: 1.38

methacrylic acid:
Partition coefficient: n-octanol/water : log Pow: 0.93 (72 °F / 22 °C)
pH: 2.2

2,6-di-tert-butyl-p-cresol:
Partition coefficient: n-octanol/water : log Pow: 5.1

Mobility in soil

Mobility : No data available

Components:

2,6-di-tert-butyl-p-cresol:
Distribution among environmental compartments : Koc: 8183
Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA**

UN/ID No.	: UN 1133
Proper shipping name	: Adhesives
Class	: 3
Packing group	: II
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 364
Packing instruction (passenger aircraft)	: 353

IMDG

UN number	: UN 1133
Proper shipping name	: ADHESIVES
Class	: 3
Packing group	: II
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**DOT Classification**

ARALDITE® 2051 RESIN

Version Revision Date: SDS Number: Date of last issue: -
 1.0 11/17/2018 400000006586 Date of first issue: 11/17/2018

UN/ID/NA number : UN 1133
 Proper shipping name : ADHESIVES

 Class : 3
 Packing group : II
 Labels : FLAMMABLE LIQUID
 ERG Code : 128
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
alpha,alpha-dimethylbenzyl hydroperoxide	80-15-9	10	1388
methyl methacrylate	80-62-6	1000	1767
1,1,2-trichloroethane	79-00-5	100	*
hydroquinone	123-31-9	100	*
p-cresol	106-44-5	100	*
cumene	98-82-8	5000	*
acetophenone	98-86-2	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Serious eye damage or eye irritation
 Respiratory or skin sensitisation
 Specific target organ toxicity (single or repeated exposure)
 Skin corrosion or irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

methyl methacrylate 80-62-6 >= 50 - < 70 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

methyl methacrylate 80-62-6

California Prop. 65

WARNING: This product can expose you to chemicals including 1,1,2-trichloroethane, cumene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

ARALDITE® 2051 RESIN

Version 1.0 Revision Date: 11/17/2018 SDS Number: 400000006586 Date of last issue: -
 Date of first issue: 11/17/2018

- CH INV : The formulation contains substances listed on the Swiss Inventory, On the inventory, or in compliance with the inventory
- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- NZIoC : On the inventory, or in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

- Revision Date : 11/17/2018
- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1
Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3
Mineral Dusts

ARALDITE® 2051 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	11/17/2018	400000006586	Date of first issue: 11/17/2018

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour
workday during a 40-hour workweek
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.



ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	400000001213	Date of first issue: 01/12/2016

SECTION 1. IDENTIFICATION

Product name : ARALDITE® 2051 HARDENER

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
 Address : P.O. Box 4980
 The Woodlands,
 TX 77387
 United States of America

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS : MSDS@huntsman.com

Emergency telephone : Chemtrec: (800) 424-9300 or (703) 527-3887



Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Skin sensitization : Category 1

Specific target organ systemic toxicity - single exposure : Category 3 (Respiratory system)

Acute aquatic toxicity : Category 3

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.
 H402 Harmful to aquatic life.

ARALDITE® 2051 HARDENER

Version 1.1 Revision Date: 01/21/2016 SDS Number: 400000001213 Date of last issue: 01/12/2016
 Date of first issue: 01/12/2016

Precautionary Statements : **Prevention:**
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
 P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 21.5 %

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
methyl methacrylate	80-62-6	60 - 100
3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine	34562-31-7	3 - 7

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Consult a physician.

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	400000001213	Date of first issue: 01/12/2016

- Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
- In case of eye contact : Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not use a solid water stream as it may scatter and spread fire.
- Hazardous combustion products : No data is available on the product itself.
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Use water spray to cool unopened containers. For safety reasons in case of fire, cans should be stored separately in closed containments.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	400000001213	Date of first issue: 01/12/2016

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Avoid formation of aerosol. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Container may be opened only under exhaust ventilation hood.
- Conditions for safe storage : No smoking.
Store in cool place.
Keep in a well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.
- Recommended storage temperature : 2 - 8 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH

ARALDITE® 2051 HARDENER

Version 1.1 Revision Date: 01/21/2016 SDS Number: 40000001213 Date of last issue: 01/12/2016
 Date of first issue: 01/12/2016

		TWA	100 ppm 410 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	100 ppm 410 mg/m3	OSHA PEL

Personal protective equipment

- Respiratory protection : In the case of vapor formation use a respirator with an approved filter.
- Hand protection
Remarks : Solvent-resistant gloves
The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.
Before removing gloves clean them with soap and water.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles.
- Skin and body protection : impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : yellow
- Odor : like acrylic
- Odor Threshold : No data is available on the product itself.
- pH : No data is available on the product itself.
- Flash point : 10 °C
- Evaporation rate : No data is available on the product itself.
- Flammability (solid, gas) : No data is available on the product itself.
- Upper explosion limit : No data is available on the product itself.
- Lower explosion limit : No data is available on the product itself.
- Vapor pressure : No data is available on the product itself.

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	400000001213	Date of first issue: 01/12/2016

Relative vapor density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 0.94 - 0.95 g/cm³ (23 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Autoignition temperature : No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Viscosity

Viscosity, dynamic : 30,000 - 55,000 mPa.s (20 °C)
thixotropic

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable under recommended storage conditions.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : Stable under recommended storage conditions.
No decomposition if used as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Ingredients:

methyl methacrylate:

Acute inhalation toxicity : LC50 (Rat, male and female): 29.8 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Directive 67/548/EEC, Annex V, B.2.

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	400000001213	Date of first issue: 01/12/2016

Ingredients:

methyl methacrylate:
 Acute dermal toxicity : LD50 (Rabbit, male): > 5,000 mg/kg
 Method: OECD Test Guideline 402

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Ingredients:**

3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine:
 Assessment: Irritating to skin.
 Result: Irritating to skin.

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization**Ingredients:**

methyl methacrylate:
 Routes of exposure: Skin
 Species: Mouse
 Assessment: May cause sensitization by skin contact.
 Method: OECD Test Guideline 429
 Result: Causes sensitization.

Assessment: No data available

Germ cell mutagenicity

Genotoxicity in vitro : No data available

Genotoxicity in vivo : No data available

Carcinogenicity

No data available

Carcinogenicity - Assessment : No data available

IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	400000001213	Date of first issue: 01/12/2016

by NTP.

Reproductive toxicity

Effects on fertility : No data available

Effects on fetal development : No data available

Reproductive toxicity - Assessment : No data available

STOT-single exposure

Ingredients:

methyl methacrylate:
Routes of exposure: Inhalation
Target Organs: Respiratory Tract
Assessment: May cause respiratory irritation.

STOT-repeated exposure

No data available

Repeated dose toxicity

No data available

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available



ARALDITE® 2051 HARDENER

Version 1.1	Revision Date: 01/21/2016	SDS Number: 400000001213	Date of last issue: 01/12/2016 Date of first issue: 01/12/2016
----------------	------------------------------	-----------------------------	---

Further information**Product:**

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:**

methyl methacrylate:
Toxicity to fish : LC50: 191 mg/l
Exposure time: 96 h

Ingredients:

methyl methacrylate:
Toxicity to daphnia and other : EC50: 69 mg/l
aquatic invertebrates Exposure time: 48 h

Ingredients:

methyl methacrylate:
Toxicity to algae : IC50: > 110 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic toxicity) : No data available

Toxicity to daphnia and other : No data available
aquatic invertebrates
(Chronic toxicity)

M-Factor (Chronic aquatic toxicity) : No data available

Toxicity to bacteria : No data available

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment
Acute aquatic toxicity : No data available

ARALDITE® 2051 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 01/12/2016
1.1	01/21/2016	40000001213	Date of first issue: 01/12/2016

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Further information

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 21.5 %

Persistence and degradability**Ingredients:**

methyl methacrylate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: > 60 %
Exposure time: 28 d

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Stability in water : No data available

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Ingredients:**

methyl methacrylate:

Bioaccumulation : Bioconcentration factor (BCF): 3

Ingredients:

methyl methacrylate:

Partition coefficient: n-octanol/water : log Pow: 1.38

ARALDITE® 2051 HARDENER

Version 1.1	Revision Date: 01/21/2016	SDS Number: 40000001213	Date of last issue: 01/12/2016 Date of first issue: 01/12/2016
----------------	------------------------------	----------------------------	---

Mobility in soil

Mobility : No data available

Distribution among environmental compartments : No data available

Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layerOzone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
SubstancesRemarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information - Product : There is no data available for this product.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Offer surplus and non-recyclable solutions to a licensed
disposal company.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

ARALDITE® 2051 HARDENER

Version 1.1 Revision Date: 01/21/2016 SDS Number: 400000001213 Date of last issue: 01/12/2016
 Date of first issue: 01/12/2016

SECTION 14. TRANSPORT INFORMATION

International Regulation

IATA

UN/ID No. : UN 1247
 Proper shipping name : Methyl methacrylate monomer, stabilized
 Class : 3
 Packing group : II
 Labels : Flammable Liquids
 Packing instruction (cargo aircraft) : 364
 Packing instruction (passenger aircraft) : 353

IMDG

UN number : UN 1247
 Proper shipping name : METHYL METHACRYLATE MONOMER, STABILIZED
 Class : 3
 Packing group : II
 Labels : 3
 EmS Code : F-E, S-D
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

DOT Classification

UN/ID/NA number : UN 1247
 Proper shipping name : METHYL METHACRYLATE MONOMER, STABILIZED
 Class : 3
 Packing group : II
 Labels : FLAMMABLE LIQUID
 ERG Code : 129P
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

TSCA - 5(a) Significant New Use Rule List of Chemicals : Not relevant

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ	Calculated product RQ
-------------	---------	--------------	-----------------------

ARALDITE® 2051 HARDENER

Version 1.1 Revision Date: 01/21/2016 SDS Number: 400000001213 Date of last issue: 01/12/2016
 Date of first issue: 01/12/2016

		(lbs)	(lbs)
METHYL METHACRYLATE	80-62-6	1000	1409

SARA 311/312 Hazards : Fire Hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

methyl methacrylate 80-62-6 70.95 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

methyl methacrylate 80-62-6 70.95 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

California Prop 65 This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

The ingredients of this product are reported in the following inventories:

- CH INV : The mixture contains substances listed on the Swiss Inventory
- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- NZIoC : not determined
- ENCS : Not in compliance with the inventory
- ISHL : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory


ARALDITE® 2051 HARDENER

Version 1.1 Revision Date: 01/21/2016 SDS Number: 400000001213 Date of last issue: 01/12/2016
 Date of first issue: 01/12/2016

SECTION 16. OTHER INFORMATION

Further information

NFPA:



HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Revision Date : 01/21/2016

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE. THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

