







www.rudolphbros.com rbcsupport@rudbro.com

SAFETY DATA SHEET

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2053-15 A

Version 1.0

Revision Date: SDS Number: 06/03/2021 400000011046 Date of last issue: -

Date of first issue: 06/03/2021

Print Date 06/28/2021

SECTION 1. IDENTIFICATION

Product name : ARALDITE® 2053-15 A

Manufacturer or supplier's details

Company name of supplier

: Huntsman Advanced Materials Americas LLC P.O. Box 4980

Address

Telephone

The Woodlands,

TX 77387 United States of America (USA) : Non-Emergency: (800) 257-5547

E-mail address of person

: Global Product EHS AdMat@huntsman.com

responsible for the SDS

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Resin

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitisation : Category 1

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

Short-term (acute) aquatic

hazard

: Category 3

Chronic aquatic toxicity : Category 3

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.



Enriching lives through innovation

ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

Date of first issue: 06/03/2021 06/03/2021 400000011046 1.0

Print Date 06/28/2021

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eve damage.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eve protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air

and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

		PIIII Date 00/20/2021
Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	50 - 70
silica, amorphous, fumed, crystalline free	7631-86-9	5 - 10
methacrylic acid	79-41-4	5 - 10
octadecyl methacrylate	32360-05-7	1 - 5
hexadecyl methacrylate	2495-27-4	1 - 5
calcium carbonate	471-34-1	1 - 5
zinc oxide	1314-13-2	1 - 5
Talc (Mg3H2(SiO3)4)	14807-96-6	0.1 - 1
2,2'-[(4-methylphenyl)imino]bisethanol	3077-12-1	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with

difficulty.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

None known.

SDS_US-AM - EN - 400000011046



Enriching lives through innovation

ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

Avoid inhalation, ingestion and contact with skin and eyes. No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

Exercise caution when using a high volume water jet as it may

scatter and spread fire

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

Carbon oxides

Specific extinguishing

methods

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Neutralize with chalk, alkali solution or ammonia.
 Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion

Do not spray on a naked flame or any incandescent material.

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Use only with

Use only with adequate ventilation/personal protection.

Provide sufficient air exchange and/or exhaust in work rooms.

For personal protection see section 8. Keep container closed when not in use.

Avoid formation of aerosol.

Do not breathe vapours or spray mist.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Keep in properly labelled containers.

Materials to avoid : Keep away from strong bases.

Recommended storage

temperature

36 - 46 °F / 2 - 8 °C

Further information on

storage stability

: Stable under normal conditions.

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control	Basis
	07.10.110.	(Form of	parameters /	
		exposure)	Permissible	
			concentration	
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm	OSHA Z-1
			410 mg/m3	
		TWA	100 ppm 410 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA P0
silica, amorphous, fumed,	7631-86-9	TWA (Dust)	20 Million	OSHA Z-3
crystalline free			particles per cubic	
			foot	
			(Silica)	
		TWA (Dust)	80 mg/m3 /	OSHA Z-3
			%SiO2	
		T10/0	(Silica)	NICOLLEGE
		TWA	6 mg/m3 (Silica)	NIOSH REL
methacrylic acid	79-41-4	TWA	20 ppm	ACGIH
		TWA	20 ppm	NIOSH REL
			70 mg/m3	00114 50
		TWA	20 ppm 70 mg/m3	OSHA P0
zinc oxide	1314-13-2	TWA	2 mg/m3	ACGIH
		(Respirable		
		particulate		
		matter)	10 / 0	400111
		STEL	10 mg/m3	ACGIH
		(Respirable		
		particulate		
		matter) TWA	5 mg/m3	OSHA Z-1
		(Fumes)	3 mg/m3	0311A Z-1
		TWA (total	15 mg/m3	OSHA Z-1
		dust)	15 mg/ms	0011/4 2-1
		TWA	5 mg/m3	OSHA Z-1
		(respirable	Jg	
		fraction)		
		TWA (Dust)	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	NIOSH REL
		(Fumes)		
		ST (Fumes)	10 mg/m3	NIOSH REL
		C (Dust)	15 mg/m3	NIOSH REL
		TWA (Total	10 mg/m3	OSHA P0
		dust)		
		TWA	5 mg/m3	OSHA P0
		(respirable		
		dust fraction)		

SDS_US-AM - EN - 400000011046



Enriching lives through innovation

ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

			Print Date	e 06/28/2021
		TWA (Fumes)	5 mg/m3	OSHA P0
		STEL	10 mg/m3	OSHA P0
calcium carbonate	471-34-1	(Fumes) TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Talc (Mg3H2(SiO3)4)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : Ensure adequate ventilation.

Suitable respiratory equipment: Respirator with a half face mask Recommended Filter type:

Combined particulates and organic vapour type

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : Filter type A-P2 (organic vapours, particles)

Hand protection

Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of

contact).

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Colour : beige

Odour : acrylic-like

Odour Threshold : No data is available on the product itself.

pH : 4

Concentration: 500 g/l

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : 50 °F / 10 °C

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.04 g/cm3 (77 °F / 25 °C)

Solubility(ies)

Water solubility : insoluble, immiscible

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Self-Accelerating

decomposition temperature

(SADT)

No data is available on the product itself.

Viscosity

Viscosity, dynamic : 59,000 mPa.s (77 °F / 25 °C)

Explosive properties No data is available on the product itself.

Oxidizing properties No data is available on the product itself.

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability Stable under normal conditions.

Possibility of hazardous

reactions

Vapours may form explosive mixture with air.

Conditions to avoid Heat, flames and sparks.

Incompatible materials None known.

Hazardous decomposition

products

carbon dioxide carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : No data is available on the product itself.

exposure

Acute toxicity

: Acute toxicity estimate : > 5,000 mg/kg Acute oral toxicity - Product

Method: Calculation method

Acute inhalation toxicity -

Product

Acute toxicity estimate: 44.08 mg/l

Exposure time: 4 h

Test atmosphere: vapour

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

06/03/2021 40000011046 Date of first issue: 06/03/2021 1.0

Print Date 06/28/2021

Method: Calculation method

Acute dermal toxicity -

: Acute toxicity estimate : > 5,000 mg/kg

Product

Method: Calculation method

Acute toxicity (other routes of : No data available

administration)

Skin corrosion/irritation

Components:

methyl methacrylate: Species: Rabbit

Method: OPPTS 870.2500 Result: Skin irritation

silica, amorphous, fumed, crystalline free:

Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

methacrylic acid: Species: Rabbit

Assessment: Causes severe burns. Method: OECD Test Guideline 404

Result: Extremely corrosive and destructive to tissue.

GLP: yes

octadecyl methacrylate: Result: Skin irritation

hexadecyl methacrylate: Result: Skin irritation

calcium carbonate: Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

zinc oxide: Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

2,2'-[(4-methylphenyl)imino]bisethanol:

Species: Rabbit

Assessment: No skin irritation Method: Other guidelines Result: No skin irritation

GLP: no



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Serious eye damage/eye irritation

Components:

silica, amorphous, fumed, crystalline free:

Species: Rabbit
Result: No eye irritation
Assessment: No eye irritation
Method: OECD Test Guideline 405

methacrylic acid: Species: Rabbit

Result: Irreversible effects on the eye

Assessment: Risk of serious damage to eyes.

Method: Draize Test

GLP: no

octadecyl methacrylate: Result: Eye irritation

hexadecyl methacrylate: Result: Eye irritation

calcium carbonate:
Species: Rabbit
Result: No eye irritation
Assessment: No eye irritation

Method: OECD Test Guideline 405

zinc oxide: Species: Rabbit Result: No eye irritation

Assessment: No eye irritation
Method: OECD Test Guideline 405

2,2'-[(4-methylphenyl)imino]bisethanol:

Species: Rabbit

Result: Risk of serious damage to eyes. Assessment: Risk of serious damage to eyes.

Method: OECD Test Guideline 405

GLP: no

Respiratory or skin sensitisation

Components:

methyl methacrylate: Exposure routes: Skin Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

methacrylic acid:

Test Type: Buehler Test Exposure routes: Skin Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

octadecyl methacrylate: Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.

hexadecyl methacrylate: Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.

zinc oxide:

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406 Result: Does not cause skin sensitisation.

2,2'-[(4-methylphenyl)imino]bisethanol: Test Type: Local lymph node assay (LLNA)

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Assessment: No data available

Germ cell mutagenicity

Components:

methyl methacrylate:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)

Test system: Salmonella typhimurium Method: OECD Test Guideline 471

Result: negative

silica, amorphous, fumed, crystalline free:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

methacrylic acid:

Genotoxicity in vitro : Test Type: reverse mutation assay

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

octadecyl methacrylate:

Genotoxicity in vitro : Concentration: .1 - 1200 μg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Concentration: 33 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Concentration: 14.5 - 2233 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

hexadecyl methacrylate:

Genotoxicity in vitro : Concentration: .1 - 1200 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Concentration: 33 - 5000 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Concentration: 14.5 - 2233 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

calcium carbonate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Concentration: 0 - 250 µg/L

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

zinc oxide:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella tryphimurium and E. coli

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster lung cells

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

GLP: yes

Test Type: Micronucleus test

Metabolic activation: without metabolic activation

Method: OECD Test Guideline 487

Result: negative

2,2'-[(4-methylphenyl)imino]bisethanol:

Genotoxicity in vitro : Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: no

Test Type: Chromosome aberration test in vitro

Test system: Human lymphocytes

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Components:

silica, amorphous, fumed, crystalline free:

Genotoxicity in vivo : Application Route: Inhalation

Dose: 50 mg/m3 Result: negative

methacrylic acid:

Genotoxicity in vivo : Test Type: in vivo assay

Species: Rat (male) Cell type: Somatic

Application Route: Inhalation

Exposure time: 2 h

Dose: 0.4, 1.6, 2.8 and 4 mg/L Method: OECD Test Guideline 475

Result: Not classified due to inconclusive data.

GLP: no

Test Type: dominant lethal test Species: Mouse (male)

Application Route: Inhalation

Exposure time: 6 h



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Dose: 0.405, 4.05 and 36.45 mg/L Method: OECD Test Guideline 478

Result: negative

GLP: no

octadecyl methacrylate:

Genotoxicity in vivo : Application Route: Oral

Exposure time: 72 h Dose: 5000 mg/kg

Method: OECD Test Guideline 474

Result: negative

hexadecyl methacrylate:

Genotoxicity in vivo : Application Route: Oral

Exposure time: 72 h Dose: 5000 mg/kg

Method: OECD Test Guideline 474

Result: negative

zinc oxide:

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse (male) Cell type: Bone marrow

Application Route: Intraperitoneal injection

Dose: 15, 30 and 60 mg/kg bw Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-

Assessment

: No data available

Carcinogenicity

Components:

methyl methacrylate:

Species: Rat, male and female Application Route: Oral Exposure time: 2 Years Dose: 6, 60, 2000 ppm

Frequency of Treatment: once daily

NOAEL: 90.3 mg/kg bw/day

Result: negative

silica, amorphous, fumed, crystalline free:

Species: Rat, male and female Application Route: Oral Exposure time: 103 weeks Dose: 1800 - 3200 mg/kg Frequency of Treatment: 7 daily

Method: OECD Test Guideline 453 Result: negative

methacrylic acid:

Species: Rat, male and female Application Route: inhalation (vapour)

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Exposure time: 102 weeks

Frequency of Treatment: 5 days/week NOAEL: >= 2.05 mg/kg body weight

Method: OECD Test Guideline 451

Species: Mouse, male and female Application Route: inhalation (vapour)

Exposure time: 102 weeks Dose: ca. 2.05 and 4.1 mg/L

Frequency of Treatment: 5 days/week

LOAEL: ca. 2.05 mg/l

Method: OECD Test Guideline 451

zinc oxide:

Species: Mouse, male and female

Application Route: Oral Exposure time: 1 year

Dose: 1000 and 5000 ppm Zinc Frequency of Treatment: daily

NOAEL: > 22,000 mg/kg body weight

Remarks: Information given is based on data obtained from similar substances.

Carcinogenicity - : No data available

Assessment

IARC Group 1: Carcinogenic to humans

Talc (Mg3H2(SiO3)4)

ACGIH Confirmed human carcinogen

Talc (Mg3H2(SiO3)4)

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP Known to be human carcinogen

Talc (Mg3H2(SiO3)4)

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Components:

methacrylic acid:

Effects on fertility : Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 150, 450 mg/kg/day

General Toxicity - Parent: No observed adverse effect level:

50 mg/kg body weight

Fertility: No observed adverse effect level F1: 400 mg/kg body

weight

Symptoms: Reduced body weight Method: OECD Test Guideline 416

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

GLP: yes

octadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

Dose: >= 1000 milligram per kilogram Frequency of Treatment: 7 days/week Method: OECD Test Guideline 422

Result: negative

Species: Rat, male and female

Application Route: Oral

Dose: 400 milligram per kilogram Frequency of Treatment: 7 days/week Method: OECD Test Guideline 416

Result: negative

hexadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

Dose: >=1000 milligram per kilogram Frequency of Treatment: 7 days/week Method: OECD Test Guideline 422

Result: negative

Species: Rat, male and female

Application Route: Oral

Frequency of Treatment: 7 days/week Method: OECD Test Guideline 416

Result: negative

zinc oxide:

Test Type: Two-generation study Species: Rat, male and female

Application Route: Oral Dose: 7.5/15/30 mg/kg bw/day

General Toxicity - Parent: Lowest observed adverse effect

level: 7.5 mg/kg body weight

General Toxicity F1: No observed adverse effect level: 15

mg/kg body weight

Method: OECD Test Guideline 416

Remarks: Information given is based on data obtained from

similar substances.

Components:

methyl methacrylate:

Effects on foetal development

Species: Rat

Application Route: Inhalation Dose: 99, 304, 1178 ppm

Teratogenicity: No observed adverse effect concentration F1:

8,300 mg/m³

Embryo-foetal toxicity: No observed adverse effect

concentration F1: 8,300 mg/m³ Method: OECD Test Guideline 414 Result: No teratogenic effects

SDS_US-AM - EN - 400000011046



Enriching lives through innovation

ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

silica, amorphous, fumed, crystalline free:

Species: Mouse Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,340 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rabbit Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,600 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

Species: Rat

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,350 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

methacrylic acid:

Test Type: Pre-natal Species: Rat, female

Application Route: Inhalation
Dose: 0, 50, 100, 200 or 300 ppm
Duration of Single Treatment: 14 d
Frequency of Treatment: 7 days/week

General Toxicity Maternal: No observed adverse effect level:

200 ppm

Developmental Toxicity: No observed adverse effect level: >=

300 ppm

Embryo-foetal toxicity: No observed adverse effect

concentration F1: 300 ppm

Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

Test Type: Pre-natal

Species: Rabbit, male and female

Application Route: Oral

Dose: 50, 150, 450 milligram per kilogram Duration of Single Treatment: 23 d Frequency of Treatment: 7 days/week

General Toxicity Maternal: No observed adverse effect level:

50 mg/kg body weight

Developmental Toxicity: No observed adverse effect level F1:

450 mg/kg body weight

Result: No effects on fertility and early embryonic

development were detected.

octadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

SDS_US-AM - EN - 400000011046



Enriching lives through innovation

ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

1,000 mg/kg body weight

Method: OECD Test Guideline 422 Result: No teratogenic effects

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

100 ppm

Method: OECD Test Guideline 414 Result: No teratogenic effects

hexadecyl methacrylate:

Species: Rat, male and female

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

1,000 mg/kg body weight

Method: OECD Test Guideline 422 Result: No teratogenic effects

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

100 ppm

Method: OECD Test Guideline 414 Result: No teratogenic effects

zinc oxide:

Test Type: Pre-natal

Species: Rat

Application Route: inhalation (dust/mist/fume)

Dose: 0.3/1.5/7.5 mg/m3

Duration of Single Treatment: 6 h

General Toxicity Maternal: No observed adverse effect

concentration: 1.5 mg/m³

Developmental Toxicity: No observed adverse effect

concentration: 7.5 mg/m³

Method: OECD Test Guideline 414 Result: No teratogenic effects

2,2'-[(4-methylphenyl)imino]bisethanol:

Test Type: Pre-natal Species: Rat, females Application Route: Oral

Dose: 60/200/600 milligram per kilogram Duration of Single Treatment: 15 d

General Toxicity Maternal: No observed adverse effect level:

200 mg/kg body weight

Developmental Toxicity: No observed adverse effect level: >=

600 mg/kg body weight

Method: OECD Test Guideline 414

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Reproductive toxicity -

Assessment

: No data available

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

STOT - single exposure

Components:

methyl methacrylate: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

methacrylic acid:

Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with respiratory tract irritation.

octadecyl methacrylate: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

hexadecyl methacrylate: Exposure routes: Inhalation Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

methyl methacrylate:

Species: Rat, male and female

NOAEL: 124.1 mg/kg

Application Route: oral (drinking water)

Exposure time: 2 years Number of exposures: daily Dose: 6, 60, 2000 ppm

silica, amorphous, fumed, crystalline free:

Species: Rat, male and female NOAEL: 7950 - 8980 mg/kg Application Route: Ingestion Exposure time: 4,320 h Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female NOEC: 4000 - 4500 mg/m3 Application Route: Ingestion

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Test atmosphere: dust/mist Exposure time: 13 Weeks Number of exposures: 7 d

Method: OECD Test Guideline 413

methacrylic acid:

Species: Rat, male and female NOEC: 352 - 1232 mg/m3

Application Route: inhalation (vapour)

Test atmosphere: vapour Exposure time: 90 d Number of exposures: 6 h Dose: 70/352/1232 mg/m3

Subsequent observation period: 5 days/week

Method: OECD Test Guideline 413

GLP: yes

octadecyl methacrylate:

Species: Rat, male and female

NOAEL: 1000 mg/kg

Application Route: Ingestion Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female

NOAEL: 120 mg/kg

Application Route: Ingestion Exposure time: 2,160 h Number of exposures: 7 d Method: Subchronic toxicity

hexadecyl methacrylate:

Species: Rat, male and female

NOAEL: 1000 mg/kg

Application Route: Ingestion Number of exposures: 7 d Method: Subchronic toxicity

Species: Rat, male and female

NOAEL: 120 mg/kg

Application Route: Ingestion Exposure time: 2,160 h Number of exposures: 7 d Method: Subchronic toxicity

zinc oxide:

Species: Mouse, male and female

NOEL: 3000 ppm

Application Route: Ingestion Exposure time: 13 Weeks Number of exposures: 7 d Method: Subchronic toxicity

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Remarks: Information given is based on data obtained from similar substances.

Species: Rat, male

Application Route: inhalation (dust/mist/fume)

Exposure time: 13 weeks 6 h Number of exposures: 5 days/week Dose: 0.3, 1.5 and 4.5 mg/m3 Method: OECD Test Guideline 413

GLP: yes

Species: Rat, male and female

LOAEL: 75 mg/kg

Application Route: Dermal Exposure time: 28 days 6 h

Number of exposures: 5 days/week Dose: 0, 75, 180, and 360 mg/kg bw/d

2,2'-[(4-methylphenyl)imino]bisethanol:

Species: Rat, male and female

NOAEL: 100 mg/kg Application Route: Oral Exposure time: 28 d Number of exposures: daily

Dose: 100/300/600/1000 mg/kg bw/day Method: OECD Test Guideline 407

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Repeated dose toxicity -

Assessment

: No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Neurological effects

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

methyl methacrylate:

Toxicity to fish : LC50: 191 mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): > 79 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: Fish Early-life Stage Toxicity Test

silica, amorphous, fumed, crystalline free:

Toxicity to fish : LL50 (Brachydanio rerio (zebrafish)): > 10,000 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

methacrylic acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 85 mg/l

End point: mortality Exposure time: 96 h

Test Type: flow-through test Test substance: Fresh water Method: Fish Acute Toxicity Test

GLP: yes

Remarks: Toxic to aquatic organisms.

calcium carbonate:

Toxicity to fish : LC50: > 56,000 mg/l

Exposure time: 96 h

Talc (Mg3H2(SiO3)4):

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100 mg/l

Exposure time: 24 h

2,2'-[(4-methylphenyl)imino]bisethanol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

End point: mortality Exposure time: 96 h Test Type: static test Analytical monitoring: yes

SDS_US-AM - EN - 400000011046

HUNTSM*i*

Enriching lives through innovation

ARALDITE® 2053-15 A

Version **Revision Date:** SDS Number: Date of last issue: -

06/03/2021 40000011046 Date of first issue: 06/03/2021 1.0

Print Date 06/28/2021

Test substance: Fresh water Method: OECD Test Guideline 203

GLP: ves

Remarks: Based on data from similar materials

Components:

methyl methacrylate:

Toxicity to daphnia and other : EC50: 69 mg/l aquatic invertebrates Exposure time: 48 h

silica, amorphous, fumed, crystalline free:

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): >= 1,000 mg/l

Exposure time: 24 h Test Type: static test Test substance: Fresh water

Method: OECD Test Guideline 202

methacrylic acid:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 130 mg/l

End point: Immobilization Exposure time: 48 h Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water

Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater

Daphnids GLP: yes

2,2'-[(4-methylphenyl)imino]bisethanol:

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 48 mg/l

End point: Immobilization Exposure time: 48 h Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 202

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Components:

methyl methacrylate:

Toxicity to algae/aquatic : EC50: > 110 mg/l plants Exposure time: 72 h

silica, amorphous, fumed, crystalline free:

Toxicity to algae/aquatic

plants

: EL50 (Desmodesmus subspicatus (green algae)): > 10,000

mg/l

Exposure time: 72 h Test Type: static test Test substance: Fresh water Method: OECD Test Guideline 201

methacrylic acid:

Toxicity to algae/aquatic : ErC50 (Selenastrum capricornutum (green algae)): 45 mg/l

SDS US-AM - EN - 400000011046



Enriching lives through innovation

ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

plants Exposure time: 72 h

Test Type: static test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 201

GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 8.2 mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

2,2'-[(4-methylphenyl)imino]bisethanol:

Toxicity to algae/aquatic plants

: EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: ves

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h
Test Type: static test
Analytical monitoring: yes
Test substance: Fresh water
Method: OECD Test Guideline 201

GLP: yes

Remarks: Based on data from similar materials

Components:

zinc oxide:

M-Factor (Acute aquatic

toxicity)

: 1

Components:

methacrylic acid:

Toxicity to fish (Chronic

toxicity)

: NOEC (Brachydanio rerio (zebrafish)): 10 mg/l

Exposure time: 35 d

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 210

GLP: yes

Components:

methyl methacrylate:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 37 mg/l

aquatic invertebrates Exposure time: 21 d

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

(Chronic toxicity) Test Type: flow-through test

Method: OECD Test Guideline 211

methacrylic acid:

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 53 mg/l

Exposure time: 21 d

Test Type: flow-through test Analytical monitoring: yes Test substance: Fresh water Method: OECD Test Guideline 211

GLP: yes

Components:

zinc oxide:

M-Factor (Chronic aquatic

toxicity)

Components:

methacrylic acid:

Toxicity to microorganisms : EC50 (Pseudomonas putida): 270 mg/l

: 1

Exposure time: 16.5 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: DIN 38 412 Part 8

GLP: yes

2,2'-[(4-methylphenyl)imino]bisethanol:

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h
Test Type: static test
Analytical monitoring: no
Test substance: Fresh water
Method: OECD Test Guideline 209

GLP: yes

Remarks: Information given is based on data obtained from

similar substances.

Toxicity to soil dwelling

organisms

: No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial

organisms

: No data available

Ecotoxicology Assessment

Components:

zinc oxide:

Acute aquatic toxicity : Very toxic to aquatic life.

Components:

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

zinc oxide:

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

Persistence and degradability

Components:

methyl methacrylate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 60 % Exposure time: 28 d

methacrylic acid:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Concentration: 3 mg/l

Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 28 d

Method: OECD Test Guideline 301D

GLP: yes

2,2'-[(4-methylphenyl)imino]bisethanol:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge, non-adapted

Concentration: 18 mg/l Result: Not biodegradable Biodegradation: 1.5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: ves

Remarks: Based on data from similar materials

Biochemical Oxygen

Demand (BOD)

: No data available

Chemical Oxygen Demand

(COD)

: No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon

(DOC)

: No data available

Physico-chemical

removability

: No data available

SDS_US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Stability in water : No data available

Photodegradation : No data available

Impact on Sewage

Treatment

: No data available

Bioaccumulative potential

Components:

methyl methacrylate:

Bioaccumulation : Bioconcentration factor (BCF): 3

Components:

methyl methacrylate:

Partition coefficient: n-

: log Pow: 1.38

octanol/water

methacrylic acid:

Partition coefficient: n- : log Pow: 0.93 (72 °F / 22 °C)

octanol/water pH: 2.2

hexadecyl methacrylate:

Partition coefficient: n- : log Pow: 8.64 octanol/water : Method: QSAR

GLP: no

2,2'-[(4-methylphenyl)imino]bisethanol:

Partition coefficient: n- : log Pow: 2 (95 °F / 35 °C)

octanol/water pH: 7

Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

Distribution among

: No data available

environmental compartments

Stability in soil : No data available

Other adverse effects

Environmental fate and

: No data available

pathways

Results of PBT and vPvB

assessment

: No data available

Endocrine disrupting

potential

: No data available

Adsorbed organic bound

halogens (AOX)

: No data available

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Revision Date: Date of last issue: -Version SDS Number:

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Global warming potential

(GWP)

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA

UN/ID No. : UN 1133 : Adhesives Proper shipping name

Class 3 Packing group : 11

: Flammable Liquids Labels

Packing instruction (cargo

aircraft)

Packing instruction : 353

(passenger aircraft)

364

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

IMDG

UN number : UN 1133
Proper shipping name : ADHESIVES

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

DOT Classification

UN/ID/NA number : UN 1133
Proper shipping name : ADHESIVES

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
methyl methacrylate	80-62-6	1000	1939
hydroquinone	123-31-9	100	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Respiratory or skin sensitisation Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

methyl methacrylate 80-62-6 >= 50 - < 70 %

SDS US-AM - EN - 400000011046



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -

1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

zinc oxide 1314-13-2 >= 1 - < 5 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

methyl methacrylate 80-62-6

California Prop. 65

WARNING: This product can expose you to chemicals including Talc (Mg3H2(SiO3)4), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not

on the Canadian DSL nor NDSL.

AIIC : Not in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Notified. Allowed to be imported / manufactured only by the

notifiers. Please contact your Huntsman sales representative

for more information.

TCSI : On the inventory, or in compliance with the inventory

TSCA : On or in compliance with the active portion of the TSCA

inventory

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

1-800-375-0605



ARALDITE® 2053-15 A

Version Revision Date: SDS Number: Date of last issue: -


1.0 06/03/2021 400000011046 Date of first issue: 06/03/2021

Print Date 06/28/2021

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 06/03/2021

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3

Mineral Dusts

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA P0 / TWA : 8-hour time weighted average OSHA P0 / STEL : Short-term exposure limit OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.



ARALDITE® 2053-15 A

Version

1.0

Revision Date: 06/03/2021

SDS Number: 400000011046

Date of last issue: -

Date of first issue: 06/03/2021

Print Date 06/28/2021

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SDS_US-AM - EN - 400000011046

33 / 33





1-800-375-0605 Option 8 for 24/7 Service



6550 Oley Speaks Way Canal Winchester, OH 43110



www.rudolphbros.com rbcsupport@rudbro.com