

RUST-OLEUM®
HIGH PERFORMANCE
 INDUSTRIAL COATINGS

2300 SYSTEM INVERTED STRIPING PAINT

DESCRIPTION AND USES

Rust-Oleum® High Performance Inverted Striping Paint is a lead-free aerosol paint that features weather and abrasion resistance for durability. When used with one of the Rust-Oleum Striping Machines, these coatings are ideal for striping parking lots and warehouse aisles. They dry fast and adhere to concrete, pavement, gravel, grass and more.

PRODUCTS

DESCRIPTION	SKU
Red	2364838
Blue	2326838
Black	2378838
Yellow	2348838
White	2391838
Safety Green	362971
Safety Orange	362972

PACKAGING

20 fl. oz. container, 18 oz. fill wt., 6 aerosols packed to a carton

PRODUCT APPLICATION

SURFACE PREPARATION

ALL SURFACES: Remove loose debris and contaminants by sweeping the surface before application of the coating. Grease, oil and chemical contaminants are best removed by washing the surface with Krud Kutter® Original Cleaner Degreaser, commercial detergent, or other suitable cleaner. Rinse thoroughly with clean fresh water and allow to fully dry.

PRODUCT APPLICATION

APPLICATION

Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. The Inverted Striping sprays are designed for use with Rust-Oleum Striping Machine item #2395000. Follow machine directions for proper use.

The width of the stripe can be varied from 2-4 inches wide by adjusting the position of the can holder on the Striping Machine. For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping.

If clogging occurs, carefully remove spray tip and clean in thinner. DO NOT insert any object into can valve opening. Use care when replacing the spray tip. The inverted striping aerosols can also be used with the #2388000 Striping Wand.

DISPOSAL

Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled.

AEROSOLS	TECHNICAL DATA	RO-02
RUST-OLEUM[®] HIGH PERFORMANCE INDUSTRIAL COATINGS	2300 SYSTEM INVERTED STRIPING PAINT	

PHYSICAL PROPERTIES

		INVERTED STRIPING PAINT
Resin Type		Vinyl Toluene Modified Alkyd
Pigment Type		Varies with color
Solvents		Xylene and Toluene
Solids	By Weight	31-41%
	By Volume	—
MIR		Maximum value of 0.85
Fill Weight		18 oz. (510 g)
Recommended Dry Film Thickness (DFT) Per Coat		1.0-2.0 mils (25-50 μ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		275-300 ft. @ 3" wide using 2348838 Yellow Coverage is dependent on surface porosity
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Tack-free	<10 minutes
	Handle	30 minutes
	Recoat	Anytime
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Safety Information		THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. FOR INDUSTRIAL OR COMMERCIAL USE ONLY. SEE THE SAFETY DATA SHEET (SDS) AND LABEL WARNINGS FOR ADDITIONAL SAFETY INFORMATION.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061

Phone: 877-385-8155
www.rustoleum.com/industrial

Form: GDH-1089
Rev.: 081020