



SAFETY DATA SHEET
- US



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

SECTION 1. IDENTIFICATION

Product name : Surface Enhancer 360

Manufacturer or supplier's details

Company name of supplier : Chem-Trend LP
1445 W McPherson Park Dr
PO Box 860, Howell MI 48844-0860
United States
+1 517 546 4520

E-mail address of person responsible for the SDS : SDS-NA@chemtrend.com
Emergency telephone number : +1 517 545 7070

Recommended use of the chemical and restrictions on use

Recommended use : Processing aid
Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)
Specific target organ toxicity - repeated exposure (Inhalation) : Category 2 (Central nervous system)
Aspiration hazard : Category 1

GHS label elements

Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Hazard pictograms :



Signal word :

Danger

Hazard statements :

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of damaging fertility or the unborn child.
May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Precautionary statements :

Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe mist.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
Do NOT induce vomiting.

Storage:

Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated	64742-49-0	Trade secret (>= 30 - < 60)



Surface Enhancer 360

Version 1.0 Revision Date: 02/09/2023 Date of last issue: -
Date of first issue: 02/09/2023 Print Date: 03/03/2023

light		
Acetone	67-64-1	Trade secret ($\geq 10 - < 30$)
Propane	74-98-6	Trade secret ($\geq 5 - < 10$)
Butane	106-97-8	Trade secret ($\geq 5 - < 10$)
Isobutane	75-28-5	Trade secret ($\geq 1 - < 5$)
Pentane	109-66-0	Trade secret ($\geq 1 - < 5$)
n-hexane	110-54-3	Trade secret ($\geq 1 - < 5$)

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
Wash off with soap and plenty of water.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.
Aspiration may cause pulmonary oedema and pneumonitis.
- Notes to physician : Treat symptomatically.



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Advice on safe handling : Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. For personal protection see section 8. Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the application area. Wash hands and face before breaks and immediately after handling the product. Do not get in eyes or mouth or on skin. Do not get on skin or clothing. Do not use sparking tools. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA	500 ppm 2,000 mg/m3	OSHA Z-1 (2007-01-01)
		TWA (Mist)	5 mg/m3	OSHA Z-1 (2018-03-15)
		TWA (Mist)	5 mg/m3	NIOSH REL (2019-10-04)
		ST (Mist)	10 mg/m3	NIOSH REL (2019-10-04)
Acetone	67-64-1	TWA	250 ppm	ACGIH (2021-01-01)
		STEL	500 ppm	ACGIH (2021-01-01)
		TWA	250 ppm 590 mg/m3	NIOSH REL (2013-10-08)
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1 (1997-08-04)
Propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL (2013-10-08)



Surface Enhancer 360

Version 1.0 Revision Date: 02/09/2023 Date of last issue: -
Date of first issue: 02/09/2023

Print Date:
03/03/2023

		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1 (1997-08-04)
Butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL (2013-10-08)
		STEL	1,000 ppm	ACGIH (2018-03-20)
Isobutane	75-28-5	TWA	800 ppm 1,900 mg/m3	NIOSH REL (2013-10-08)
		STEL	1,000 ppm	ACGIH (2018-03-20)
Pentane	109-66-0	TWA	120 ppm 350 mg/m3	NIOSH REL (2013-10-08)
		C	610 ppm 1,800 mg/m3	NIOSH REL (2013-10-08)
		TWA	1,000 ppm 2,950 mg/m3	OSHA Z-1 (1997-08-04)
		TWA	1,000 ppm	ACGIH (2014-03-01)
n-hexane	110-54-3	TWA	50 ppm	ACGIH (2007-01-01)
		TWA	50 ppm 180 mg/m3	NIOSH REL (2013-10-08)
		TWA	500 ppm 1,800 mg/m3	OSHA Z-1 (1997-08-04)

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI (2017-03-01)
n-hexane	110-54-3	2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI (2020-02-01)

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Short term only
Combination filter:



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Filter type : Filter type A-P

Hand protection

Remarks : Protective gloves The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : colourless

Odour : mild

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -0.40 °F / -18 °C

Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Method: closed cup

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	12.8 %(V) (68 °F / 20 °C)
Lower explosion limit / Lower flammability limit	:	0.8 %(V) (68 °F / 20 °C)
Vapour pressure	:	4,825.87 hPa (68 °F / 20 °C)
Relative vapour density	:	No data available
Relative density	:	0.69 (68 °F / 20 °C) Reference substance: Water The value is calculated
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available

SECTION 10. STABILITY AND REACTIVITY



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:
Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder, Dizziness, Drowsiness, Vomiting,
Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Propane:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Butane:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Isobutane:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Pentane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

n-hexane:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259.35 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Naphtha (petroleum), hydrotreated light:

Result : Skin irritation

Acetone:

Result : Repeated exposure may cause skin dryness or cracking.

n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Components:

Acetone:

Species : Rabbit
Result : Eye irritation

n-hexane:

Species : Rabbit
Result : No eye irritation
Assessment : No eye irritation
Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

n-hexane:

Species : Mouse
Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

IARC OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

n-hexane:

Reproductive toxicity - Assessment : - Fertility -
Suspected human reproductive toxicant

STOT - single exposure

Components:

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Acetone:

Exposure routes : Inhalation
Assessment : May cause drowsiness or dizziness.

Pentane:

Assessment : May cause drowsiness or dizziness.

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

n-hexane:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Repeated dose toxicity

Product:



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Pentane:

May be fatal if swallowed and enters airways.

n-hexane:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish :
Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates :
Remarks: No data available

Toxicity to algae/aquatic plants :
Remarks: No data available

Toxicity to microorganisms :
Remarks: No data available



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Components:

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Pentane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.26 mg/l
End point: mortality
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
Exposure time: 48 h

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12.51 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 21.85 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 9.285 mg/l
Exposure time: 72 h

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: rapidly biodegradable



Surface Enhancer 360

Version 1.0 Revision Date: 02/09/2023 Date of last issue: -
Date of first issue: 02/09/2023

Print Date:
03/03/2023

Acetone:

Biodegradability : Result: Readily biodegradable.

Propane:

Biodegradability : Result: Biodegradable

Butane:

Biodegradability : Result: rapidly biodegradable

Isobutane:

Biodegradability : Result: Biodegradable

Pentane:

Biodegradability : Result: Readily biodegradable.

n-hexane:

Biodegradability : aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 21 %
Exposure time: 28 d
GLP: yes

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Partition coefficient: n-octanol/water : Remarks: No data available

Acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0.2

Propane:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : Pow: 2.36

Butane:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : Pow: 2.89

Isobutane:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-octanol/water : Pow: 2.76

Pentane:

Bioaccumulation : Bioconcentration factor (BCF): 171

n-hexane:

Bioaccumulation : Bioconcentration factor (BCF): 501.19

Partition coefficient: n-octanol/water : log Pow: 4 (68 °F / 20 °C)
pH: 7



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1

Surface Enhancer 360

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/09/2023	Date of first issue: 02/09/2023	03/03/2023

Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1950
Proper shipping name : Aerosols

Class : 2.1
Packing group : Not assigned by regulation
Labels : FLAMMABLE GAS
ERG Code : 126
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation
Aspiration hazard



Surface Enhancer 360

Version 1.0	Revision Date: 02/09/2023	Date of last issue: - Date of first issue: 02/09/2023	Print Date: 03/03/2023
----------------	------------------------------	--	---------------------------

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

n-hexane	110-54-3	>= 1 - < 5 %
----------	----------	--------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

n-hexane	110-54-3	>= 1 - < 5 %
----------	----------	--------------

California Prop. 65

WARNING: This product can expose you to chemicals including n-hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average

AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -

Surface Enhancer 360

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/09/2023	Date of first issue: 02/09/2023	03/03/2023

Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/09/2023

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.



Surface Enhancer 360

Version	Revision Date:	Date of last issue: -	Print Date:
1.0	02/09/2023	Date of first issue: 02/09/2023	03/03/2023

