

BONDERITE®**BONDERITE L-FM F 737 ACHESON
FORMING LUBRICANT
(KNOWN AS MULTAN F 737)**

Authorized Distributor



1-800-375-0605 www.rudolphbros.com

Issued 6/6/2013

Product Description

BONDERITE L-FM F 737 ACHESON (known as MULTAN F 737) is a water soluble synthetic fluid designed for use on light to medium forming applications. It is ideal for applications currently using a high VOC vanishing oil. These applications could include light stamping, punching or piercing. This material is suitable for use on all metal types including pre-painted substrates. BONDERITE L-FM F 737 ACHESON (known as MULTAN F 737) is meant to be used as received.

Benefits

- Eliminate high VOC products for improved environmental compliance.
- Remaining film is slightly waxy in consistency which removes easily in most cleaning systems.
- Can be used on steel, galvanized, stainless, aluminum, copper or brass substrates.
- Applied via most common ways including spraying, flooding, roll coating or hand application.
- No further mixing stations required.

Characteristics

Typical concentration range: 100%

Appearance: Light amber fluid

Viscosity (cP @ RT): 13

pH of concentrate: 8.2-8.4

Weight (lbs/gal): 8.3

Chlorine: No

Health, Environment & Safety

Please follow all applicable Federal, state and local regulations regarding proper disposal of this product. Please consult the Material Safety Data Sheet for more detail on the safe handling of this product.

Integrated Equipment Solutions

Henkel offers a full range of equipment solutions, including refractometers, proportioners, oil coalescers, automated control systems, titration chemicals and bulk tanks.

Additional Information

For more detail on this product, or Henkel's capabilities contact your local account representative or the phone number below.

Henkel Corporation | 32100 Stephenson Highway | Madison Heights, MI 48071
PHONE: (248) 583-9300 | FAX: (248) 583-2976 | www.henkelna.com/

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

