


1-800-375-0605 Option 8 for 24/7 Service



Safety Data Sheet



Revision Number: 003.6 Issue date: 04/04/2022

PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-MRB-200 SEMI IDH number: 1620730

SYNTHETIC COOLANT known as

MULTAN B-200

Product type/use: Lubricant Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 Region: United States Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW CAUSES SKIN IRRITATION.

DANGER:

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE DAMAGE.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several Response:

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Take

off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

4 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s) CAS Number Percentage' IDH number: 1620730

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 30
Dicyclohexylamine	101-83-7	1 - 5
Oleylamidoethyleneoxyethanol	Proprietary	5 - 10
Boric acid (H3BO3), compd. w ith 2-(2-aminoethoxy)	124756-59-8	1 - 5
Amine borate	Proprietary	1 - 5
Diglycol amine	929-06-6	1 - 5
Monoethanolamine	141-43-5	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

4. FIRST AID MEASURES

If inhaled, immediately remove the affected person to fresh air. If symptoms Inhalation:

develop and persist, get medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

In case of contact with the eyes, rinse immediately with plenty of water for 15 Eye contact:

minutes, and seek immediate medical attention.

Ingestion: Get medical attention. DO NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to a victim who is

unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: This material, if aspirated into the lungs, may cause chemical pneumonitis;

treat the affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

This product is an aqueous mixture and although it will exhibit a flash point, it Unusual fire or explosion hazards:

will not support combustion.

Hazardous combustion products: Upon decomposition, this product emits oxides of sulfur, carbon monoxide,

carbon dioxide and/or low molecular w eight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sew er or waterways.

Absorb spill with inert material. Shovel material into appropriate container for Clean-up methods:

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Avoid breathing vapors or mists of this product. For industrial use only. Do not

mix this product with fluids which contain NITRITES/NITRATES.

NITROSAMINE may be formed.

Storage: Not available.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

IDH number: 1620730 Product name: BONDERITE L-MR B-200 SEMI SYNTHETIC COOLANT known as MULTAN B-200

Page 2 of 5







8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Dicyclohexylamine	None	None None		None
Oleylamidoethyleneoxyethanol	None	None	None	None
Boric acid (H3BO3), compd. w ith 2-(2-aminoethoxy)	None	None None		None
Amine borate	None	None	None	None
Diglycol amine	None	None	None	None
Monoethanolamine	6 ppm STEL 3 ppm TWA	3 ppm (6 mg/m3) PEL	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If mist is generated (heating, spraying) and engineering controls are not

sufficient, wear approved organic vapor respirator suitable for oil mist.

Eye/face protection: Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:AmberOdor:AmineOdor threshold:Not available.pH:9.5 - 10.5Vapor pressure:Not determined

Boiling point/range: > 98.8 °C (> 209.8 °F)calculated

Melting point/ range: Not applicable Specific gravity: 1.00 - 1.01 Vapor density: Not determined Flash point: Not determined Flam mable/Explosive limits - lower: Not applicable Flam mable/Explosive limits - upper: Not applicable Autoignition temperature: Not applicable Not applicable Flam mability: Evaporation rate: Not applicable Solubility in water: Complete Partition coefficient (n-octanol/water): Not determined Not determined VOC content: Viscosity: 100 mPa.s Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decompositionUpon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

products: molecular w eight hydrocarbons. Oxides of nitrogen. Oxides of sulfur.

Incompatible materials: This product may react with strong acids or oxidizing agents. Nitrites may react with organic

amines to form nitrosamines which can cause cancer.

Reactivity: Not available.

Conditions to avoid: Keep aw ay fromheat, ignition sources and incompatible materials.

IDH number: 1620730 Product name: BONDERITE L-MR B-200 SEMI SYNTHETIC COOLANT know n as MULTAN B-200

Page 3 of 5







11. TOXICOLOGICAL INFORMATION

Skin, Inhalation, Eyes, Ingestion Relevant routes of exposure:

Potential Health Effects/Symptoms

Inhalation: This product is irritating to the respiratory system.

Skin contact: This product is irritating to the skin. May cause sensitization by skin contact.

Eye contact: Causes serious eye damage.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion:

Hazardous Component(s)	LD50s and LC50s Immediate and Delayed Health Eff		
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l	Irritant	
Dicyclohexylamine	Oral LD50 (Rat) = 373 mg/kg	Allergen, Blood, Central nervous system, Corrosive, Irritant, Kidney, Liver, Mutagen	
Oleylamidoethyleneoxyethanol	None	No Records	
Boric acid (H3BO3), compd. w ith 2-(2-aminoethoxy)	None	Cardiac, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Metabolic, Reproductive	
Amine borate	None	Cardiac, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Metabolic, Reproductive	
Diglycol amine	None	Corrosive, Irritant	
Monoethanolamine	Oral LD50 (Rat) = 10.2 g/kg Oral LD50 (Mouse) = 700 mg/kg Dermal LD50 (Rabbit) = 1,025 mg/kg	Irritant, Kidney, Liver, Corrosive, Respiratory, Developmental	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Dicyclohexylamine	No	No	No
Oleylamidoethyleneoxyethanol	No	No	No
Boric acid (H3BO3), compd. w ith 2-(2- aminoethoxy)	No	No	No
Amine borate	No	No	No
Diglycol amine	No	No	No
Monoethanolamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

TRANSPORT INFORMATION 14.

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Propershipping name: Not regulated

Hazard class or division: None Identification number: None None Packing group:

IDH number: 1620730 Product name: BONDERITE L-MR B-200 SEMI SYNTHETIC COOLANT known as MULTAN B-200

Page 4 of 5







International Air Transportation (ICAO/IATA)

Propershipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Propershipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: Amine borates (CAS# 124756-59-8).

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 04/04/2022

DISCLAIM ER: The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirmthat the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

Product name: BONDERITE L-MR B-200 SEMI SYNTHETIC COOLANT known as MULTAN B-200

Page 5 of 5



IDH number: 1620730



