



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® TankBond™ Thread Stopper

PRODUCT DESCRIPTION

Fix any loose screw in seconds! DAP® Tank Bond™ Thread Stopper Tape is the perfect solution to fix anything that shakes, rattles, jiggles or comes loose around your home. The easy-to-apply tape keeps screws and bolts tightly in place while absorbing shock and vibration from everyday wear and tear. Thread Stopper Tape remains easily removable and even reusable up to 3X with each application. Works on all fastener types and sizes as well as on virtually any surface including metal, wood, plastic & more. Covers up to 90 screws or bolts so you can use it again and again throughout your house. Water and chemical resistant formula can be used for interior or exterior and can help prevent leakage or stripping.



PACKAGING	COLOR	UPC
1/2" x 5' Roll	Orange	7079800169

KEY FEATURES & BENEFITS

- Fixes Loose Screws in Seconds
- Covers up to 90 Screws or Bolts
- Ready Instantly – No Dry Time
- Works on All Fastener Types and Sizes

PERFORMANCE CHARACTERISTICS

- Holds Screws & Bolts Tightly in Place
- Absorbs Shock and Vibrations
- Remove & Reuse up to 3x Per Application
- Multi Material: Wood, Metal, Plastic, & More



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Water-Resistant
- Chemical-Resistant
- Corrosion-Resistant
- Interior / Exterior Use
- 5 Year Shelf Life
- Minimizes Stripping of Fastener Threads
- Prevents Leakage

SUGGESTED USES

Can be used to secure screws and bolts and prevent fastener from loosening, even under ? vibration.

- Ideal for use in applications such as:
 - Door Handles, Knobs and Hinges
 - Cabinet Hardware
 - Furniture Assembly & Repair
 - Building Projects
 - Construction Fasteners
 - Automotive Maintenance
 - Motorcycle and Bicycle Maintenance
 - Lawn Care Equipment
 - Appliances
 - PVC Projects and Assemblies
 - DIY Projects
- Ideal for adhering to virtually any surface including:
 - Metal
 - Wood
 - Plastic & More

APPLICATION

Surface Preparation:

1. Ensure parts are clean, dry and free from all foreign materials.

Application:

1. Separate end of tape from Press end of tape into threads of fastener and hold while pulling remaining tape to stretch slightly.
2. Wrap Thread Stopper Tape tightly around fastener 1 ½ to 2 revolutions at area of engagement stretching tape as you wrap.
3. Press and hold tape against threads on desired end spot and tear remainder of tape away. Press any excess down tightly against fastener.
4. Install screw or bolt back tightly into place. Scrape away any excess or squeeze out.

Note: It is recommended that DAP Tank Bond Thread Stopper Tape be tested in the application for which it is to be used.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Acrylic Polymer
Consistency:	Solid
Color:	Orange
Non-Volatiles:	84.5%
Flash Point:	505 °F (263 °C)
Weight/Gal:	9.47
Application Temperature Range:	0°F to 120°F
Service Temperature Range:	-65°F to 165°F
Full Cure (for assembly):	No dry time
Shelf Life:	5 Years
Film Thickness	5.3 mil (±0.3 mil)
Recommended Thread Fill	25-50% of the thread root area
Chemical Resistance	Resistant to many common solvents
Corrosion Resistance	Resistant to acid/alkali and acts as a corrosion barrier
Prevailing On Torque	Moderate
Breakaway Torque	No distinct breakaway; Slow release as cold material flows
Prevailing Off Torque	Continued constant resistance during removal
Reusability	Up to 3X per application
Lead Thread Requirement	None

CLEAN UP & STORAGE

To remove from threads, scrape or brush away with a wire brush. Store in original package in a cool dry place and be sure to wash hands with soap and warm water after use.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or calling 888-DAP-TIPS.

WARRANTY



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

LIMITED WARRANTY: If product fails when used as directed, within one year of purchase, DAP will provide replacement product or refund sales price: call (888) DAP TIPS with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com