



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Alex Flex® Flexible Spackling

PRODUCT DESCRIPTION

DAP® ALEX FLEX® Flexible Spackling is a premium spackling for eliminating reoccurring cracks in drywall. It's ready-to-use smooth, white formula spreads easily for fast, professional repairs. ALEX FLEX Spackling sands effortlessly and can be painted. It does not flash or gloss low sheen/flat paint. It can be used for interior or exterior applications.



PACKAGING	COLOR	UPC
16 oz. (473 mL)	White	7079818742
32 oz. (946 mL)	White	7079818743

KEY FEATURES & BENEFITS

- **Flexible – Eliminate reoccurring cracks**
- **Sandable**
- **Paintable**
- **Won't sink or shrink**
- **Interior/Exterior use**

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on: Drywall, Plaster, Wood

FOR BEST RESULTS

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a quality paint.
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

APPLICATION

1. Surface must be clean, dry and free of foreign material.
2. Stir thoroughly before use.
3. Apply with a clean putty knife.
4. For a smoother finish, dip putty knife in water and lightly smooth spackling.
5. One application is usually sufficient for small repairs. For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
6. May be sanded or painted in 1 to 5 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
7. Clean tools immediately with water.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	13.5 pounds
Solids	74%
Application Temperature	50°F minimum
Service Temperature	0°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	1 to 5 hours depending on temperature, humidity and depth of fill



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

- Wash tools immediately after use with water.
- Dried material must be removed by scraping or sanding.
- Be sure container lid/cap is closed and tightly sealed.
- Store in a cool, dry place.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com