



SAFETY DATA SHEET

DDP Specialty Electronic Materials US,
LLC

Product name: BETASEAL™ 5026NA Glass Primer

Issue Date: 10/15/2018

Print Date: 02/19/2021

DDP Specialty Electronic Materials US, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: BETASEAL™ 5026NA Glass Primer

Recommended use of the chemical and restrictions on use

Identified uses: A primer - For use in automotive applications.

COMPANY IDENTIFICATION

DDP Specialty Electronic Materials US,
LLC

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 2

Eye irritation - Category 2A

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 2

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/ attention if you feel unwell.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
Methyl ethyl ketone	78-93-3	> 55.0 - < 65.0 %

ALIPHATIC BASED URETHANE POLYMER P93-669	Not available	> 10.0 - < 20.0 %
Carbon black	1333-86-4	> 5.0 - < 15.0 %
3-Methoxy-1-butyl acetate	4435-53-4	> 1.0 - < 5.0 %
Propylene glycol monomethyl ether acetate	108-65-6	> 1.0 - < 5.0 %
Ethylbenzene	100-41-4	< 2.0 %
Naphtha, petroleum	8030-30-6	< 2.0 %
Methyl methacrylate	80-62-6	< 1.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapor space of containers at room temperature. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water. Product may be carried across water surface spreading fire or contacting an ignition source.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Evacuate area. Keep personnel out of low areas. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. For large spills, warn public of downwind explosion hazard. Check area with combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Spills or discharge to natural waterways is likely to kill aquatic organisms. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Cat litter. Sand. Sawdust. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep away from heat, sparks and flame. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid breathing vapor or mist. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Ignition sources can include and are not limited to pilot lights, flames, smoking, sparks, heaters, electrical equipment, and static discharges. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Never use air pressure for transferring product unless a risk assessment has been conducted that includes consideration of the flammability of the product. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Minimize sources of ignition, such as static build-up, heat, spark or flame. Keep container closed. Flammable mixtures may exist within the vapor space of containers at room temperature.

Storage stability

Storage temperature:

> 5 - < 35 °C (> 41 - < 95
°F)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Methyl ethyl ketone	Dow IHG	TWA	50 ppm
	Dow IHG	STEL	100 ppm
	ACGIH	TWA	200 ppm
	ACGIH	STEL	300 ppm
	OSHA Z-1	TWA	590 mg/m3 200 ppm
Propylene glycol monomethyl ether acetate	Dow IHG	TWA	30 ppm
	Dow IHG	TWA	SKIN
	Dow IHG	STEL	90 ppm
	Dow IHG	STEL	SKIN

	US WEEL	TWA	50 ppm
Ethylbenzene	ACGIH	TWA	20 ppm
	OSHA Z-1	TWA	435 mg/m3 100 ppm
Naphtha, petroleum	OSHA Z-1	TWA	400 mg/m3 100 ppm
Methyl methacrylate	ACGIH	TWA	50 ppm
	ACGIH	TWA	Skin Sensitizer
	ACGIH	STEL	100 ppm
	OSHA Z-1	TWA	410 mg/m3 100 ppm
	ACGIH	STEL	Skin Sensitizer
	CAL PEL	PEL	205 mg/m3 50 ppm
	CAL PEL	STEL	410 mg/m3 100 ppm

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methyl ethyl ketone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI
Propylene glycol monomethyl ether acetate	108-65-6				100 mg/g	
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI
Methyl methacrylate	80-62-6				100 mg/g 100 mg/g 100 mg/g	

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Polyethylene. Polyvinyl alcohol ("PVA"). Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Neoprene. Chlorinated polyethylene. Natural rubber

("latex"). Avoid gloves made of: Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	Liquid.
Color	Black
Odor	Solvent
Odor Threshold	No test data available
pH	No test data available
Melting point/range	No test data available
Freezing point	No test data available
Boiling point (760 mmHg)	No test data available
Flash point	closed cup -7 °C (19 °F) <i>PMCC, ASTM D93</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Flammable liquid
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	No test data available
Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	0.91 <i>ASTM D1475</i>
Water solubility	No test data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Dynamic Viscosity	No test data available

Kinematic Viscosity	No test data available
Explosive properties	No test data available
Oxidizing properties	No test data available
Molecular weight	No data available
Volatile Organic Compounds	5.4 lb/gln <i>EPA Method No. 24</i> (typical value)

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Avoid static discharge.

Incompatible materials: Avoid contact with: Acids. Bases. Oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Single dose oral LD50 has not been determined.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

The dermal LD50 has not been determined.

Acute inhalation toxicity

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. May cause nausea and vomiting. This material contains mineral and/or inorganic fillers. There is essentially no potential for inhalation exposure to these fillers incidental to industrial handling due to the physical state.

The LC50 has not been determined.

Skin corrosion/irritation

Prolonged contact may cause moderate skin irritation with local redness.
May cause drying and flaking of the skin.
May stain skin.

Serious eye damage/eye irritation

May cause moderate eye irritation which may be slow to heal.
May cause moderate corneal injury.
Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

For skin sensitization:

A component in this mixture has caused allergic skin reactions in humans.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals:

Liver.

Kidney.

Lung.

Nasal tissue.

Methyl ethyl ketone is probably not neurotoxic in itself but it potentiates the neurotoxicity of methyl-n-butyl ketone and n-hexane.

Methyl ethyl ketone has caused liver effects in laboratory animals exposed by inhalation to high concentrations.

Although one early inhalation study on ethylbenzene reported an adverse effect on the testes, recent, more comprehensive studies have not shown this effect.

May cause hearing loss based on animal data.

Carcinogenicity

Ethylbenzene has been shown to cause cancer in laboratory animals. There is no evidence that these findings are relevant to humans.

Teratogenicity

Contains component(s) which caused birth defects in laboratory animals only at doses toxic to the mother. Contains component(s) which, in laboratory animals, have been toxic to the fetus at doses nontoxic to the mother.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies. Contains component(s) which did not interfere with fertility in animal studies.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard

Based on available information, aspiration hazard could not be determined.

COMPONENTS INFLUENCING TOXICOLOGY:**Methyl ethyl ketone****Acute oral toxicity**

LD50, Rat, 2,657 - 5,554 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 34.5 mg/l

ALIPHATIC BASED URETHANE POLYMER P93-669**Acute oral toxicity**

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Carbon black**Acute oral toxicity**

LD50, Rat, > 8,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 3,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

LC50, Rat, 1 Hour, dust/mist, 27 mg/l No deaths occurred at this concentration.

3-Methoxy-1-butyl acetate**Acute oral toxicity**

LD50, Rat, 4,210 mg/kg

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Propylene glycol monomethyl ether acetate**Acute oral toxicity**

Observations in animals include: Lethargy. LD50, Rat, > 5,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity

LC0, Rat, 6 Hour, vapour, > 23.5 mg/l No deaths occurred at this concentration.

Ethylbenzene**Acute oral toxicity**

LD50, Rat, 3,500 mg/kg

Acute dermal toxicity

LD50, Rabbit, 15,500 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 17.2 mg/l

Naphtha, petroleum**Acute oral toxicity**

LD50, Rat, male and female, > 5,000 mg/kg OECD 401 or equivalent No deaths occurred at this concentration.

Acute dermal toxicity

LD50, Rat, male and female, > 2,000 mg/kg OECD 402 or equivalent No deaths occurred at this concentration.

Acute inhalation toxicity

No adverse effects are anticipated from single exposure to vapor.

LC50, Rat, male and female, 4 Hour, vapour, > 7,630 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

Methyl methacrylate**Acute oral toxicity**

Swallowing may result in gastrointestinal irritation.

LD50, Rat, 7,900 mg/kg

Acute dermal toxicity

Although data from animal studies indicate a lowpotential for absorption through the skin in harmful amounts, there have been a few case reports which suggest that sensory (neurological) effects may result from skin contact. LD50, Rabbit, > 5,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 29.8 mg/l

LC50, Rat, 4 Hour, vapour, 7031 - 9281 ppm

Carcinogenicity**Component****Ethylbenzene****List**

IARC

ACGIH

Classification

Group 2B: Possibly carcinogenic to humans

A3: Confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Methyl ethyl ketone

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 2,993 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 308 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (microalgae), static test, 96 Hour, Growth rate inhibition, 2,029 mg/l, OECD Test Guideline 201

Toxicity to bacteria

EC50, Bacteria, 96 Hour, > 1,000 mg/l, hUCC

ALIPHATIC BASED URETHANE POLYMER P93-669

Acute toxicity to fish

No relevant data found.

Carbon black

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Leuciscus idus (Golden orfe), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 5,600 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

NOEC, Desmodesmus subspicatus (green algae), 72 Hour, 10,000 mg/l, OECD Test Guideline 201

3-Methoxy-1-butyl acetate

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, Danio rerio (zebra fish), semi-static test, 96 Hour, 7.1 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, 360 mg/l
LC50, crustacean Chaetogammarus marinus, 96 Hour, 128 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate inhibition, > 70 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 1,000 mg/l

Propylene glycol monomethyl ether acetate**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 134 mg/l, Method Not Specified.

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 408 mg/l, Method Not Specified.

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (microalgae), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 201 or Equivalent

Ethylbenzene**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 4.2 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), Static, 48 Hour, 1.8 - 2.4 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth inhibition (cell density reduction), 3.6 - 4.6 mg/l, OECD Test Guideline 201 or Equivalent

Toxicity to bacteria

EC50, Bacteria, 16 Hour, > 12 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Ceriodaphnia dubia (water flea), semi-static test, 7 d, 0.96 mg/l

Toxicity to soil-dwelling organisms

LC50, Eisenia fetida (earthworms), 2 d, survival, 0.047 mg/cm²

Naphtha, petroleum**Acute toxicity to fish**

Material is highly toxic to aquatic organisms on an acute basis (LC50/EC50 between 0.1 and 1 mg/L in the most sensitive species tested).
LC50, Fathead minnow (Pimephales promelas), 96 Hour, 2.5 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna, 48 Hour, 0.9 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata, 72 Hour, Growth rate, 1 mg/l, OECD Test Guideline 201

Methyl methacrylate**Acute toxicity to fish**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), flow-through test, 96 Hour, > 79 mg/l, OECD Test Guideline 203 or Equivalent

LC50, Lepomis macrochirus (Bluegill sunfish), flow-through test, 96 Hour, 233 mg/l, EPA-660-75-009

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, 69 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate inhibition, > 110 mg/l, OECD Test Guideline 201 or Equivalent

NOEC, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, 110 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, Danio rerio (zebra fish), 35 d, 9.4 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 37 mg/l

Persistence and degradability

Methyl ethyl ketone

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 2.44 mg/mg

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	71 - 76 %
10 d	71 - 82 %
20 d	71 - 89 %

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 8 d

Method: Estimated.

ALIPHATIC BASED URETHANE POLYMER P93-669

Biodegradability: No relevant data found.

Carbon black

Biodegradability: Biodegradation is not applicable.

3-Methoxy-1-butyl acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: > 90 %

Exposure time: 12 d

Method: OECD Test Guideline 301E or Equivalent

10-day Window: Not applicable

Biodegradation: > 95 %

Exposure time: 20 d

Method: OECD Test Guideline 302B or Equivalent

10-day Window: Not applicable

Biodegradation: 63.5 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Theoretical Oxygen Demand: 1.97 mg/mg

Photodegradation

Atmospheric half-life: 0.57 d

Method: Estimated.

Propylene glycol monomethyl ether acetate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 83 %

Exposure time: 28 d

Method: OECD Test Guideline 301F or Equivalent

10-day Window: Not applicable

Biodegradation: 100 %

Exposure time: 28 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 1.82 mg/mg

Ethylbenzene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 100 %

Exposure time: 6 d

Method: OECD Test Guideline 301E or Equivalent

Theoretical Oxygen Demand: 3.17 mg/mg Estimated.

Chemical Oxygen Demand: 2.62 mg/mg Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	31.5 %
10 d	38.5 %
20 d	45.4 %

Photodegradation**Sensitization:** OH radicals**Atmospheric half-life:** 55 Hour**Method:** Estimated.**Naphtha, petroleum****Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 77.05 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301F**Methyl methacrylate****Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 94 %**Exposure time:** 14 d**Method:** OECD Test Guideline 301C or Equivalent

10-day Window: Not applicable

Biodegradation: > 95 %**Exposure time:** 28 d**Method:** OECD Test Guideline 302B or Equivalent**Theoretical Oxygen Demand:** 1.02 mg/mg**Physico-chemical removability**

Rapidly hydrolyzed under alkaline conditions.

Photodegradation**Test Type:** Half-life (indirect photolysis)**Sensitization:** OH radicals**Atmospheric half-life:** 6.997 Hour**Method:** Estimated.**Bioaccumulative potential****Methyl ethyl ketone****Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).**Partition coefficient: n-octanol/water(log Pow):** 0.29 Measured**ALIPHATIC BASED URETHANE POLYMER P93-669**

Bioaccumulation: No relevant data found.

Carbon black

Bioaccumulation: No relevant data found.

3-Methoxy-1-butyl acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.01 Estimated.

Propylene glycol monomethyl ether acetate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.2 Measured

Ethylbenzene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 3.15 Measured

Bioconcentration factor (BCF): 15 Fish Measured

Naphtha, petroleum

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.1 - 6 estimated

Bioconcentration factor (BCF): 511 Fish Estimated.

Methyl methacrylate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.38 Measured

Mobility in soil

Methyl ethyl ketone

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 3.8 Estimated.

ALIPHATIC BASED URETHANE POLYMER P93-669

No relevant data found.

Carbon black

No relevant data found.

3-Methoxy-1-butyl acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 10 Estimated.

Propylene glycol monomethyl ether acetate

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 1.7 Estimated.

Ethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 518 Estimated.

Naphtha, petroleum

No relevant data found.

Methyl methacrylate

Potential for mobility in soil is high (Koc between 50 and 150).

Partition coefficient (Koc): 87 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Coating solution
UN number	UN 1139
Class	3
Packing group	II
Reportable Quantity	Methyl ethyl ketone

Classification for SEA transport (IMO-IMDG):

Proper shipping name	COATING SOLUTION
UN number	UN 1139
Class	3
Packing group	II
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Coating solution
UN number	UN 1139
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components	CASRN
Ethylbenzene	100-41-4

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

The following product components are cited in the Pennsylvania Hazardous Substance List and/or the Pennsylvania Environmental Substance List, and are present at levels which require reporting.

Components	CASRN
Methyl ethyl ketone	78-93-3
Carbon black	1333-86-4
Ethylbenzene	100-41-4
Naphtha, petroleum	8030-30-6

California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, Ethylbenzene, Benzene, which is/are known to the State of California to cause cancer, and Methanol, Benzene, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Flammability	Instability
2	3	1

Revision

Identification Number: 12021362 / A749 / Issue Date: 10/15/2018 / Version: 17.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	ACGIH - Biological Exposure Indices (BEI)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Dow IHG	Dow Industrial Hygiene Guideline
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
PEL	Permissible exposure limit
SKIN	Absorbed via skin
STEL	Short term exposure limit
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP Specialty Electronic Materials US, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US