

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
INDUSTRIAL
— CHOICE —

T1600 SYSTEM TREE MARKING PAINT

DESCRIPTION AND USES

Tree Marking Paint is a solvent-based marking paint designed for marking trees and logs ready to be milled. Tree Marking Paint is designed to be used by loggers and foresters in sawmills, lumber companies, paper manufacturing and highway departments.

PRODUCTS

- Fast dry
- Suitable for wet and dry application
- Excellent adhesion in extreme wet conditions
- Excellent resistance to color fading

PRODUCTS

SKU	DESCRIPTION
306513	White
306514	Black
306515	Yellow
306516	Red
306517	Orange
306518	Blue
306519	Green
306520	Dark Green
306521	Silver
306522	Fluorescent Red
306523	Fluorescent Pink
306524	Fluorescent Orange
306525	Fluorescent Yellow

PACKAGING

16 fl. oz. aerosol container, (12 oz. fill weight), 12 aerosols/carton.

PRODUCT APPLICATION

SURFACE PREPARATION

None Required

APPLICATION

Use when temperature is 35-90°F (2-32°C). This product can be used down to 25°F (-4°C) which may result in a slight reduction of delivery rate. SHAKE CAN VIGOROUSLY for one minute after mixing ball is heard. Do not strike can. Hold can 12-18 inches from surface. Be sure the nozzle opening is facing the surface. Apply in steady motion. Keep can moving to prevent build-up.

DRY & RECOAT TIMES

Dry and recoat times are based on 70°F and 50% relative humidity. This product dries tack free in 20 minutes, to handle in 30 minutes and can be recoated within 1 hour or after 24 hours.

CLEAN-UP

Wipe off spray tip when finished using. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled.

AEROSOLS	TECHNICAL DATA	IC-34
• TRUSTED QUALITY SINCE 1921 • RUST-OLEUM® INDUSTRIAL — CHOICE —	T1600 SYSTEM TREE MARKING PAINT	

PHYSICAL PROPERTIES

		TREE MARKING PAINT
Resin Type		Modified Alkyd
Pigment Type		Varies with color
Solvents		Acetone, N-Butyl Acetate, Low Aromatic Mineral Spirits, Xylene
MIR		Maximum value of 0.85
Fill Weight		12 oz.
Recommended Dry Film Thickness (DFT) per Coat		1.0 mil
Practical Coverage		Approximately 300 linear feet at 1 inch wide
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Tack Free	20 minutes
	Handle	30 minutes
	Recoat	Within 1 hour or after 24 hours
Shelf Life		3 years
Safety Information		For additional information, see SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.