



UR-AWAY FL

Uncured Urethane Flushing Solvent



UR-Away FL is a formulated solvent which is used for flushing and removal of uncured urethane materials, including polyurethane foams, reactive hot melts, and other urethane based materials.

CLEANING APPLICATIONS:

Urethane metering, mixing and processing equipment flushing
Spray polyurethane foam equipment flushing

ADVANTAGES:

More efficient than acetone, MEK & other solvents
High flash point
High loading capacity and recyclability allows for reuse and reduced cost of ownership
Used at room temperature

SPECIFICATIONS:

Specific gravity:	0.90
Boiling point:	> 480°F (>248°C)
Flash point:	270°F (132°C)

MATERIALS REMOVED:

Uncured urethane materials

PRODUCT USAGE GUIDELINES

(SEE SDS FOR EH&S INFORMATION):

1. UR-AWAY FL is typically used at room temperature. Heat to 130° – 150°F (54° – 65°C) for faster results.
2. Flush equipment of uncured urethane materials.

MATERIAL COMPATIBILITY:

Recommended materials including:

All metals
Teflon®
Polyethylene & polypropylene

Avoid materials including:

EDPM
PVC
Neoprene



The information contained herein is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto.

Versum and the Versum Materials logo are trademarks of Versum Materials, Inc. © 2017 Versum Materials, Inc.

325-17-049-GLOBAL



1-800-375-0605
Option 8 for 24/7 Service



6550 Oley Speaks Way
Canal Winchester, OH 43110



www.RudolphBros.Com
RBCsupport@RudBro.Com