

BETASEAL™ 43532

Body Primer

Description

BETASEAL™ 43532 Body Primer is a polyurethane based, methylene chloride free, solvent evaporation, and moisture cure type primer. After application to a substrate, this primer has a tendency to drip less than standard primers. **BETASEAL 43532** is recommended for use as an adhesion promoter between BETASEAL Urethane Adhesives and automotive paint coatings.

Typical Applications

BETASEAL 43532 primer is an integral component of a **BETASEAL** bonding system. Its suggested use is priming coated automotive body flanges (pinch welds) before the application of a **BETASEAL™** adhesive.

Application Techniques

BETASEAL 43532 can be applied by using pressurized dispensing (steam or spray) equipment, pad, brush, or other suitable applicator. Allow the **BETASEAL 43532** to dry at room temperature for a minimum of 30 minutes before applying a **BETASEAL** adhesive. If the primed surface is clean (free of oil, dirt or dust), adhesive can be applied for up to 110 hours after the primer has dried.

Safety Precautions

Refer to Material Safety Data Sheet for details.

Storage

BETASEAL 43532 Primer is a moisture sensitive material and **MUST** be stored in airtight, dry containers at temperatures between 65° and 95°F.

Storage Stability

Shelf stability is assured for 6 months from date of manufacture when stored according to manufacturer's instructions.

Packaging

BETASEAL 43532 is available in one quart cans and in 5-gallon pails.

Physical Properties



Appearance	Black
VOC lbs./gal	4.65
Flash Point,	
°F	25°
°C	-4°
Solids Content,	
minimum, %	46
Viscosity, Ford Cup # 4	25-25

Contact your Dow Automotive Sales Representative for more detailed information.

DISCLAIMER OF WARRANTY

All statements, technical information and recommendations herein are based on tests we believe to be reliable. BUT THE ACCURACY OR COMPLETENESS THEREOF IS NOT GUARANTEED, AND THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PURPOSE. Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therein. NEITHER SELLER NOR MANUFACTURER SHALL BE LIABLE EITHER IN CONTRACT FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL, OR CONSEQUENTIAL, ARISING OUT OF THE USE AND OR THE INABILITY TO USE THE PRODUCT. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer.

Distributed by:
Rudolph Bros. & Co.
PO Box 425, Canal Winchester, OH 43110
Phone: 614-833-0707
Fax: 800-600-9508
e-mail: rbcsupport@rudbro.com
www.rudbro.com