



Revision Number: 004.0

Issue date: 08/25/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE LB 8012 known as Moly Paste	IDH number:	234227
Product type:	Lubricant	Item number:	51048
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention:	Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Molybdenum disulphide	1317-33-5	60 - 100
Residual oil, solvent-dewaxed, <3% DMSO	64742-62-7	10 - 30

IDH number: 234227

Product name: LOCTITE LB 8012 known as Moly Paste

Quartz (SiO ₂)	14808-60-7	1 - 5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1 - 5
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	1 - 5
aluminium tristearate	637-12-7	0.1 - 1
Barium dinonylnaphthalenesulfonate	25619-56-1	0.1 - 1
Lubricating oils, petroleum, hydrotreated spent	64742-58-1	0.1 - 1
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	0.1 - 1

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow material to contaminate ground water system.
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Scrape up as much material as possible. Clean residue with soap and water. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Molybdenum disulphide	10 mg/m ³ TWA (as Mo) Inhalable fraction. 3 mg/m ³ TWA (as Mo) Respirable fraction.	15 mg/m ³ PEL (as Mo) Total dust.	None	None
Residual oil, solvent-dewaxed, <3% DMSO	5 mg/m ³ TWA mist Exposure by all routes should be carefully controlled to levels as low as possible. 10 mg/m ³ STEL mist 5 mg/m ³ TWA Inhalable fraction. Included in the regulation but with no data values. See regulation for further details	5 mg/m ³ TWA mist	None	None
Quartz (SiO ₂)	0.025 mg/m ³ TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m ³ TWA Respirable. 0.05 mg/m ³ PEL	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ TWA Inhalable fraction. 5 mg/m ³ TWA mist 10 mg/m ³ STEL mist	5 mg/m ³ TWA mist 500 ppm (2,000 mg/m ³) PEL 5 mg/m ³ PEL Mist.	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m ³ TWA Inhalable fraction.	5 mg/m ³ PEL Mist. 500 ppm (2,000 mg/m ³) PEL	None	None
aluminium tristearate	1 mg/m ³ TWA Respirable fraction. 10 mg/m ³ TWA	None	None	None
Barium dinonylnaphthalenesulfonate	0.5 mg/m ³ TWA (as Ba)	0.5 mg/m ³ PEL (as Ba)	None	None
Lubricating oils, petroleum, hydrotreated spent	Exposure by all routes should be carefully controlled to levels as low as possible. 5 mg/m ³ TWA Inhalable fraction. Included in the regulation but with no data values. See regulation for further details	None	None	None
Distillates (petroleum), hydrotreated heavy paraffinic	5 mg/m ³ TWA mist 10 mg/m ³ STEL mist	5 mg/m ³ TWA mist	None	None

Engineering controls:

Use only with adequate ventilation. Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eyeface protection:

Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

Skin protection:

Chemical resistant, impermeable gloves. Use of Butyl or Nitrile Rubber gloves is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Gray
Odor:	Mild, Petroleum
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.9614
Vapor density:	Heavier than air.
Flash point:	160 °C (320°F)
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Less than butyl acetate.
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not determined
VOC content:	5.08 %; 102.3 g/l EPA Method 24
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of carbon. Hydrocarbons.
Incompatible materials:	Oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
------------------------------	-----------------------------------

Potential Health Effects/Symptoms**Inhalation:**

May cause respiratory tract irritation. Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust.

Skin contact:

Causes skin irritation.

Eye contact:

Causes serious eye irritation.

Ingestion:

May cause gastrointestinal disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Molybdenum disulphide	None	No Target Organs
Residual oil, solvent-dewaxed, <3% DMSO	None	Irritant
Quartz (SiO ₂)	None	Immune system, Lung, Some evidence of carcinogenicity
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant
aluminium tristearate	None	Lung
Barium dinonylnaphthalenesulfonate	None	No Records
Lubricating oils, petroleum, hydrotreated spent	None	Irritant
Distillates (petroleum), hydrotreated heavy paraffinic	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Molybdenum disulphide	No	No	No
Residual oil, solvent-dewaxed, <3% DMSO	No	No	No
Quartz (SiO ₂)	Known To Be Human Carcinogen.	Group 1	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
aluminium tristearate	No	No	No
Barium dinonylnaphthalenesulfonate	No	No	No
Lubricating oils, petroleum, hydrotreated spent	Known To Be Human Carcinogen.	Group 1	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D005. Barium.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Timothy Pratt, Regulatory Affairs Specialist

Issue date: 08/25/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Distributed by:
Rudolph Bros. & Co.
6550 Oley Speaks Way
Canal Winchester, OH 43110
Phone: 614-833-0707
Fax: 800-600-9508
e-mail: rbcsupport@rudbro.com
www.rudbro.com