



Revision Number: 002.0

Issue date: 03/11/2014

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>TECHNOMELT COOLMELT known as HYS COOLMELT MAX.STCK 35 LB CT</b>	<b>IDH number:</b>	420392
<b>Product type:</b>	Adhesive	<b>Item number:</b>	83394
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	<b>Contact information:</b>	Telephone: 860.571.5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.  
VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND  
RESPIRATORY TRACT IRRITATION.  
STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR  
FLAMMABLE VAPORS MAY CAUSE IGNITION.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)
None

**Precautionary Statements**

<b>Prevention:</b>	Not prescribed
<b>Response:</b>	Not prescribed
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Molten adhesive may cause severe burns. Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn.
<b>Eye contact:</b>	If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.
<b>Ingestion:</b>	Ingestion of solid adhesive is not expected to be hazardous. Do not induce vomiting. If adverse health effects develop seek medical attention.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Use extinguishing measures appropriate to local circumstances and the surrounding environment. Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	None
<b>Unusual fire or explosion hazards:</b>	None
<b>Hazardous combustion products:</b>	Oxides of carbon. Acrid smoke and fumes.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	No special environmental precautions required. Do not allow material to contaminate ground water system.
<b>Clean-up methods:</b>	Health injuries are not known or expected under normal use. Sweep up spilled material. Avoid creating dust.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Do not place wet or damp solid into melt tank. Follow suggested application temperature. Always be careful around molten material. Avoid skin contact with molten resins. Do not wear contact lenses. Avoid dust formation.
<b>Storage:</b>	For safe storage, store between 8 °C (46.4 °F) and 21 °C (69.8 °F)

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

<b>Engineering controls:</b>	Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Heat only in areas with appropriate exhaust ventilation.
<b>Respiratory protection:</b>	Respirator with combination filter for vapor/particulate. In case of insufficient ventilation wear suitable respiratory equipment.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.
<b>Skin protection:</b>	Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Solid
<b>Color:</b>	Light yellow
<b>Odor:</b>	Mild
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not applicable
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	157 °C (314.6 °F)
<b>Specific gravity:</b>	0.94
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	> 232 °C (> 449.6 °F)
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	0 %; 0 g/l
<b>Viscosity:</b>	1,000 - 1,500 cp
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
<b>Incompatible materials:</b>	Oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Prolonged heating at temperatures above 200 °C.

## 11. TOXICOLOGICAL INFORMATION

<b>Product toxicity data:</b>	Henkel is not aware of any toxicity data on the specific mixture of chemical components contained in this product.
<b>Relevant routes of exposure:</b>	Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

**Inhalation:** Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.

**Skin contact:** Molten adhesive may cause severe burns. Solid adhesive has no hazards.

**Eye contact:** Molten adhesive in eyes will cause severe and permanent damage. Can cause mechanical irritation if dusts are generated.

**Ingestion:** Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
None	None	None

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None  
**Exceptions:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health  
**CERCLA/SARA Section 313:** None above reporting de minimis

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Catherine Bimler, Regulatory Affairs Specialist

**Issue date:** 03/11/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Distributed by:  
Rudolph Bros. & Co.  
6550 Oley Speaks Way  
Canal Winchester, OH 43110  
Phone: 614-833-0707  
Fax: 800-600-9508  
e-mail: [rbcsupport@rudbro.com](mailto:rbcsupport@rudbro.com)  
[www.rudbro.com](http://www.rudbro.com)