

FASTWELD 10 RESIN US

Version 1.0 Revision Date: 02/20/2017 SDS Number: 400001012600 Date of last issue: -
Date of first issue: 02/20/2017

SECTION 1. IDENTIFICATION

Product name : FASTWELD 10 RESIN US

Manufacturer or supplier's details

Company name of supplier : Huntsman Advanced Materials Americas LLC
Address : P.O. Box 4980
The Woodlands,
TX 77387
United States of America (USA)
Telephone : Non-Emergency: (800) 257-5547
E-mail address of person responsible for the SDS : MSDS@huntsman.com
Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Epoxy constituents

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1
Acute aquatic toxicity : Category 2
Chronic aquatic toxicity : Category 2

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage.

Storage:

Not available

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Bisphenol A epoxy resin	25068-38-6	50 - 70
limestone	1317-65-3	30 - 50
quartz (SiO ₂)	14808-60-7	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water.

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : No data is available on the product itself.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
No data is available on the product itself.

Hazardous combustion products : No data is available on the product itself.
No hazardous combustion products are known

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid dust formation.
Avoid breathing dust.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Avoid dust formation. Provide appropriate exhaust ventilation at places where dust is formed.

Advice on safe handling : Avoid formation of respirable particles.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
quartz (SiO ₂)	14808-60-7	TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.025 mg/m ³ (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1

Personal protective equipment

Hand protection

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Material	:	butyl-rubber
Break through time	:	> 8 h
		Solvent-resistant gloves (butyl-rubber) Nitrile rubber 10 - 480 min
		Neoprene gloves
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Colour	:	black
Odour	:	mild
Odour Threshold	:	No data is available on the product itself.
pH	:	No data is available on the product itself.
Freezing point	:	No data is available on the product itself.
Melting point	:	No data is available on the product itself.
Boiling point	:	No data is available on the product itself.
Flash point	:	> 93.33 °C Method: estimated, closed cup
Evaporation rate	:	No data is available on the product itself.
Flammability (solid, gas)	:	No data is available on the product itself.
Flammability (liquids)	:	No data is available on the product itself.
Upper explosion limit	:	No data is available on the product itself.
Lower explosion limit	:	No data is available on the product itself.

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Vapour pressure : < 0.00001 hPa (25 °C)

Relative vapour density : No data is available on the product itself.

Relative density : 1.43 - 1.53

Density : No data is available on the product itself.

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : No data available

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity**Components:**

Bisphenol A epoxy resin:

Acute oral toxicityComponents : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

limestone:
Acute oral toxicity
Components : LD50 (Rat): 6,450 mg/kg

Acute inhalation toxicity : No data available

Components:

Bisphenol A epoxy resin:
Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Assessment: No data available

Germ cell mutagenicity**Components:**

Bisphenol A epoxy resin:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Components:

Bisphenol A epoxy resin:
Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Result: negative

Cell type: Somatic
 Application Route: Oral
 Dose: 0 - 5000 mg/kg
 Method: OPPTS 870.5395
 Result: negative

Components:

Bisphenol A epoxy resin:
 Germ cell mutagenicity-
 Assessment : Weight of evidence does not support classification as a germ
 cell mutagen.

Germ cell mutagenicity-
 Assessment : No data available

Carcinogenicity**Components:**

Bisphenol A epoxy resin:
 Species: Rat, (male and female)
 Application Route: Oral
 Exposure time: 24 month(s)
 Dose: 15 mg/kg
 Frequency of Treatment: 7 days/week
 Method: OECD Test Guideline 453
 Result: negative

Species: Mouse, (male)
 Application Route: Dermal
 Exposure time: 24 month(s)
 Dose: 0.1 mg/kg
 Frequency of Treatment: 3 days/week
 Method: OECD Test Guideline 453
 Result: negative

Species: Rat, (female)
 Application Route: Dermal
 Exposure time: 24 month(s)
 Dose: 1 mg/kg
 Frequency of Treatment: 5 days/week
 Method: OECD Test Guideline 453
 Result: negative

Carcinogenicity -
 Assessment : No data available

IARC

Group 1: Carcinogenic to humans

quartz (SiO₂)**ACGIH**

Suspected human carcinogen

quartz (SiO₂)

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP Known to be human carcinogen
quartz (SiO₂)

Reproductive toxicity**Components:**

Bisphenol A epoxy resin:
Effects on fertility

: Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: >750 milligram per kilogram
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Components:

Bisphenol A epoxy resin:
Effects on foetal
development

: Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

STOT - repeated exposure

No data available

Repeated dose toxicity**Components:**

Bisphenol A epoxy resin:
Species: Rat, male and female
NOAEL: 50 mg/kg
Application Route: Ingestion
Exposure time: 14 Weeks
Number of exposures: 7 d
Method: Subchronic toxicity

Species: Rat, male and female
NOEL: 10 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks
Number of exposures: 5 d
Method: Subchronic toxicity

Species: Mouse, male
NOAEL: 100 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks
Number of exposures: 3 d
Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Neurological effects

No data available

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:**

Bisphenol A epoxy resin:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

limestone:

Toxicity to fish : LC50: > 56,000 mg/l
Exposure time: 96 h

Components:

Bisphenol A epoxy resin:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Components:

Bisphenol A epoxy resin:

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic toxicity) : No data available

Components:

Bisphenol A epoxy resin:

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
Exposure time: 21 d

FASTWELD 10 RESIN US

Version 1.0 Revision Date: 02/20/2017 SDS Number: 400001012600 Date of last issue: -
Date of first issue: 02/20/2017

(Chronic toxicity) Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

limestone:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50 (Daphnia magna (Water flea)): > 350 mg/l
Exposure time: 125 d
Test Type: semi-static test
Test substance: Fresh water

M-Factor (Chronic aquatic toxicity) : No data available

Components:

Bisphenol A epoxy resin:
Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to the environment : No data available

Persistence and degradability**Components:**

Bisphenol A epoxy resin:
Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

Bisphenol A epoxy resin:
Stability in water

: Degradation half life(DT50): 4.83 d (25 °C) pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 7.1 d (25 °C) pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 3.58 d (25 °C) pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential**Components:**

Bisphenol A epoxy resin:
Bioaccumulation

: Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Components:

Bisphenol A epoxy resin:
Partition coefficient: n-octanol/water

: log Pow: 3.242 (25 °C)
pH: 7.1
Method: OECD Test Guideline 117

limestone:

Partition coefficient: n-octanol/water

: log Pow: < 1
Method: No information available.

Mobility in soil

Mobility : No data available

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

Components:

Bisphenol A epoxy resin:
 Distribution among environmental compartments : Koc: 445
 Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available
 Results of PBT and vPvB assessment : No data available
 Endocrine disrupting potential : No data available
 Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
 Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
 Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Toxic to aquatic life with long lasting effects.
 Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Do not re-use empty containers.

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA**

UN/ID No.	: UN 3077
Proper shipping name	: Environmentally hazardous substance, solid, n.o.s. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: Miscellaneous
Packing instruction (cargo aircraft)	: 956
Packing instruction (passenger aircraft)	: 956

IMDG

UN number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: 9
EmS Code	: F-A, S-F
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**DOT Classification**

UN/ID/NA number	: UN 3077
Proper shipping name	: ENVIRONMENTALLY HAZARDOUS SUBSTANCES, SOLID, N.O.S. (BISPHENOL A EPOXY RESIN)
Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(BISPHENOL A EPOXY RESIN)

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****SARA 311/312 Hazards** : Acute Health Hazard

FASTWELD 10 RESIN US

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	02/20/2017	400001012600	Date of first issue: 02/20/2017

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

methanol

67-56-1

The components of this product are reported in the following inventories:

CH INV : The formulation contains substances listed on the Swiss Inventory, On the inventory, or in compliance with the inventory

DSL : This product contains one or several components listed in the Canadian NDSL.

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.




Authorized Distributor

1-800-375-0605

www.rudolphbros.com

FASTWELD 10 RESIN US

Version 1.0 Revision Date: 02/20/2017 SDS Number: 400001012600 Date of last issue: -
 Date of first issue: 02/20/2017

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS® IV:**

HEALTH		2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Revision Date : 02/20/2017

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.