

SAFETY DATA SHEET

ARALDITE® 2012 HARDENER/HAERTER/DURCISSEUR

Section 1. Identification

GHS product identifier : ARALDITE® 2012 HARDENER/HAERTER/DURCISSEUR
Product code : 00052655
Other means of identification : Not available.
Product type : Liquid.
Material uses : Component for adhesive applications
Supplier's details : Huntsman Advanced Materials Americas LLC
P.O. Box 4980
The Woodlands, TX 77387

Non-Emergency phone: (800) 257-5547

e-mail address of person responsible for this SDS : MSDS@huntsman.com


Emergency telephone number (24h/7day) : Chemtrec: (800) 424-9300 or (703) 527-3887

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): ORAL [brain] - Category 2
AQUATIC HAZARD (LONG-TERM) - Category 3
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 90.1%
Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 90.1%

GHS label elements

Hazard pictograms : 

Signal word : Warning

Hazard statements : Causes skin and eye irritation.
May cause damage to organs through prolonged or repeated exposure if swallowed. (brain)
Harmful to aquatic life with long lasting effects.

Section 2. Hazards identification

Precautionary statements : Wear protective gloves: > 8 hours (breakthrough time): Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber. Wear eye or face protection. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling. Get medical attention if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
triethylene glycol dimercaptan	1 - 3	14970-87-7
DIMETHYL DIPROPYL TRIAMINE	1 - 3	10563-29-8
2,4,6-tris(dimethylaminomethyl)phenol	1 - 3	90-72-2
N,n,4-trimethylpiperazine-1-ethylamine	1 - 3	104-19-8
N-butyl acetate	1 - 3	123-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : No specific treatment. Treat symptomatically. Call medical doctor or poison control center immediately if large quantities have been ingested.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

- Flash point** : Closed cup: >100°C (>212°F) [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)]
Open cup: 102°C (215.6°F)

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
Carbon monoxide
nitrogen oxides
sulfur oxides
halogenated compounds

Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Methods and materials for containment and cleaning up** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** :

Section 7. Handling and storage

Store between the following temperatures: 2 to 40°C (35.6 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
N-butyl acetate	ACGIH TLV (United States, 6/2013). TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes. OSHA PEL (United States, 2/2013). TWA: 150 ppm 8 hours. TWA: 710 mg/m ³ 8 hours.

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Ethyl Vinyl Alcohol Laminate (EVAL), butyl rubber
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Thermal hazards** : Not available.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid. [Viscous liquid.]
- Color** : Light yellow
- Odor** : Repulsive.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/Freezing point** : Not available.
- Boiling/condensation point** : >200°C (>392°F)
- Flash point** : Closed cup: >100°C (>212°F) [DIN 51758 EN 22719 (Pensky-Martens Closed Cup)]
Open cup: 102°C (215.6°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : <0.001 kPa (<0.0075 mm Hg) [room temperature]
- Vapor density** : Not available.
- Relative density** : Not available.
- Solubility in water** : practically insoluble
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : >200°C (>392°F)
- Density** : 1.165 g/cm³ [25°C (77°F)]
- Viscosity** : Dynamic (room temperature): 20000 to 40000 mPa·s (20000 to 40000 cP)

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.

Section 10. Stability and reactivity

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Test	Endpoint	Species	Result
DIMETHYL DIPROPYL TRIAMINE	Unknown guidelines	LD50 Dermal	Rabbit	1310 mg/kg
2,4,6-tris (dimethylaminomethyl) phenol	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	1669 mg/kg
	Unknown guidelines	LD50 Dermal	Rat - Male	>971 mg/kg
N,n, 4-trimethylpiperazine-1-ethylamine	OECD 401 Acute Oral Toxicity	LD50 Oral	Rat - Male, Female	2169 mg/kg
	-	LD50 Dermal	Rabbit	448 mg/kg
N-butyl acetate	-	LD50 Oral	Rat	677 mg/kg
	-	LD50 Dermal	Rabbit	>17600 mg/kg
	-	LD50 Oral	Guinea pig	4700 mg/kg
	-	LD50 Oral	Mouse	7060 mg/kg
	-	LD50 Oral	Rabbit	7437 mg/kg
ARALDITE 2012 HARDENER/HAERTER/ DURCISSEUR	-	LD50 Oral	Rat	>8800 mg/kg
	-	LD50 Dermal	Rat - Male, Female	>4000 mg/kg
	-	LD50 Oral	Rat	2631 mg/kg

Irritation/Corrosion

Product/ingredient name	Test	Species	Result
DIMETHYL DIPROPYL TRIAMINE	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Corrosive
2,4,6-tris(dimethylaminomethyl) phenol	OECD 404 Acute Dermal Irritation/Corrosion	Rabbit	Skin - Corrosive
ARALDITE 2012 HARDENER/ HAERTER/DURCISSEUR	EPA CFR	Rabbit	Eyes - Corrosive
	-	Rabbit	Skin - Non-irritant.

Conclusion/Summary

Skin : Non-irritating to the skin.

triethylene glycol : No additional information.

dimercaptan : No additional information.

DIMETHYL DIPROPYL TRIAMINE : Corrosive to the skin.

2,4,6-tris (dimethylaminomethyl) phenol : Corrosive to the skin.

N,n, 4-trimethylpiperazine-1-ethylamine : No additional information.

N-butyl acetate : No additional information.

Section 11. Toxicological information

Eyes	:	triethylene glycol dimercaptan	No additional information.
		DIMETHYL DIPROPYL TRIAMINE	No additional information.
		2,4,6-tris (dimethylaminomethyl) phenol	Corrosive to eyes.
		N,n, 4-trimethylpiperazine-1-ethylamine	No additional information.
		N-butyl acetate	No additional information.
	Respiratory	:	triethylene glycol dimercaptan
		DIMETHYL DIPROPYL TRIAMINE	No additional information.
		2,4,6-tris (dimethylaminomethyl) phenol	No additional information.
		N,n, 4-trimethylpiperazine-1-ethylamine	No additional information.
		N-butyl acetate	No additional information.

Sensitization

Product/ingredient name	Test	Route of exposure	Species	Result
DIMETHYL DIPROPYL TRIAMINE	OECD 406 Skin Sensitization	skin	Guinea pig	Sensitizing
2,4,6-tris (dimethylaminomethyl) phenol	OECD 406 Skin Sensitization	skin	Guinea pig	Not sensitizing
N-butyl acetate	-	skin	Guinea pig	Not sensitizing

Mutagenicity

Product/ingredient name	Test	Result
DIMETHYL DIPROPYL TRIAMINE	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	Experiment: In vitro Subject: Mammalian-Animal Metabolic activation: +/-	Negative
2,4,6-tris (dimethylaminomethyl)phenol	Experiment: In vitro Subject: Mammalian-Human Metabolic activation: +/-	Negative
	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
N-butyl acetate	Experiment: In vitro Subject: Mammalian-Animal Cell: Somatic Metabolic activation: +/-	Negative
	Experiment: In vitro Subject: Mammalian-Human Cell: Somatic Metabolic activation: +/-	Negative
	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative

Section 11. Toxicological information

Conclusion/Summary :

DIMETHYL DIPROPYL TRIAMINE
2,4,6-tris (dimethylaminomethyl) phenol

Not mutagenic in a standard battery of genetic toxicological tests.
Not mutagenic in a standard battery of genetic toxicological tests.

Carcinogenicity

Product/ingredient name	Test	Species	Dose	Exposure	Result/Result type
DIMETHYL DIPROPYL TRIAMINE	No official guidelines	Mouse - Male	-	20 months; 3 days per week	Negative - Dermal - NOAEL

Reproductive toxicity

Product/ingredient name	Test	Species	Maternal toxicity	Fertility	Developmental effects
2,4,6-tris (dimethylaminomethyl) phenol	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Rat - Male, Female	Negative	Negative	Negative

Teratogenicity

Product/ingredient name	Test	Species	Result/Result type
DIMETHYL DIPROPYL TRIAMINE	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Rat - Male, Female	Positive - Oral

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
N-butyl acetate	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,4,6-tris(dimethylaminomethyl)phenol	Category 2	Oral	brain

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Section 11. Toxicological information

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation.
- Ingestion** : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Product/ingredient name	Test	Endpoint	Species	Result
DIMETHYL DIPROPYL TRIAMINE	OECD 408 Repeated Dose 90-Day Oral Toxicity Study in Rodents	Sub-chronic NOAEL Oral	Rat - Male, Female	1000 ppm
2,4,6-tris (dimethylaminomethyl) phenol	No official guidelines	Chronic NOAEL Dermal	Mouse - Male	>56.3 mg/kg/d
	No official guidelines	Sub-acute NOEC Inhalation Vapor	Rat - Male, Female	550 mg/m ³
	OECD 422 Combined Repeated Dose Toxicity Study with the Reproduction/ Developmental Toxicity Screening Test	Sub-acute NOEL Oral	Rat - Male, Female	15 mg/kg

- General** : May cause damage to organs through prolonged or repeated exposure if swallowed. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.

Section 11. Toxicological information

- Teratogenicity** : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information : Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Test	Endpoint	Exposure	Species	Result
DIMETHYL DIPROPYL TRIAMINE	DIN DIN 38412 Part 8	Acute EC50	16 hours Static	Bacteria	181 mg/l
	OECD 202 <i>Daphnia</i> sp. Acute Immobilisation Test	Acute EC50	48 hours Static	Daphnia	9.2 mg/l
	OECD 201 Alga, Growth Inhibition Test	Acute ErC50 (growth rate)	72 hours Static	Algae	21 mg/l
	OECD 203 Fish, Acute Toxicity Test	Acute LC50	96 hours Static	Fish	>100 mg/l
	OECD 201 Alga, Growth Inhibition Test	Chronic LOAEL	72 hours Static	Algae	5.7 mg/l
2,4,6-tris (dimethylaminomethyl)phenol	OECD 201 Alga, Growth Inhibition Test	Acute ErC50 (growth rate)	72 hours Static	Algae	84 mg/l
	Unknown guidelines	Acute LC50	96 hours Static	Daphnia	718 mg/l
N-butyl acetate	-	Acute LC50	96 hours Static	Fish	175 mg/l
	-	Chronic NOEC	72 hours	Algae	6.25 mg/l
	-	Acute EC50	72 hours	Algae	674.7 mg/l
	-	Acute EC50	24 hours	Daphnia	205 mg/l
	-	Acute EC50	96 hours	Fish	185 mg/l
-	Acute IC0	24 hours	Bacteria	1200 mg/l	

Persistence and degradability

Product/ingredient name	Test	Period	Result
DIMETHYL DIPROPYL TRIAMINE	ISO ISO 7827, 1984 - Evaluation in an aqueous medium of the ultimate aerobic biodegradability of organic compounds	28 days	100 %
2,4,6-tris (dimethylaminomethyl)phenol	OECD 301D Ready Biodegradability - Closed Bottle Test	28 days	4 %
N-butyl acetate	-	28 days	98 %

Section 12. Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
DIMETHYL DIPROPYL TRIAMINE	-	-	Readily
2,4,6-tris (dimethylaminomethyl)phenol	-	-	Not readily
N-butyl acetate	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
DIMETHYL DIPROPYL TRIAMINE	0.5	-	low
2,4,6-tris (dimethylaminomethyl)phenol	0.219	-	low
N-butyl acetate	-	4 to 14	low

Mobility in soil

Not available.

Other adverse effects : No known significant effects or critical hazards.

Other ecological information

BOD5 : Not determined.

COD : Not determined.

TOC : Not determined.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information

Proper shipping name

DOT : Not regulated.

TDG : Not regulated.

IMDG : Not regulated.

IATA : Not regulated.

Section 14. Transport information

Regulatory information	UN number	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-		-
TDG Classification	Not regulated.	-	-		-
IMDG Classification	Not regulated.	-	-		-
IATA Classification	Not regulated.	-	-		-

PG* : Packing group

Section 15. Regulatory information

Safety, health and environmental regulations specific for the product

United States Regulations

TSCA 8(b) inventory : All components are listed or exempted.

TSCA 5(a)2 final significant new use rule (SNUR) : No ingredients listed.

TSCA 5(e) substance consent order : No ingredients listed.

TSCA 12(b) export notification : No ingredients listed.

SARA 311/312 : Immediate (acute) health hazard
Delayed (chronic) health hazard

Clean Air Act - Ozone Depleting Substances (ODS) : This product does not contain nor is it manufactured with ozone depleting substances.

SARA 313 : No ingredients listed.

CERCLA Hazardous substances : No ingredients listed.

State regulations

PENNSYLVANIA - RTK : N-butyl acetate

California Prop 65 : This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

Canadian regulations

CEPA DSL : At least one component is not listed.

Section 15. Regulatory information

WHMIS Classes : Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Brazil Regulations

Classification system used : Norma ABNT-NBR 14725-2:2012

International lists

Australia inventory (AICS): All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Japan inventory: Not determined.
Korea inventory: All components are listed or exempted.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): At least one component is not listed.
Taiwan inventory (CSNN): Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.) :

Health	2
Flammability	1
Physical hazards	0
Personal protection	

The customer is responsible for determining the PPE code for this material.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

National Fire Protection Association (U.S.A.) :



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing : 9/30/2014.

Date of issue : 9/30/2014.

Date of previous issue : 9/30/2014.

Version : 2

Section 16. Other information

✔ Indicates information that has changed from previously issued version.

ARALDITE® is a registered trademark of Huntsman Corporation or an affiliate thereof in one or more countries, but not all countries.

Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

Distributed by:
Rudolph Bros. & Co.
6550 Oley Speaks Way
Canal Winchester, OH 43110
Phone: 614-833-0707
Fax: 800-600-9508
e-mail: rbcsupport@rudbro.com
www.rudbro.com