





# Safety Data Sheet



Revision Number: 005.0

Issue date: 04/05/2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:294 ThProduct type:AnaeroRestriction of Use:None idCompany address:Henkel CorporationOne Henkel WayRocky Hill, Connecticut 06067

**294 Threadlocker Wicking Grade** Anaerobic Sealant None identified IDH number:232774Item number:27936Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCYPhone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCYPhone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: w ww.henkelna.com

#### 2. HAZARDS IDENTIFICATION

 EMERGENCY OVERVIEW

 DANGER:
 HARMFUL IF SWALLOWED.

 CAUSES SKIN IRRITATION.

 MAY CAUSE AN ALLERGIC SKIN REACTION.

 CAUSES SERIOUS EYE IRRITATION.

 FATAL IF INHALED.

 SUSPECTED OF CAUSING CANCER.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY INHALATION	1
SKIN IRRITATION	2
EYEIRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2



#### **Precautionary Statements**

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke w hen using this product. Use only outdoors or in a w ell-ventilated area. Contaminated w ork clothing should not be allow ed out of the w orkplace. Wear protective gloves, clothing, eye and face protection. [In case of inadequate ventilation] w ear respiratory protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of w ater. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with w ater for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store locked up.

#### Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CASNumber	Percentage*	
1H-Pyrrole-2,5-dione, 1-phenyl-	941-69-5	10 - 20	
Bisphenol A, 2-EO dimethacrylate	41637-38-1	5 - 10	
Cumene hydroperoxide	80-15-9	0.1 - 1	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4	. FIRST AID MEASURES
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. Get medic attention.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.
5. F	IRE FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

RUDOLPH

BROS. E. CO

Do not allow product to enter sew er or waterways.

IDH number: 232774

Page 2 of 6

Product name: 294 Threadlocker Wicking Grade



Clean-up methods:

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wearfull protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

### 7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Do not taste or sw allow. Refer to Section 8.

Storage:

For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, w ell ventilated area aw ay fromheat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
1H-Pyrrole-2,5-dione, 1-phenyl-	None	None	None	None
Bisphenol A, 2-EO dimethacrylate	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
1-Acetyl-2-phenylhydrazine	None	None	None	None
Engineering controls: Respiratory protection:	exp	ride adequate local exhaus osure limits. NIOSH approved respirato s).		·
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety show ers and eye wash stations should be available.			
Skin protection:	apro	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.		

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/range: Specific gravity: Vapor density: Flash point: Flam mable/Explosive limits - low er: Flam mable/Explosive limits - upper: Autoignition temperature: Flam mability: Liquid Green Mild Not available. Not applicable  $0.7 \text{ kPa} (20 ^{\circ} \text{C} (68 ^{\circ} \text{F}))$ > 149  $^{\circ} \text{C} (> 300.2 ^{\circ} \text{F})$ Not available. 1.1229 Not available. > 93.3  $^{\circ} \text{C} (> 199.94 ^{\circ} \text{F})$  Tagliabue closed cup Not available. Not available. Not available. Not available. Not available. Not available. Not available.

IDH number: 232774

Product name: 294 Threadlocker Wicking Grade





1-800-375-0605 Option 8 for 24/7 Service

Page 3 of 6



Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature: Not available. Slight Not available. < 4 %; < 44.92 g/l Not available. Not available.

	10. STABILITY AND REACTIVITY
Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.
Hazardous decomposition products:	Oxides of carbon. Oxides of nitrogen. Irritating organic vapours. Toxic fumes.
Incom patible materials:	lron. copper Aluminum. Rust. Zinc. Reducing agents. Strong acids and oxidizing agents. Oxygen scavengers. Strong alkalis. Peroxides. Heat, sunlight, or UV light.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition. Store aw ay from incompatible materials. Elevated temperatures.

## **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

Inhalation:	This product is harmful or fatal by inhalation.
Skin contact:	Causes skin irritation. May cause allergic skin reaction.
Eye contact:	Causes serious eye irritation.
Ingestion:	Harmful if sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
1H-Pyrrole-2,5-dione, 1-phenyl-	None	Irritant
Bisphenol A, 2-EO dimethacrylate	None	Allergen, Irritant
Cumene hydroperoxide	Inhalation LC50 (Mouse, 4 h) = 200 mg/l	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
1-Acetyl-2-phenylhydrazine	Oral LD50 (Mouse) = 270 mg/kg	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
1H-Pyrrole-2,5-dione, 1-phenyl-	No	No	No
Bisphenol A, 2-EO dimethacrylate	No	No	No
Cumene hydroperoxide	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

## 12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

IDH number: 232774

Page 4 of 6

Product name: 294 Threadlocker Wicking Grade







# **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.				
Recommended method of disposal:	Follow all local, state, federal and provincial regulations for disposal.			
Hazardous waste number:	Not a RCRA hazardous waste.			
14. TRANSPORT INFORMATION				
The transport information provided in this s package/configuration.	ection only applies to the material/formulation itself, and is not specific to an y			
U.S. Department of Transportation Ground (	49 CFR)			
Propershipping name:	Toxic, liquids, organic, n.o.s. (n-Phenylmaleimide)			
Hazard class or division:	6.1			
Identification number:	UN 2810			
Packing group:	III			
International Air Transportation (ICAO/IATA				
Propershipping name:	, Toxic liquid, organic, n.o.s. (n-PhenyImaleimide)			
Hazard class or division:	6.1			
Identification number:	UN 2810			
Packing group:				
Exceptions:	Consumer Commodity, ID 8000, Class 9, (Not more than 500 ml)			
Water Transportation (IMO/IMDG)				
Proper shipping name:	TOXIC LIQUID, ORGANIC, N.O.S. (n-Phenylmaleimide, Methylphenyl-			
	dimaleimide)			
Hazard class or division:	6.1			
Identification number:	UN 2810			
Packing group:				
Marine pollutant:	Methylphenyl-dimaleimide			

**15. REGULATORY INFORMATION** 

#### United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: CERCLA Reportable quantity:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis. Cumene hydroperoxide (CAS#80-15-9) 10 lbs. (4.54 kg)
California Proposition 65:	This product contains a chemical know n in the State of California to cause cancer. This product contains a chemical know n to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

## **16. OTHER INFORMATION**

This safety data sheet contains changes from the previous version in sections: 2

IDH number: 232774

Page 5 of 6

Product name: 294 Threadlocker Wicking Grade





rvice



Prepared by:

#### Product Safety and Regulatory Affairs

**Issue date:** 04/05/2018


**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 232774

Product name: 294 Threadlocker Wicking Grade

Page 6 of 6







www.rudolphbros.com rbcsupport@rudbro.com