

# Cyberbond™ 6070

Version 1.1 Revision Date 09/03/2019

#### Authorized Distributor

# RUDOLPH BROS. & CO. ADHERING TO QUALITY



#### 1-800-375-0605 www.rudolphbros.com

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : Cyberbond™ 6070 Product code : 100000004762

#### Manufacturer or supplier's details

Company : H.B. Fuller Engineering Adhesives

Address : 9001 W Fey Drive Frankfort, IL, 60423 Telephone : 1-815-464-5606

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent based adhesive

Restrictions on use : For industrial use only.

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	liquid
Color	colorless
Odor	solvent

#### **GHS Classification**

Flammable liquids : Category 2 Aspiration hazard : Category 1

**GHS label elements** 

Hazard pictograms





Signal Word : Danger

#### **Hazard Statements:**

H225 Highly flammable liquid and vapor. H304 May be fatal if swallowed and enters airways.

#### **Precautionary Statements:**

**Prevention:** P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P280 Wear protective gloves/ eye protection/ face protection.

Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P303 +



# Cyberbond™ 6070

Version 1.1 Revision Date 09/03/2019

P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P331 Do NOT induce vomiting. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:** P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

#### **Potential Health Effects**

Carcinogenicity:

**IARC** Group 2B: Possibly carcinogenic to humans

Distillates (petroleum), light 68410-97-9

distillate hydrotreating process,

low-boiling

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	90 - 100
cyclohexane	110-82-7	1 - 5
1,8-diazabicyclo[5.4.0]undec-7-ene	6674-22-2	0.1 - 1

#### **SECTION 4. FIRST AID MEASURES**

General advice : Show this material safety data sheet to the doctor in

attendance.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off with soap and water.

Get medical attention if irritation develops and persists.

In case of eye contact : Flush eyes with water at least 15 minutes. Get medical

attention if eye irritation develops or persists.

If swallowed : Do NOT induce vomiting.

If victim is fully conscious, give a cupful of water.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

# Cyberbond™ 6070

Version 1.1 Revision Date 09/03/2019

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Specific hazards during fire

fighting

: Cool closed containers exposed to fire with water spray.

Special protective equipment

for fire-fighters

: In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.

Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions** 

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

Sweep up and shovel into suitable containers for disposal.

Non-sparking tools should be used.

#### **SECTION 7. HANDLING AND STORAGE**

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.

Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces.

Keep container closed when not in use.

Take precautionary measures against static discharges.

Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.

Use explosion-proof equipment.

Keep containers tightly closed in a dry, cool and well-

ventilated place.

Keep away from sources of ignition - No smoking.

Solvent vapors are heavier than air and may spread along

floors.

Materials to avoid : Strong oxidizing agents

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Cyberbond™ 6070

Version 1.1 Revision Date 09/03/2019

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
cyclohexane	110-82-7	TWA	100 ppm	ACGIH
		TWA	300 ppm 1,050 mg/m3	OSHA Z-1
		TWA	300 ppm 1,050 mg/m3	OSHA P0
		PEL	300 ppm 1,050 mg/m3	CAL PEL

**Engineering measures** : Use local exhaust ventilation or other engineering controls to

minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

Hand protection

Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

Hygiene measures : Avoid contact with skin, eyes and clothing.

Provide adequate ventilation.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid
Color : colorless
Odor : solvent

Odor Threshold : No data available

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : -4 °C

Evaporation rate : not determined

Upper explosion limit : Upper flammability limit

not determined

# Cyberbond™ 6070

Version 1.1 Revision Date 09/03/2019

Lower explosion limit : Lower flammability limit

not determined

Density : 0.68 g/cm3

Solubility(ies)

Water solubility : not determined
Partition coefficient: n- : No data available

octanol/water

Autoignition temperature : not determined

Viscosity

Viscosity, kinematic : not determined

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Heat, flames and sparks.

Hazardous decomposition

products

: Stable under normal conditions.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

**Components:** 

cyclohexane:

Acute inhalation toxicity : LC50 Rat: 13.9 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

# Cyberbond™ 6070

Version 1.1

Revision Date 09/03/2019

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

#### STOT-single exposure

No data available

#### STOT-repeated exposure

No data available

#### **Aspiration toxicity**

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

# Components: cyclohexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 3.96 - 5.18

mg/l

Exposure time: 96 h

Test Method: flow-through test

#### Persistence and degradability

No data available

**Bioaccumulative potential** 

#### Mobility in soil

No data available

#### Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : This product meets the definition of hazardous waste under

the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial

authorities for more restrictive requirements.

The hazard and precautionary statements displayed on the

label also apply to any residues left in the container.

# Cyberbond™ 6070

Version 1.1 Revision Date 09/03/2019

#### **SECTION 14. TRANSPORT INFORMATION**

#### Special precautions for user

Not applicable

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : 1268

Proper shipping name : Petroleum distillates, n.o.s.

Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : no

#### **International Regulations**

**IATA-DGR** 

UN/ID No. : 1268

Proper shipping name : Petroleum distillates, n.o.s.

Class : 3
Packing group : II
Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

**IMDG-Code** 

UN number : 1268

Proper shipping name : PETROLEUM DISTILLATES, N.O.S.

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15. REGULATORY INFORMATION**

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Aspiration hazard



Cyberbond™ 6070					
Version 1.1	Revision Date 09/03/2019				
SARA 302	: This material does not contain any comp EHS TPQ.	ponents with a section 302			
SARA 313	: The following components are subject to by SARA Title III, Section 313:	o reporting levels established			
	cyclohexane	110-82-7			

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### **US State Regulations**

California Prop 65 : Please contact Supplier for more information.

#### The ingredients of this product are reported in the following inventories:

**TSCA** All substances listed as active on the TSCA inventory **DSL** All components of this product are on the Canadian DSL **AICS** On the inventory, or in compliance with the inventory **ENCS** On the inventory, or in compliance with the inventory **KECI** On the inventory, or in compliance with the inventory **PICCS** On the inventory, or in compliance with the inventory **IECSC** On the inventory, or in compliance with the inventory Inventories LegendTSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV

#### **SECTION 16. OTHER INFORMATION**

(Taiwan)

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com


# Cyberbond™ 6070

Version 1.1

Revision Date 09/03/2019

#### **Further information**





#### HMIS III:

HEALTH	3
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.

#### **Authorized Distributor**



1-800-375-0605 www.rudolphbros.com