

USA SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LORD 850

Product Use/Class: Acrylic Adhesive, Part 1 of 2

LORD Corporation 111 LORD Drive Cary, NC 27511-7923 USA

Cary, NC 27311-7923 USA

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 04/08/2020

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Flammable liquids Category 2

Acute toxicity Oral Category 4 - 32.5% of the mixture consists of ingredient(s) of unknown toxicity.

Skin corrosion/irritation Category 1B

Serious eye damage/eye irritation Category 1

Skin sensitization Category 1

Respiratory sensitization Category 1

Reproductive toxicity Category 2

Specific target organ systemic toxicity (single exposure) Category 1 Respiratory system

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (single exposure) Category 2 Central nervous system

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (repeated exposure) Category 1 upper respiratory system, Respiratory

system, Nervous system

Hazardous to the aquatic environment - acute hazard Category 3 Hazardous to the aquatic environment - chronic hazard Category 3

GHS LABEL ELEMENTS: Symbol(s)

ymbol(s)









Signal Word

DANGER

Hazard Statements

Highly flammable liquid and vapor.

Harmful if swallowed.

Causes severe skin burns and eye damage.

Causes serious eye damage.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.(Respiratory system)

May cause drowsiness or dizziness.

May cause damage to organs.(Central nervous system)

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure. (upper respiratory system, Respiratory system,

Nervous system)

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Immediately call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Wash contaminated clothing before reuse.

Storage

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).


Acute: May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May cause headache and nausea.

Chronic: May cause kidney damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Range	
Methyl methacrylate	80-62-6	45 - 50 %	
Methacrylate monomer	PROPRIETARY	10 - 15 %	
Methacrylate phosphate ester	PROPRIETARY	1 - 5 %	
Amine curative	PROPRIETARY	1 - 5 %	
Amine catalyst	PROPRIETARY	1 - 5 %	







Methacrylic acid	79-41-4	1 - 5 %
Paraffin wax	PROPRIETARY	1 - 5 %
Methacrylate blend	PROPRIETARY	0.9 - 1 %
Methacrylate monomer	PROPRIETARY	0.1 - 0.9 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention. Immediately flush eyes continuously with lukewarm, gently flowing water for at least 30 minutes. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur. Wash clothing before reuse.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog **UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Avoid contact.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Contain and remove with inert absorbent material and non-sparking tools. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form.

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat,





sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

STORAGE: Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

Chemical Name	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	Skin
Methyl methacrylate	50 ppm	100 ppm	410 mg/m3 100 ppm	N.E.	N.A.
Methacrylate monomer	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylate phosphate ester	N.E.	N.E.	N.E.	N.E.	N.A.
Amine curative	N.E.	N.E.	N.E.	N.E.	N.A.
Amine catalyst	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylic acid	20 ppm	N.E.	N.E.	N.E.	S
Paraffin wax	2 mg/m3	N.E.	N.E.	N.E.	N.A.
Methacrylate blend	N.E.	N.E.	N.E.	N.E.	N.A.
Methacrylate monomer	N.E.	N.E.	N.E.	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact. If contact with the product is prolonged or repeated, Silver Shield or Butyl rubber gloves are recommended.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR: Acrylic VAPOR PRESSURE: N.D.

APPEARANCE: Amber VAPOR DENSITY: Heavier than Air PHYSICAL STATE: Paste LOWER EXPLOSIVE LIMIT: 1.6 %(V)
FLASH POINT: 59 °F, 15 °C Setaflash UPPER EXPLOSIVE LIMIT: 8.8 %(V)







Closed Cup

BOILING RANGE: N.A. EVAPORATION RATE: Faster than n-butyl-

acetate.

AUTOIGNITION TEMPERATURE: N.D. DENSITY: 0.97 g/cm3 - 8.11 lb/gal

 DECOMPOSITION TEMPERATURE:
 N.D.
 VISCOSITY, DYNAMIC:
 ≥250,000 mPa.s @ 25 °C

 ODOR THRESHOLD:
 N.D.
 VISCOSITY, KINEMATIC:
 ≥257,732 mm2/s @ 25

°C

SOLUBILITY IN H2O: Insoluble VOLATILE BY WEIGHT: 0.03 % PH: N.A. VOLATILE BY VOLUME: 0.03 %

FREEZE POINT: N.D. VOC CALCULATED: 0 lb/gal, 0 g/l0 g/l

COEFFICIENT OF WATER/OIL N.D.

DISTRIBUTION:

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures. Sources of ignition.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, Ammonia, Oxides of nitrogen,

Nitric acid

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Chemical Name	<u>LD50/LC50</u>	
Methyl methacrylate	Oral LD50: Rat 8,420 - 10,000 mg/kg	
	Dermal LD50: Rabbit > 5 g/kg	
	Dermal LD50: Rabbit 5,000 - 7,500 mg/kg	
	Inhalation LC50: Rat 78 mg/l /4 h Inhalation LC50: Rat 7093 ppm/4 h	
Methacrylate monomer	Oral LD50: Rat > 2,000 mg/kg	
Methacrylate phosphate ester	Oral LD50: rat > 5,000 mg/kg	
Amine curative	Oral LD50: Rat 25 mg/kg	
Amine catalyst	Oral LD50: Rat 1,700 mg/kg	
	Dermal LD50: Rabbit 3,200 mg/kg	
Methacrylic acid	Oral LD50: Rat 1,060 mg/kg	
	Dermal LD50: Rabbit 500 - 1,000 mg/kg	
	GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l GHS LC50	
	(dust and mist): Acute toxicity point estimate 1.5 mg/l	
Paraffin wax	Oral LD50: Rat > 5,000 mg/kg	
	Dermal LD50: Rabbit > 3,600 mg/kg	
Methacrylate blend	Oral LD50: rat > 5,000 mg/kg	
	Dermal LD50: rat > 2,000 mg/kg	
Methacrylate monomer	Oral LD50: Rat 5,050 mg/kg	
	Dermal LD50: Rabbit > 3,000 mg/kg	





Germ cell mutagenicity: No classification proposed

Carcinogenicity: No classification proposed

Reproductive toxicity: Category 2 - Suspected of damaging fertility or the unborn child. Components contributing to classification: Methacrylate monomer. Amine catalyst.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity	
Methyl methacrylate	Fish: Pimephales promelas 243 - 275 mg/l96 h flow-through Pimephales promelas 125.5 - 190.7 mg/l96 h Static Lepomis macrochirus 170 - 206 mg/l96 h flow-through Lepomis macrochirus 153.9 - 341.8 mg/l96 h Static Oncorhynchus mykiss > 79 mg/l96 h flow-through Oncorhynchus mykiss > 79 mg/l96 h Static Poecilia reticulata 326.4 - 426.9 mg/l96 h Static Invertebrates: Daphnia magna 69 mg/l48 h Plants: Pseudokirchneriella subcapitata 170 mg/l96 h	
Methacrylate monomer	Fish: Oryzias latipes 2.78 mg/l96 h semi-static	
Methacrylate phosphate ester	Fish: Oncorhynchus mykiss > 112 mg/l96 h Static	
Amine curative	Fish: Brachydanio rerio 17 mg/l96 h Static Danio rerio 17 mg/l96 h Static Invertebrates: Daphnia magna (Water flea) 28.8 mg/l48 h Static	
Amine catalyst	Fish: Pimephales promelas 1,510 - 1,980 mg/l96 h flow-through	
Methacrylic acid	Fish: Oncorhynchus mykiss 85 mg/l96 h flow-through	
Paraffin wax	N.D.	
Methacrylate blend	Fish: Danio rerio 590 mg/l96 h flow-through	
Methacrylate monomer	<u>Fish:</u> Pimephales promelas 213 - 242 mg/l96 h flow-through Pimephales promelas 227 mg/l96 h	

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14. TRANSPORT INFORMATION

US DOT Road

Proper Shipping Name: Adhesives

Hazard Class: 3
SECONDARY HAZARD: None
UN/NA Number: 1133
Packing Group: II





Emergency Response Guide Number: 128

IATA Cargo

PROPER SHIPPING NAME: Adhesives

Hazard Class: 3
HAZARD CLASS: None
UN NUMBER: 1133
PACKING GROUP: II
EMS: 3L

IMDG

PROPER SHIPPING NAME: Adhesives

Hazard Class:3HAZARD CLASS:NoneUN NUMBER:1133PACKING GROUP:IIEMS:F-E

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

<u>Chemical Name</u> <u>CAS Number</u> <u>Weight % Less Than</u>

Methyl methacrylate 80-62-6 50.0 %

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

The chemical substances in this product are on the TSCA Section 8 Inventory.

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2* FLAMMABILITY: 3 PHYSICAL HAZARD: 1

* - Indicates a chronic hazard; see Section 2

Revision: Section 2, Section 11

Effective Date: 04/08/2020

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by







use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.



