

Safety Data Sheet



Revision Number: 004.8 Issue date: 09/18/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE M-CR 1500 AERO known IDH number:

as ALODINE 1500(AERO DIST ONLY)

Product type/use: Coating
Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: United States **Contact information:**

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

595833

1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTAINS FLUORIDES. MAY CAUSE DELAYED BURNS (NOT

IMMEDIATELY PAINFUL OR VISIBLE)! LONG TERM EXPOSURE TO

FLUORIDES OVER YEARS MAY CAUSE FLUOROSIS! CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE AN ALLERGIC SKIN REACTION.

MAY CAUSE CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
CARCINOGENICITY	1A

PICTOGRAM(S)



Precautionary Statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protection

protective gloves, clothing, eye and face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

IDH number: 595833

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Chromic acid	7738-94-5	5 - 10
Ammonium hexafluorozirconate	16919-31-6	1 - 5

Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Remove contaminated clothing and footwear while rinsing the affected area

with large amounts of running water for at least 15 minutes. GET IMMEDIATE MEDICAL ATTENTION. If iced solution of 0.13% aqueous Benzalkonium Chloride (Zephiran) or 2.5% calcium gluconate gel is available, rinsing may be limited to 5 minutes, with the soak solution or gel applied as soon as the rinsing is stopped. Gloves should be worn when applying the gel to prevent transfer of HF and secondary burns. If using calcium gluconate gel, it should be continuously re-applied and massaged into the affected area until pain has been relieved for at least 30 minutes. If Benzalkonium Chloride (Zephiran) or calcium gluconate gel is not available, rinsing must continue until medical treatment is provided.

For skin contact, flush with large amounts of water. Seek immediate medical attention. If irritation persists, repeat flushing and get medical attention. Discard any shoes or clothing items that cannot be decontaminated.

Eye contact: Immediately flush affected eye with large amounts of gently flowing water or

0.9% sterile saline solution for at least 15 minutes. Hold eyelid wide open. Get immediate medical attention. Eye flushing should continue during

transportation to a doctor.

Ingestion: Get immediate medical attention. Do not induce vomiting. Attempt immediate

administration of a fluoride binding substance: milk, chewable calcium carbonate tablets or 4-8 ounces (120-240 ml) of milk of magnesia or a liquid antacid. Avoid large amounts of liquid as it may induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: Treatment of hypocalcemia associated with corrosive fluoride compounds

exposure may be corrected by intravenous calcium gluconate or calcium chloride. Treatment of hypomagnesemia may be corrected by intravenous

magnesium sulfate.

5. FIRE FIGHTING MEASURES

Water spray (fog), foam, dry chemical or carbon dioxide. Extinguishing media:

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Hydrogen fluoride.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Block any potential routes

to water systems.

Product name: BONDERITE M-CR 1500 AERO known as ALODINE 1500(AERO DIST ONLY) IDH number: 595833

Page 2 of 6







Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Do not take internally. For industrial use only. Clothing or other material wet with this product and allowed to dry may

become flammable.

Storage: For safe storage, store at or above 40 °F (4.4 °C)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Chromic acid	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. (Dermal sensitization) (Respiratory sensitization)	0.005 mg/m3 TWA 0.0025 mg/m3 OSHA_ACT 0.1 mg/m3 Ceiling	None	None
Ammonium hexafluorozirconate	5 mg/m3 TWA (as Zr) 10 mg/m3 STEL (as Zr)	5 mg/m3 PEL (as Zr)	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or Respiratory protection:

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Use of impervious apron and boots

are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Orange-red Odor: Bland Odor threshold: Not available. pH: < 2 Vapor pressure: Not determined > 212 °F (> 100°C) Boiling point/range: Melting point/ range: 27 °F (-2.8 °C) 1.03 - 1.06 Specific gravity: Vapor density: Not determined > 100 °C (> 212°F) Flash point: Flammable/Explosive limits - lower: Not applicable Flammable/Explosive limits - upper: Not applicable Autoignition temperature: Not applicable Flammability: Not applicable **Evaporation rate:** Not available.

Product name: BONDERITE M-CR 1500 AERO known as ALODINE 1500(AERO DIST ONLY) IDH number: 595833

Page 3 of 6







Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Complete

Not determined

Not applicable

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. May liberate hydrogen fluoride.

Incompatible materials: Avoid contact with organic materials, oils, greases, and any oxidizable materials.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns. Prolonged or repeated breathing

may cause ulceration of nasal membranes. Contains fluorides. Exposure to fluorides over

years may cause fluorosis.

Skin contact: Product contains chromium, which may cause an allergic skin sensitization reaction. Contact

with broken skin may lead to formation of firmly marginated "chrome sores". This product is severely irritating to the skin and may cause burns. Massive overexposures may lead to kidney failure and death. Liquid or vapor can cause fluoride-type irritation or burns which may not be immediately painful or visible. Hydrofluoric acid will penetrate the skin and attack underlying tissue and bone. Large burns (over 25 square inches) may also cause hypocalcemia and other

systemic effects which may be fatal.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness.

Ingestion: Ingestion of small amounts of this product may result in potentially fatal hypocalcemia and

systemic toxicity. Ingestion of large amounts of this product may result in fluoride poisoning including symptoms of calcification of the ligaments and severe bone changes making normal movements painful, mottling of the teeth, pulmonary fibrosis, anemia, anorexia, dental effects, and possibly death. Ingestion causes burns of the upper digestive and respiratory tracts.

Contains fluorides. Exposure to fluorides over years may cause fluorosis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Chromic acid	None	Allergen, Blood, Carcinogen, Central nervous system, Corrosive, Developmental, Eyes, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Reproductive, Respiratory
Ammonium hexafluorozirconate	None	Allergen, Blood, Cardiac, Central nervous system, Corrosive, Gastrointestinal tract, Irritant, Kidney, Lung, Metabolic, Muscle, Teeth, Less weight gain and food intake.

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Chromic acid	Known To Be Human Carcinogen.	Group 1	Yes
Ammonium hexafluorozirconate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

IDH number: 595833 Product name: BONDERITE M-CR 1500 AERO known as ALODINE 1500(AERO DIST ONLY)

Page 4 of 6







DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: This product, if discarded directly, would be a characteristic RCRA corrosive

waste (D002). This product contains chromium which is a hazardous waste (D007). Wastes must be tested using methods described in 40 CFR Part 261

to determine if it meets applicable definitions of hazardous wastes.

TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Chromic acid solution

Hazard class or division:

Identification number: UN 1755 Packing group:

DOT Hazardous Substance(s): Chromic acid

International Air Transportation (ICAO/IATA)

Proper shipping name: Chromic acid solution

Hazard class or division:

Identification number: UN 1755 Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name: CHROMIC ACID SOLUTION (Chromic acid)

Hazard class or division: Identification number: UN 1755 Packing group: Ш

Marine pollutant: Chromic acid

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

Chromic acid (CAS# 7738-94-5). TSCA 12 (b) Export Notification:

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Chromic acid (CAS# 7738-94-5)

CERCLA Reportable quantity: Chromic acid (CAS# 7738-94-5) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 4, 5, 10, 11

Prepared by: Regulatory Affairs

Issue date: 09/18/2020

IDH number: 595833 Product name: BONDERITE M-CR 1500 AERO known as ALODINE 1500(AERO DIST ONLY)

Page 5 of 6







DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

Product name: BONDERITE M-CR 1500 AERO known as ALODINE 1500(AERO DIST ONLY)
Page 6 of 6



IDH number: 595833





