



# Mono-Coat® RM-1905RF

## Semi-Permanent Release Agent

### Description

Mono-Coat® RM-1905RF is a flange and vent-tube release for use in all types of roto-molding situations. Mono-Coat® RM-1905RF is a 100% solids product and has excellent thermal stability for rotational molding applications.

### Typical Properties

Appearance	Clear to Slightly Hazy Colorless Fluid
Density, lbs/gal; kg/l	8.10; 0.97
Flash Point, °F/°C	350/177
Storage Stability, unopened	24 months

### Application

1. Thoroughly clean the area to be treated with a Chem-Trend mold cleaner to remove any previous release agent or other buildup. Wipe dry with a clean cloth or towel. Then wipe with a clean solvent or naphtha and let air dry.
2. Mono-Coat® RM-1905RF should be applied with a soft-bristled brush, or wiped on with a cotton cloth.
3. To pre-treat or condition the flange or vent-tube of the mold, apply Mono-Coat® RM-1905RF in three, even coats at normal processing temperatures.
4. Reapply an even coat as necessary.

### Storage

If stored in cold temperatures, allow product to warm to room temperature prior to use.

### Handling

We believe Mono-Coat® RM-1905RF has a low degree of hazard when used as intended. For more information, request a copy of Chem-Trend's Safety Data Sheet.

### Packaging

Mono-Coat® RM-1905RF is available in a variety of package sizes. Please contact Chem-Trend customer service for details.

#### Further Information

Request information on our complete range of materials: custom-formulated release agents for polyurethane molding; tire lubes and bladder coatings; Mono-Coat® semi-permanent release coatings; aerosol formulations; mold cleaners and sealers; specialized coatings and application equipment.

*While the technical information and suggestions for use contained herein are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.*

Distributed by:  
Rudolph Bros. & Co.  
6550 Oley Speaks Way  
Canal Winchester, OH 43110  
Phone: 614-833-0707  
Fax: 800-600-9508  
e-mail: [rbcsupport@rudbro.com](mailto:rbcsupport@rudbro.com)  
[www.rudbro.com](http://www.rudbro.com)