

Revision Number: 001.1

Issue date: 12/12/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

OSI® GreenSeries™ FlameSeal® Fire,

Smoke & Draft Stop Sealant

Sealant

Product type: Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 **IDH** number:

1390035

United States Region:

Contact information:

Telephone: +1 (800) 624-7767 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-

4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

2. HAZARDS IDENTIFICATION

		. <u> </u>
	EMERGENCY OVERVIEW	
WARNING:	CAUSES EYE IRRITATION.	

	HAZARD CATEGORY	
EYE IRRITATION		28
· · · · · · · · · · · · · · · · · · ·		
	PICTOGRAM(S)	

None

Precautionary Statements

Prevention:

Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to remove. Continue rinsing. If eye imitation persists: Get medical attention.

Storage: Disposal: Not prescribed Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910,1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological Information.

3 COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	30 - 60

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections

4. FIRST AID MEASURES

Inhalation:

Move to fresh air in case of accidental inhalation of vapours.

Skin contact:

Wash affected area immediately with soap and water.

Eye contact:

Immediately flush eyes with plenty of water for at least 15 minutes. If

symptoms develop and persist, get medical attention.

Ingestion:

Consult a physician if necessary.

Symptoms:

See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:

All standard firefighting procedures.

Special firefighting procedures:

Do not breathe combustion gases. Wear protective equipment.

Unusual fire or explosion hazards:

None known.

Hazardous combustion products:

Carbon dioxide. Carbon monoxide. Hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not empty into drains.

Clean-up methods:

Scrape up spilled material and place in a closed container for disposal. Wear

appropriate protective equipment and clothing during clean-up.

7 HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Keep out of the reach of children.

Storage:

For safe storage, store between 4 °C (39.2 °F) and 32 °C (89.6 °F)

Keep from freezing. Store in a cool, dry area. Keep containers closed when

not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust	None	None

Engineering controls:

Use general ventilation and use local exhaust, where possible, in confined or

enclosed spaces.

Respiratory protection:

Not normally required. Use NIOSH approved respirator if there is potential to

exceed exposure limit(s).

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Chemical resistant, impermeable gloves. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical state:

pasty Red

Color: Odor:

Mild, aromatic Not available.

Odor threshold: pH:

8.0 - 9.0

IDH number: 1390035

Product name: OSI® GreenSeries™ FlameSeal® Fire, Smoke & Draft Stop Sealant Page 2 of 5

Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity:

18.51880 mm hg > 100 °C (> 212°F) Not available

Vapor density: Flash point:

1.40 - 1.50 at 25 °C (77°F) Heavier than air, (Air = 1) not applicable

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature:

Not available. Not available. Not available.

Evaporation rate: Solubility in water:

Partition coefficient (n-octanoi/water):

Not available. Not determined

VOC content:

1.48 %; 32.5 g/l (calculated)

Not available.

Viscosity:

Not available.

Decomposition temperature:

10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of storage and use.

Hazardous reactions:

Will not occur.

Hazardous decomposition

Incompatible materials:

Carbon dioxide. Carbon monoxide.

products:

Alkalis, Mineral acids,

Reactivity:

Not available.

Conditions to avoid:

Do not freeze.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Inhalation, Skin contact, Eyes

Potential Health Effects/Symptoms

Inhalation:

May cause irritation to nose and throat.

Skin contact:

May cause slight imitation to skin.

Eye contact:

May cause slight imitation to eyes on contact.

Ingestion:

Not expected to be harmful by ingestion, Ingestion of large amounts may produce

gastrointestinal disturbances including irritation, nausea, and diarrhea.

LD50s and LC50s		Immediate and Delayed Health Effects	
None	Nuisance dust		
NTP Carcinogen	IARC Carcinogen		OSHA Carcinogen
		None	None

	.		(Specifically Regulated)
Limestone	 No	No	No
34 (1)	12. ECOLOGICAL IN	IFORMATION :	

Ecological information:

IDH number: 1390035

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and loxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

44 TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None None

Identification number: Packing group:

None None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division: identification number: None None

Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None

Identification num Packing group: None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

None above reporting de minimis immediate Health

CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:

None above reporting de minimis

California Proposition 65:

No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16 OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by:

Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

Issue date:

IDH number: 1390035

12/12/2014

Product name: OSI® GreenSeries™ FlameSeal® Fire, Smoke & Draft Stop Sealant Page 4 of 5

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Distributed by: Rudolph Bros. & Co. 6550 Oley Speaks Way Canal Winchester, OH 43110

Phone: 614-833-0707 Fax: 800-600-9508

e-mail: rbcsupport@rudbro.com

www.rudbro.com