



Revision Number: 001.2

Issue date: 10/10/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	OSI Quad Window, Door and Siding VOC Advanced Formula Sealant	<b>IDH number:</b>	1642878
<b>Product type:</b>	SealantSolvent	<b>Region:</b>	United States
<b>Restriction of Use:</b>	None identified	<b>Contact Information:</b>	
<b>Company address:</b>	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Telephone: +1 (800) 624-7767	
		MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-627-3887	

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

### PICTOGRAM(S)



### Precautionary Statements

<b>Prevention:</b>	Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves.
<b>Response:</b>	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	10 - 30
Hydrocarbon resin	Proprietary	10 - 30
p-Chloro-a,a,a-trifluorotoluene	98-56-6	10 - 30
Aliphatic hydrocarbon	Proprietary	5 - 10
Titanium dioxide	13463-67-7	5 - 10

IDH number: 1642878

Product name: OSI Quad Window, Door and Siding VOC Advanced Formula Sealant  
Page 1 of 7

Xylenes	1330-20-7	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Distillates (petroleum), hydrotreated light	Proprietary	1 - 5
Ethylbenzene	100-41-4	0.1 - 1
Aluminum hydroxide	21645-51-2	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
<b>Ingestion:</b>	Get immediate medical attention. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.
<b>Symptoms:</b>	See Section 11.
<b>Notes to physician:</b>	Treat symptomatically and supportively.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode. Wear full protective clothing.
<b>Unusual fire or explosion hazards:</b>	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.
<b>Hazardous combustion products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

### Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not breathe fumes or dust from this material. Do not cut, grind, weld, or drill on or near this container. Do not take internally.

### Storage:

For safe storage, store between 0 °C (32°F) and 40 °C (104°F)  
Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Hydrocarbon resin	None	None	None	None
p-Chloro-a,a,a-trifluorotoluene	None	None	None	None
Aliphatic hydrocarbon	None	None	None	None
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust.	None	None
Xylenes	100 ppm TWA 150 ppm STEL	100 ppm (435 mg/m3) PEL	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Distillates (petroleum), hydrotreated light	None	None	None	None
Ethylbenzene	20 ppm TWA	100 ppm (435 mg/m3) PEL	None	None
Aluminium hydroxide	10 mg/m3 TWA (as Al) Total dust. 1 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA (as Al) Total dust. 5 mg/m3 TWA (as Al) Respirable fraction.	None	None

### Engineering controls:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

### Respiratory protection:

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

### Eye/face protection:

Safety goggles or safety glasses with side shields.

### Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical state:

Solid, Paste

### Color:

White

### Odor:

Aromatic

### Odor threshold:

Not available.

### pH:

Not applicable

### Vapor pressure:

8 mm hg (20 °C (68°F))

### Boiling point/range:

Not available.

### Melting point/ range:

Not available.

### Specific gravity:

1.3

Vapor density:	Heavier than air
Flash point:	Product is a solid. Burn Rate: <2.2mm/second
Flammable/Explosive limits - lower:	1 %
Flammable/Explosive limits - upper:	7 %
Autoignition temperature:	Not available.
Evaporation rate:	0.7 Slower than butyl acetate.
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	3.9 %; < 203 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.

## 10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	This product may react with strong acids or oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes
------------------------------	------------------------

## Potential Health Effects/Symptoms

<b>Inhalation:</b>	Inhalation of dust generated by this material may cause respiratory tract irritation.
<b>Skin contact:</b>	This product may cause irritation to the skin.
<b>Eye contact:</b>	This product may cause irritation to the eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
<b>Ingestion:</b>	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Hydrocarbon resin	None	No Records
p-Chloro-a,a,a-trifluorotoluene	None	Adrenals, Blood, Central nervous system, Immune system, Irritant, Kidney, Liver, Lung, Skin, Thyroid
Aliphatic hydrocarbon	None	Irritant, Lung
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Xylenes	Oral LD50 (RAT) = 6,670 mg/kg Oral LD50 (RAT) = 3,523 - 8,600 mg/kg Oral LD50 (RAT) = 4,300 mg/kg Dermal LD50 (RABBIT) = > 43 g/kg Inhalation LC50 (RAT, 4 h) = 6,350 mg/l	Cardiac, Central nervous system, Irritant, Kidney, Liver
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Distillates (petroleum), hydrotreated light	None	Irritant, Lung
Ethylbenzene	Oral LD50 (RAT) = 5.46 g/kg Oral LD50 (RAT) = 3,500 mg/kg Dermal LD50 (RABBIT) = 17,800 mg/kg	Irritant, Central nervous system
Aluminium hydroxide	Oral LD50 (RAT) = > 5,000 mg/kg	Irritant, Lung, Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Hydrocarbon resin	No	No	No
p-Chloro-a,a,a-trifluorotoluene	No	No	No
Aliphatic hydrocarbon	No	No	No
Titanium dioxide	No	Group 2B	No
Xylenes	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
Distillates (petroleum), hydrotreated light	No	No	No
Ethylbenzene	No	Group 2B	No
Aluminium hydroxide	No	No	No

## 12. ECOLOGICAL INFORMATION

### Ecological information:

Harmful to aquatic organisms.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA. It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** Chloro-fluoro solvent (CAS# 98-56-6).

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis  
**CERCLA/SARA Section 311/312:** Immediate Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Xylenes (CAS# 1330-20-7). Ethylbenzene (CAS# 100-41-4).

**California Proposition 65:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

**Prepared by:** Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

**Issue date:** 10/10/2014

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Distributed by:  
Rudolph Bros. & Co.  
6550 Oley Speaks Way  
Canal Winchester, OH 43110  
Phone: 614-833-0707  
Fax: 800-600-9508  
e-mail: [rbcsupport@rudbro.com](mailto:rbcsupport@rudbro.com)  
[www.rudbro.com](http://www.rudbro.com)