



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Vinyl Spackling

PRODUCT DESCRIPTION

DAP® Vinyl Spackling is a ready mixed, easy-to-use patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency and sands easily. Recommended for interior use only.



PACKAGING	COLOR	UPC
½ Pint	White	7079812130
Quart	White	7079812132
Gallon	White	7079812133

KEY FEATURES & BENEFITS

- Ready-to-use
- Interior use

SUGGESTED USES

Ideal for filling holes, cracks and defects on drywall

FOR BEST RESULTS

- Do not use on floors or as caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- If a textured finish is desired, add clean sand to spackling compound prior to application.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

1. Surface must be free of grease, oil and other foreign matter. Sweep or blow surface with compressed air to remove all mud, dirt, dust and other loose debris.
2. Stir thoroughly before use.
3. Apply with a clean putty knife.
4. For a smoother finish, dip putty knife in water and lightly smooth spackling.
5. For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
6. May be sanded or painted in 3 to 6 hours depending on temperature, humidity and depth of fill. Wet sanding is recommended to avoid generation of dust.
7. Clean tools immediately with water.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Paste
Vehicle	Latex
Volatile	Water
Filler	Inert Filler
Odor	Very Mild
Weight/Gallon	15.5 ± .2 Pounds
Solids	76% by weight
Application Temperature	Temperatures 50°F minimum
Service Temperature	0°F to 150°F
Freeze Cycle	Freeze/Thaw Stable 5 Cycles at 0°F
Dry Time	3 to 6 hours depending on temperature and relative humidity and depth of fill.
Paintable	Yes, either oil or latex-based paint when dry.
Shelf Life	12 months



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Wash tools immediately after use with water. Be sure container is closed and tightly sealed. Store in a cool, dry place.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at dap.com.

WARRANTY

Limited Warranty:

If product fails to perform as directed, within one year from the date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com