



## Dyna-Lube

### Equipment Storage Fluid



Dyna-Lube is a companion product to Dynaloy's urethane cleaning solvents. Dynalube is used in urethane processing equipment which will be stored for an extended period.

#### APPLICATIONS:

Storage fluid for urethane dispensing equipment

#### ADVANTAGES:

Eliminates formation of polyurea and crystallized isocyanate

High flash point

#### SPECIFICATIONS:

Specific gravity: 0.86

Boiling point: > 400°F (> 204°C)

Flash point: > 459°F (> 237°C)

#### PRODUCT USAGE GUIDELINES

(SEE SDS FOR EH&S INFORMATION)

1. After equipment has been flushed with Dynasolve CU-6, flush the unit with Dyna-Lube 1-3 times to remove the Dynasolve flushing solvent.
2. Pump Dyna-Lube into the system until it fills all areas of the unit.
3. Store unit, preferably in a cool, dry place.
4. This product will freeze below 50°F (10°C).

#### MATERIAL COMPATIBILITY:

**Recommended materials including:**

All metals

Teflon®

Polyethylene & polypropylene

**Avoid materials including:**

Neoprene

PVC

EPDM



VERSUM MATERIALS, LLC

The information contained herein is offered without charge for use by technically qualified personnel at their discretion and risk. All statements, technical information and recommendations contained herein are based on tests and data which we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and no warranty of any kind is made with respect thereto.

*Versum and the Versum Materials logo are trademarks of Versum Materials, Inc. © 2017 Versum Materials, Inc.*

325-17-072-GLOBAL



1-800-375-0605  
Option 8 for 24/7 Service



6550 Oley Speaks Way  
Canal Winchester, OH 43110



[www.RudolphBros.Com](http://www.RudolphBros.Com)  
[RBCsupport@RudBro.Com](mailto:RBCsupport@RudBro.Com)