



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: BETAMATE™ 1120 Structural Adhesive

Issue Date: 03/18/2016

Print Date: 01/28/2017

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: BETAMATE™ 1120 Structural Adhesive

Recommended use of the chemical and restrictions on use

Identified uses: A structural adhesive -- For use in automotive applications.

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2030 WILLARD H DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

Customer Information Number:

800-258-2436

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Skin irritation - Category 2

Eye irritation - Category 2A

Skin sensitisation - Category 1

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Precautionary statements**Prevention**

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/ eye protection/ face protection.

Response

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

Further information

The values listed below represent the percentages of ingredients of unknown toxicity.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 19.998 %

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	25085-99-8	> 20.0 - < 30.0 %
Bisphenol A-epichlorohydrin-polyoxypropylene diamine copolymer	68318-44-5	> 5.0 - < 15.0 %
Limestone	1317-65-3	> 5.0 - < 15.0 %
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxiran]e] (DGEbPA-b	25036-25-3	> 5.0 - < 15.0 %

1-Cyanoguanidine	461-58-5	< 10.0 %
Aluminum hydroxide	21645-51-2	< 10.0 %
Bisphenol A diglycidyl ether	1675-54-3	< 10.0 %
Calcium oxide	1305-78-8	< 10.0 %
Chlorite-group minerals	1318-59-8	< 10.0 %
Dimethyl siloxane, reaction product with silica	67762-90-7	< 10.0 %
Epoxy resin	68648-83-9	< 10.0 %
Polyurethane Adduct EUP27 (P10-0078)	Not available	< 10.0 %
Talc	14807-96-6	< 10.0 %
Quartz	14808-60-7	< 1.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be immediately available.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective. Water fog, applied gently may be used as a blanket for fire extinguishment.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Do not use direct water stream. May spread fire. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Water fog, applied gently may be used as a blanket for fire extinguishment. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. See Section 10 for more specific information. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Cat litter. Sand. Sawdust. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Material may be handled at elevated temperatures; contact with heated material may cause thermal burns. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Avoid contact with air (oxygen). See Section 10 for more specific information.

Storage stability

Storage temperature:
< 30 °C (< 86 °F)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	Dow IHG	TWA	10 mg/m3
Bisphenol A diglycidyl ether	Dow IHG	TWA	10 mg/m3

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. Wear a face-shield which allows use of chemical goggles, or wear a full-face respirator, to protect face and eyes when there is any likelihood of splashes.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Use gloves with insulation for thermal protection, when needed. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Neoprene. Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body

reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material.

Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state

Paste

Color

Green

Odor

Odorless

Odor Threshold

No test data available

pH

No test data available

Melting point/range

No test data available

Freezing point

No test data available

Boiling point (760 mmHg)

No test data available

Flash point

closed cup 110 °C (230 °F) *ESP-170001*

Evaporation Rate (Butyl Acetate = 1)

No test data available

Flammability (solid, gas)

The product is not flammable.

Lower explosion limit

No test data available

Upper explosion limit

No test data available

Vapor Pressure

No test data available

Relative Vapor Density (air = 1)

No test data available

Relative Density (water = 1)

1.35 *ASTM D1475*

Water solubility

No test data available

Partition coefficient: n-octanol/water

No data available

Auto-ignition temperature

No test data available

Decomposition temperature

No test data available

Dynamic Viscosity

35,000 mPa.s at 45 °C (113 °F) *Calculated.*

Kinematic Viscosity

No test data available

Explosive properties

No test data available

Oxidizing properties

No test data available

Molecular weight

No data available

Volatile Organic Compounds

No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.
Unstable at elevated temperatures.

Possibility of hazardous reactions: Can occur. Elevated temperatures can cause hazardous polymerization.

Conditions to avoid: Avoid contact with air (oxygen). Avoid temperatures above 200°C (392°F)
Exposure to elevated temperatures can cause product to decompose.

Incompatible materials: Avoid contact with: Acids. Amines. Bases. Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Single dose oral LD50 has not been determined.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

The dermal LD50 has not been determined.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; vapor from heated material may cause respiratory irritation. This material contains mineral and/or inorganic fillers. There is essentially no potential for inhalation exposure to these fillers incidental to industrial handling due to the physical state.

The LC50 has not been determined.

Skin corrosion/irritation

Prolonged contact may cause skin irritation with local redness.

Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

Serious eye damage/eye irritation

May cause eye irritation.

Material may be handled at elevated temperatures; contact with heated material may cause thermal burns.

Sensitization

A component in this mixture has caused allergic skin reactions in humans.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals:
Kidney.

Carcinogenicity

Many studies have been conducted to assess the potential carcinogenicity of diglycidyl ether of bisphenol A (DGEBA). Indeed, the most recent review of the available data by the International Agency for Research on Cancer (IARC) has concluded that DGEBA is not classified as a carcinogen. Although some weak evidence of carcinogenicity has been reported in animals, when all of the data are considered, the weight of evidence does not show that DGEBA is carcinogenic.

Teratogenicity

Resins based on the diglycidyl ether of bisphenol A (DGEBA) did not cause birth defects or other adverse effects on the fetus when pregnant rabbits were exposed by skin contact, the most likely route of exposure, or when pregnant rats or rabbits were exposed orally.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Mutagenicity

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers****Acute oral toxicity**

LD50, Rat, > 15,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, 23,000 mg/kg

Acute inhalation toxicity

The LC50 has not been determined.

Bisphenol A-epichlorohydrin-polyoxypropylene diamine copolymer**Acute oral toxicity**

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Limestone

Acute oral toxicity

LD50, Rat, > 6,000 mg/kg

Acute dermal toxicity

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 3 mg/l The LC50 value is greater than the Maximum Attainable Concentration. No deaths occurred at this concentration.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxiran]e] (DGEbPA-b

Acute oral toxicity

LD50, Rat, > 2,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 2,000 mg/kg

Acute inhalation toxicity

The LC50 has not been determined.

1-Cyanoguanidine

Acute oral toxicity

LD50, Rat, > 10,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 10,000 mg/kg

Acute inhalation toxicity

No adverse effects are anticipated from single exposure to dust. Vapors are unlikely due to physical properties.

The LC50 has not been determined.

Aluminum hydroxide

Acute oral toxicity

LD50, Rat, > 2,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 5,000 mg/kg

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, > 2.3 mg/l

Bisphenol A diglycidyl ether

Acute oral toxicity

LD50, Rat, > 15,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, 23,000 mg/kg

Acute inhalation toxicity

The LC50 has not been determined.

Calcium oxide

Acute oral toxicity

LD50, Rat, female, > 2,000 mg/kg OECD Test Guideline 425 No deaths occurred at this concentration.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Dimethyl siloxane, reaction product with silica

Acute oral toxicity

LD50, Rat, > 5,000 mg/kg OECD 401 or equivalent No deaths occurred at this concentration.

Acute dermal toxicity

LD50, Rat, > 2,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity

For similar material(s): LC50, Rat, 4 Hour, dust/mist, > 0.477 mg/l

Epoxy resin

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

As product: The LC50 has not been determined.

At room temperature, exposure to vapor is minimal due to low volatility; vapor from heated material may cause respiratory irritation.

Polyurethane Adduct EUP27 (P10-0078)

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Talc

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

Quartz**Acute oral toxicity**

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 2 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1.8 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Scenedesmus capricornutum (fresh water algae), static test, 72 Hour, Growth rate inhibition, 11 mg/l

Toxicity to bacteria

IC50, Bacteria, 18 Hour, Respiration rates., > 42.6 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 0.3 mg/l

MATC (Maximum Acceptable Toxicant Level), Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 0.55 mg/l

Bisphenol A-epichlorohydrin-polyoxypropylene diamine copolymer**Acute toxicity to fish**

No relevant data found.

Limestone**Acute toxicity to fish**

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).

LC50, Gambusia affinis (Mosquito fish), static test, 96 Hour, > 56,000 mg/l

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxiran]e (DGEbPA-b**Acute toxicity to fish**

Not expected to be acutely toxic, but may cause adverse effects by physical/mechanical means.

1-Cyanoguanidine**Acute toxicity to fish**

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).
LC50, *Oryzias latipes* (Orange-red killifish), 48 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), 48 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, alga *Scenedesmus* sp., 72 Hour, Growth rate inhibition, > 1,000 mg/l, OECD Test Guideline 201 or Equivalent

Chronic toxicity to fish

NOEC, 14 d, survival, > 100 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, *Daphnia magna* (Water flea), 21 d, number of offspring, 25 mg/l

Aluminum hydroxide**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis
(LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
NOEC, Fish, 96 Hour, 100 mg/l

Bisphenol A diglycidyl ether**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).
LC50, *Oncorhynchus mykiss* (rainbow trout), semi-static test, 96 Hour, 2 mg/l

Acute toxicity to aquatic invertebrates

EC50, *Daphnia magna* (Water flea), static test, 48 Hour, 1.8 mg/l

Acute toxicity to algae/aquatic plants

ErC50, *Scenedesmus capricornutum* (fresh water algae), static test, 72 Hour, Growth rate inhibition, 11 mg/l

Toxicity to bacteria

IC50, Bacteria, 18 Hour, > 42.6 mg/l

Chronic toxicity to aquatic invertebrates

MATC (Maximum Acceptable Toxicant Level), *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 0.55 mg/l

Calcium oxide**Acute toxicity to fish**

May increase pH of aquatic systems to > pH 10 which may be toxic to aquatic organisms.
Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).
LC50, Cyprinus carpio (Carp), static test, 96 Hour, 1,070 mg/l

Dimethyl siloxane, reaction product with silica**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis
(LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, zebra fish (Brachydanio rerio), 96 Hour, > 1,000 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 1,000 mg/l, OECD Test Guideline 202

Epoxy resin**Acute toxicity to fish**

No relevant data found.

Polyurethane Adduct EUP27 (P10-0078)**Acute toxicity to fish**

No relevant information found.

Talc**Acute toxicity to fish**

Material is practically non-toxic to fish on an acute basis (LC50 > 100 mg/L).
LC50, Danio rerio (zebra fish), 24 Hour, > 100,000 mg/l, Method Not Specified.

Quartz**Acute toxicity to fish**

Not expected to be acutely toxic to aquatic organisms.

Persistence and degradability**Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers**

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable

Biodegradation: 12 %

Exposure time: 28 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.35 mg/mg Estimated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 1.92 Hour

Method: Estimated.

Bisphenol A-epichlorohydrin-polyoxypropylene diamine copolymer

Biodegradability: No relevant data found.

Limestone

Biodegradability: Biodegradation is not applicable.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] (DGEbPA-b

Biodegradability: Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

1-Cyanoguanidine

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable

Biodegradation: 2.2 %

Exposure time: 14 d

Method: OECD Test Guideline 302C or Equivalent

Theoretical Oxygen Demand: 3.04 mg/mg

Photodegradation

Atmospheric half-life: 0.255 d

Method: Estimated.

Aluminum hydroxide

Biodegradability: Biodegradation is not applicable.

Bisphenol A diglycidyl ether

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable

Biodegradation: 12 %

Exposure time: 28 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.35 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 1.92 Hour

Method: Estimated.

Calcium oxide

Biodegradability: Biodegradation is not applicable.

Theoretical Oxygen Demand: 0.0 mg/mg

Dimethyl siloxane, reaction product with silica

Biodegradability: Biodegradation is not applicable.

Epoxy resin

Biodegradability: No relevant data found.

Polyurethane Adduct EUP27 (P10-0078)

Biodegradability: No relevant data found.

Talc

Biodegradability: Biodegradation is not applicable.

Quartz

Biodegradability: Biodegradation is not applicable.

Bioaccumulative potential

Bioaccumulation: No data available.

Mobility in soil

Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers

Potential for mobility in soil is low (Koc between 500 and 2000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 1800 - 4400 Estimated.

Bisphenol A-epichlorohydrin-polyoxypropylene diamine copolymer

No relevant data found.

Limestone

No relevant data found.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxiran]e (DGEbPA-b

In the aquatic environment, material will sink and remain in the sediment.

1-Cyanoguanidine

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 13 Estimated.

Aluminum hydroxide

No relevant data found.

Bisphenol A diglycidyl ether

Potential for mobility in soil is low (Koc between 500 and 2000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient(Koc): 1800 - 4400 Estimated.

Calcium oxide

No relevant data found.

Dimethyl siloxane, reaction product with silica

No relevant data found.

Epoxy resin

No relevant data found.

Polyurethane Adduct EUP27 (P10-0078)

No relevant data found.

Talc

No data available.

Quartz

No relevant data found.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(Epoxy resin)
UN number	UN 3077
Class	9
Packing group	III
Marine pollutant	Epoxy resin
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Environmentally hazardous substance, solid, n.o.s.(Epoxy resin)
UN number	UN 3077
Class	9
Packing group	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Acute Health Hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Limestone	1317-65-3
Calcium oxide	1305-78-8
Talc	14807-96-6

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Fire	Reactivity
1	1	2

Revision

Identification Number: 101209047 / A001 / Issue Date: 03/18/2016 / Version: 4.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

Dow IHG	Dow Industrial Hygiene Guideline
TWA	Time weighted average

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

Distributed by:
Rudolph Bros. & Co.
6550 Oley Speaks Way
Canal Winchester, OH 43110
Phone: 614-833-0707
Fax: 800-600-9508
e-mail: rbcsupport@rudbro.com
www.rudbro.com