

Revision Number: 004.0 Issue date: 06/24/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE FREKOTE 800NC known as IDH number: 398490

FREKOTE 800-NC AEROSOL

 Product type:
 Mold Release
 Item number:
 83474

 Restriction of Use:
 None identified
 Region:
 United States

Company address:Contact information:Henkel CorporationTelephone: (860) 571-5100

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

Contains one or more components for which a Toxic Substances Control Act (TSCA) Low Volume Exemption (LVE) applies. See Section 15.

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTENTS UNDER PRESSURE.

EXTREMELY FLAMMABLE AEROSOL.

MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE AEROSOL.	1
SKIN IRRITATION	2
EYE IRRITATION	2A
ASPIRATION HAZARD	1









Precautionary Statements

IDH number: 398490

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye and face protection. Wear protective gloves.

Response: IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash

with plenty of soap and water. IF IN EYÉS: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical

attention. Take off contaminated clothing.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

1 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated light	Proprietary	60 - 100
Propane	74-98-6	5 - 10

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Get medical attention.

Ingestion: Keep individual calm. Do not induce vomiting: contains petroleum distillates

and/or aromatic solvents. Never give anything by mouth to an unconscious person. If vomiting occurs, prevent aspiration by keeping the patient's head

below the knees.

Symptoms: See Section 11.

IDH number: 398490

Notes to physician: This material is an aspiration hazard. Potential danger from aspiration must

be weighed against possible oral toxicity when deciding whether to induce

vomiting.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high

volume water jet.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be

helpful in keeping adjacent containers cool. Keep personnel upwind of fire.

Unusual fire or explosion hazards: Contents under pressure. Do not puncture or incinerate pressurized

containers. Containers exposed to fire should be cooled with water to prevent vapor pressure buildup which could result in container rupture. If a leak or spill has not ignited, use water spray to disperse vapors. The liquid is volatile and gives off invisible vapors. Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form

that may ignite vapors of flammable liquids.

Hazardous combustion products: Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Irritating organic vapours. Collect contaminated fire extinguishing water

separately. This must not be discharged into drains.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. Advise authorities if product

has entered or may enter sewers, water sources or extensive land areas. This

product is insoluble in water and will float on surface.

Clean-up methods: Remove all sources of ignition. Ventilate area. Soak up with inert absorbent.

Store in a closed metal container until ready for disposal. Keep upwind of the spilled material and isolate exposure. Refer to Section 8 "Exposure Controls /

Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling: During use and until all vapors are gone: Keep area ventilated - do not

smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Avoid contact with eyes, skin and clothing. Do not breathe gas/fumes/vapor/spray. Do not taste or swallow. Wash thoroughly after handling. For operations where eye or face

contact could occur, provide safety shower and eyewash fountain.

Storage: For safe storage, store at or below 48.8 °C (119.8 °F)

Store away from heat, sparks, flames, or other sources of ignition. Keep in a

cool, well ventilated area. Keep containers closed when not in use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated light	None	None	None	None
Propane	Included in the regulation but with no data values. See regulation for further details	1,000 ppm (1,800 mg/m3) PEL	None	None

Engineering controls: Use explosion-proof mechanical ventilation and local exhaust to control

contaminants to within their occupational exposure limits during the use of this

product.

IDH number: 398490

Respiratory protection: Use a NIOSH approved supplied air respirator with an organic cartridge if the

potential to exceed established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

showers and eye wash stations should be available.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol Color: Clear colorless Odor: Mild Odor threshold: Not available.

pH: Not available. Vapor pressure: Not available. Boiling point/range: Compressed Gas. Melting point/ range: Specific gravity: Not available.

0.76

Vapor density: 4.42 Approximately

Flash point: Flammable. ASTM D 3065

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available.

Evaporation rate: 0.1 Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. **VOC** content: Not available. Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 398490

Hydrocarbons. Traces of Ammonia.

Incompatible materials: Oxidizing agents. Water. Humid air.

Reactivity: Not available.

Conditions to avoid: Keep away from open flames, hot surfaces and sources of ignition. Store away from

incompatible materials. Vapors may form explosive mixtures with air. Fire or intense heat may cause violent rupture of packages. Avoid static discharge. Exposure to air or moisture over prolonged periods. Spray mist may be flammable at temperatures below the flash point.

TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Irritates the nose, throat and respiratory system. High vapor concentrations (greater than

approximately 1000 ppm) may cause headaches, dizziness, anesthesia, drowsiness,

unconsciousness, and other central nervous system effects, including death.

Skin contact: Causes skin irritation. Solvent action can dry and defat the skin, causing the skin to crack,

leading to dermatitis.

Eye contact: Causes serious eye irritation. Liquid, aerosols or vapor are irritating and can cause tearing,

reddening and swelling.

Ingestion: This product may be fatal if it is swallowed. Aspiration may occur during swallowing or vomiting,

resulting in lung damage. May cause central nervous system effects, such as headache,

nausea, vomiting, abdominal pain, dizziness, confusion, and breathing difficulties.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated light	None	Irritant, Lung
Propane	Inhalation LC50 (RAT, 15 min) = > 1,442.847 mg/l Inhalation LC50 (RAT, 15 min) = > 1,464 mg/l	Cardiac, Central nervous system, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated light	No	No	No
Propane	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Do not puncture or incinerate pressurized containers. Follow all local, state,

federal and provincial regulations for disposal.

Hazardous waste number: D001: Ignitable.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols, flammable

Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable

Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

IDH number: 398490

Proper shipping name: AEROSOLS
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis Immediate Health, Fire, Pressure CERCLA/SARA Section 313: None above reporting de minimis

CERCLA Reportable quantity: Propane (CAS# 74-98-6) 100 lbs. (45.4 kg)

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 398490

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

Issue date: 06/24/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Distributed by: Rudolph Bros. & Co. 6550 Oley Speaks Way Canal Winchester, OH 43110

Phone: 614-833-0707 Fax: 800-600-9508

e-mail: rbcsupport@rudbro.com

www.rudbro.com