### Safety Data Sheet



#### Revision Number: 005.0

Issue date: 03/07/2017

### 1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

item number:

#### Product name:

FREKOTE EXITT - 1 DRUM 55 GALL

Product type: **Restriction of Use:** None identified Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE FREKOTE EXITT-I known as Mold Release

420437 83517

United States Region: Contact information: Telephone: (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkeina.com

#### 2. HAZARDS IDENTIFICATION

DANGER:	HIGHLY FLAMMABLE LIQUID AND VAPOR.	
	MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.	
	CAUSES SKIN IRRITATION.	
	CAUSES SERIOUS EYE IRRITATION.	
	MAY CAUSE DROWSINESS OR DIZZINESS.	

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)	

#### Precautionary Statements

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly Prevention: closed. No release into water. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection, and face protection. IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and Response: keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feet unwell, IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye imitation persists: Get medical attention. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Storage: Keep cool. Store locked up.

IDB number: 420437

#### Product name: LOCTITE FREKOTE EXITT-I known as FREKOTE EXITT - 1 DRUM 55 GALL Page 1 of 6

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Alkanes, C7-10-iso-	90622-56-3	90 - 100
Dimethyl polysiloxane	63148-62-9	5 - 10

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

# A FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. If skin irritation persists, call a physician. Wash clothing before reuse.
Eye contact:	Rinse Immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get immediate medical attention.
ingestion:	Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Never give anything by mouth to an unconscious person. Keep individual calm. Get immediate medical attention. If vorniting occurs, prevent aspiration by keeping the patient's head below the knees.
Symptoms:	See Section 11.
Notes to physician:	This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.

# 5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool, Keep personnel upwind of fire.
Unusual fire or explosion hazards:	Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, fillering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of fiarmable liquids.

Hazardous combustion products:

Oxides of carbon. Oxides of silicon. Acrid smoke and fumes. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways. Advise authorities if product has entered or may enter sewers, water sources or extensive land areas. Prevent further leakage or spillage if safe to do so.
Clean-up methods:	Remove all sources of ignition. Ventilate area. Keep upwind of the spilled material and isolate exposure. Wear suitable protective clothing, gloves and eye/face protection. Soak up with inert absorbent material (e.g. sand, silica cell acid binder, universal binder, sawdust). Store in a closed metal container

# 77 HANDLING AND STORAGE

until ready for disposal.

Handling:

During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Make sure containers are properly grounded before use or transfer of material. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not taste or swallow. For operations where eye or face contact could occur, provide safety shower and eyewash fountain.

Storage:

For safe storage, store at or below 48.8 °C (119.8 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8 8 EXPOSURE CONTROLS / PERSONAL PROJECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Alkanes, C7-10-iso-	None	None	None	None
Dimethyl polysiloxane	None	None	None	None
Engineering controls:	Use explosion-proof mechanical ventilation and local exhaust to control contaminants to within their occupational exposure limits during the use of this product.			
Respiratory protection:	Use a NIOSH approved supplied air respirator with an organic carlridge if the potential to exceed established exposure limits exists.			
Eye/face protection:	be use	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.		
Skin protection:	Use ch apron (	Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.		

Physical state:	Liquid
Color:	Colortess
Odor:	Mild, Solvent
Odor threshold:	Not available
pH:	Not applicable
Vapor pressure:	40 mm hg Estimated
Boiling point/range:	> 94 °C (> 201.2 °F)
Melting point/ range:	Not available.
Specific gravity:	0.72
Vapor density:	3.9
Flash point:	-5 °C (23°F) Tagliabue closed cup
Flammable/Explosive limits - lower:	1.5 % (value for solvent)
Flammable/Explosive limits - upper:	11.6 % (value for solvent)
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	4.2
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	92 %
Viscosity:	Not available.
Decomposition temperature:	Not available.
10. SI	ABILITY AND REACTIVITY
	der namet and life is af store of and use
Stability: Stable un Risk of ig	der normal conditions of storage and use.

 Hazardous decomposition products:
 Hydrocarbons.

 Incompatible materials:
 Strong oxidizing agents.

 Reactivity:
 Not available.

 Conditions to avoid:
 Avoid static discharge. Spray mist may be flammable at temperatures below the flash point. Keep away from open flames, hot surfaces and sources of ignition. Fire or intense heat may cause violent rupture of packages. Exposure to air or moisture over prolonged periods.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

.

Skin, Inhalation, Eyes, Ingestion

IDH number: 420437

#### Potential Health Effects/Symptoms

Inhalation:	Vapors and mists will initate nose and throat and possibly eyes. May cause central nervous system effects with nausea, dizziness and headache.
Skin contact:	Causes skin irritation. Solvent action can dry and defat the skin, causing the skin to crack,
	leading to dermatilis.
Eye contact:	Causes serious eye initation.
Ingestion:	This product may be fatal if it is swallowed. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Central nervous system depression, including dizziness, drowsiness,
	fatigue, nausea, headache, unconsciousness.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Alkanes, C7-10-iso-	None	Central nervous system, Irritant, Lung, Cardiac	
Dimethyl polysiloxane	None	irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Alkanes, C7-10-iso-	No	No	No
Dimethyl polysiloxane	No No	No	No

#### 12. ECOLOGICAL INFORMATION 4 × 75

**Ecological information:** 

Not available.

#### 13. DISPOSALCONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

D001; Ignitable.

#### **14. TRANSPORT INFORMATIONS** 1

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of	Transportation	Ground (49	CFR)	

S. Department of Transportation Ground (49 CFR)		
Proper shipping name:	Resin solution	
Hazard class or division:	3	
Identification number:	UN 1866	
Packing group:	I	

International Air Transportation (ICAO/IATA)

Identification number: Packing group:

Proper shipping name:	Resin solution
Hazard class or division:	3
Identification number:	UN 1866
Packing group:	ļI
Water Transportation (IMO/IMDG)	
Proper shipping name:	RESIN SOLUTION
Hazard class or division:	3

UN 1865 11

IDH number: 420437

## 15 REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health, Fire None above reporting de minimis.
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

# 167 OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by:

Catherine Bimler, Regulatory Affairs Specialist

Issue date: 03/07/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ('Henkel') does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.



IDH number: 420437

Product name: LOCTITE FREKOTE EXITT-I known as FREKOTE EXITT - 1 DRUM 55 GALL Page 6 of 6