RUDOLPH BROS. & CO.

P.O. BOX 425 CANAL WINCHESTER, OH 43110 (614) 833-0707 ORDER FAX 1-800-600-9508

Specification Sheet #701

Type:

Hot Melt Glue - Ethylene Vinyl Acetate

Solids:

100%

Viscosity:

@ 250/F 12,500

@ 380/F 1,500

Softening Point: 185/F

Color:

TAN

Odor:

Slight

Shelf Life:

Indefinite

Flash Point:

Above 450/F

FDA Status

Compositional compliance with FDA Regulation

#21CFR175.105 for food packaging.

Suggested Uses: Packaging adhesive with excellent hot tack, short open time and good delivery rate. Good adhesion to plain and some coated corrugated packaging and paper products

Storage:

Common Storage

Application Temperature: 250/F to 380/F

Precautions:

Do Not Mix with other adhesives

Severe burns will result if contact is made in molten

state.

Material safety data sheets providing safety

Precautions that should be observed in handling

and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. RPC warrants that the product conforms with RPC written specifications, and is free from defects. RPC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sold remedy for non compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price