

# RUDOLPH BROS. & CO.

P.O. BOX 425  
CANAL WINCHESTER, OH 43110  
(614) 833-0707  
ORDER FAX 1-800-600-9508

## Specification Sheet #725

Type: Hot Melt Glue - Ethylene Vinyl Acetate  
Solids: 100%  
Viscosity: @ 250/F 42,000  
                  @ 380/F 4,540  
Softening Point: 176/F  
Color: Clear  
Odor: Slight  
Shelf Life: Indefinite  
Flash Point: Above 450/F  
FDA Status: Compositional compliance with FDA Regulation  
                  #21 CFR 175.105 for food packaging

**Suggested Uses:** A hot melt adhesive designed for low, high and dual-temperature glue guns. General purpose adhesive with long open time and good delivery rate. In high temperature offers good adhesion to most plastics and woods. In low temperature offers good adhesion to heat sensitive substrates as Styrofoam, paper, fabric and ribbons.

Storage: Common Storage  
Application Temperature: 250/F to 380/F  
Precautions: Do Not Mix with other adhesives  
                  Severe burns will result if contact is made in molten state.  
                  Material safety data sheets providing safety Precautions that should be observed in handling and storing.

The buyer should conduct its own tests of this product before use to determine proper preparation technique and suitability for proposed application. RBC warrants that the product conforms with RBC written specifications, and is free from defects. RBC disclaims all other warranties, expressed or implied, including the warranties of merchantability and fitness for a particular purpose. The buyer's sole remedy for non-compliance with this warranty shall be for the replacement of the product or refund of the buyer's purchase price.