Distributed By... Rudolph Bros. & Co. Call us at (800)-375-0605 Order Fax 1-800-600-9508 rbcsupport@rudbro.com

Safety Data Sheet



Revision Number: 003.0

Issue date: 08/06/2014

PRODUCT AND COMPANY IDENTIFICATIONS

Product name:

LOCTITE EA 9360 AERO PART A 50ML IDH number:

KIT known as EA 9360 PART A 50ML

SEMPAK

Product type: Restriction of Use: Adhesive for the Aerospace Industry

None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

937177

Item number: Region:

AA9332328 **United States**

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

28 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
SKINTRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Precautionary Statements

Prevention:

Avoid breathing dust or fumes. Wash thoroughly after handling. Use only outdoors or in a wellventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear

eye and face protection. Wear protective gloves.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Call a poison control center or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get

medical attention. Take off contaminated clothing.

Storage: Disposal: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910,1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 937177

Product name: LOCTITE EA 9360 AERO PART A 50ML KIT known as EA 9360 PART A 50ML

SEMPAK

See Section 11 for additional toxicological information.

Hazardous Component(s)	CAS Number	Percentage*	
Epoxy resin	Proprietary	30 - 60	
Polyfunctional epoxy resin	Proprietary	10 - 30	
Glass, oxide, chemicals	65997-17-3	5 - 10	
Treated furned silica	67762-90-7	1 - 5	
Substituted silane	Proprietary	1-5	

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4 FIRSTIALD MEASURES 1

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention, Do not induce vomiting. Never give anything

by mouth to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

IDH number: 937177

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures; Wear full protective clothing. Wear self contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASEMEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal.

Dispose of according to Federal, State and local governmental regulations.

HANDLING AND STORAGE

Handling:

Avoid contact with skin and clothing. Wash thoroughly after handling. Do not breathe fumes or dust from this material. Do not take internally. For industrial

use only.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Product to be stored below 77° F.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epoxy resin	None	None	None	None
Polyfunctional epoxy resin	None	None	None	None
Glass, oxide, chemicals	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Treated furned silica	10 mg/m3 TWA 15 mg/m3 TWA Total Inhalable dust. dust. 3 mg/m3 TWA 5 mg/m3 TWA Respirable fraction.		None	None
Substituted silane	None	None	None	None

Engineering controls:

Ventilation should effectively remove and prevent buildup of any dust

generated from the handling of this product.

Respiratory protection:

When dusts or thermal processing furnes are generated and ventilation is not

sufficient to effectively remove them, appropriate NIOSH/MSHA approved

respiratory protection must be provided.

Eye/face protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

MERHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Solid Cream

Color: Odor:

Slight

Odor threshold:

Not available.

pH:

Neutral Nil

. Vapor pressure:

Bolling point/range:

Not applicable Not determined

Melting point/ range:

1.14

Specific gravity:

> 1

Vapor density:

> 1

Vapor density: Vapor density:

> 1

Vapor density:

> 93 °C (> 199.4 °F)

Flash point: Flammable/Explosive limits - lower:

Not determined Not determined

Flammable/Explosive limits - upper: Autoignition temperature:

Not determined Not determined

Evaporation rate: Solubility in water:

Negligible

Partition coefficient (n-octanol/water): VOC content:

Not determined < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

IDH number: 937177

Product name: LOCTITE EA 9360 AERO PART A 50ML KIT known as EA 9360 PART A 50ML

SEMPAK

Viscosity:

Decomposition temperature:

Not available. Not available.

STABILITY AND REACTIVITY

Stability:

Stable at normal conditions.

Hazardous reactions:

May occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials:

Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity:

Not available.

Conditions to avoid:

Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Avoid heating unless curing surfaces to be bonded. Failure to observe these precautions may

result in excessive heat build-up causing an exotherm.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:

Inhalation of dust generated by this material may cause respiratory tract irritation. This product may cause irritation to the skin. May cause allergic skin reaction.

Skin contact: Eye contact:

This product may cause irritation to the eyes.

ingestion:

Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Epoxy resin	None	Altergen, Irritant
Polyfunctional epoxy resin	None	Allergen, Blood, Central nervous system, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Nervous System
Glass, oxide, chemicals	None	Allergen, Respiratory
Treated furned silica	None	Imitant
Substituted silane	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epoxy resin	No	No	No
Polyfunctional epoxy resin	No	No	No
Glass, oxide, chemicals	No	No	No
Treated furned silica	No	No	No
Substituted sllane	No	No	No

12. EGGLOGICAL INFORMATION

Ecological information:

1DH number: 937177

Harmful to aquatic organisms.

Product name: LOCTITE EA 9360 AERO PART A 50ML KIT known as EA 9360 PART A 50ML SEMPAK

* * 11. DISPOSAL CONSIDERATIONS.

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

TRANSPORTINEORMATION TO THE SECOND PROPERTY OF THE PROPERTY OF

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None None

identification number: Packing group:

None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Environmentally hazardous substance, solid, n.o.s. (Bisphenol-A Epichlomydrin

resin, Tetraglycidyl diaminodiphenylmethane)

Hazard class or division:

Identification number:

UN 3077

Packing group:

Ш

Water Transportation (IMO/IMDG)

Proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol-A

Epichlorhydrin resin, Tetraglycidyl diaminodiphenylmethane)

Hazard class or division:

Identification number:

UN 3077 Ш

Packing group: Marine pollutant:

Bisphenol-A Epichlornydrin resin, Tetraglycidyl diaminodiphenylmethane

Exceptions:

Classified per IMDG Amendment 34; Effective Jan 1, 2010.

EGULATORY INFORMATION:

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312:

None above reporting de minimis Immediate Health, Delayed Health

CERCLA/SARA Section 313:

None above reporting de minimis

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 937177

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Product name: LOCTITE EA 9360 AERO PART A 50ML KIT known as EA 9360 PART A 50ML

SEMPAK

Prepared by:

Mark Mau, Regulatory Affairs Specialist

Issue date:

IDH number: 937177

08/06/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reitable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including tost profits.