

Revision Number: 004.2

Issue date: 12/28/2016

1. PRODUCT AND COMPANY IDENTIFICATION.

Product name:

LOCTITE EA 9394 AERO PART A 50ML IDH number:

KIT known as EA 9394 PART A 50ML

SEMPAK

Product type: Restriction of Use: Adhesive for the Aerospace Industry

None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Item number:

Region:

944952

AA9277328 United States

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)



Prevention:

Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of

the workplace. Wear protective gloves, eye protection, and face protection.

Response:

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention.

If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Disposal: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Product name: LOCTITE EA 9394 AERO PART A 50ML KIT known as EA 9394 PART A 50ML IDH number: 944952

SEMPAK

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	-
Aluminum	7429-90-5	30 - 40	
Tetraglycidyl diaminodiphenylmethane	28768-32-3	30 - 40	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	20 - 30	
Modified epoxy resin	Unknown	5 - 10	
Treated furned silica	67762-90-7	1-5	

Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical altention.

Ingestion: Get medical attention. Do not induce vomiting. Never give anything by mouth

to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full profective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantifies of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods:

Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part A at temperatures greater than 80 °C (176 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE GONTROLS/ PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Aluminum	1 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Tetraglycidyl diaminodiphenylmethane	None	None	None	No <u>ne</u>
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None
Modified epoxy resin	None	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Liquid

Color: Odor: Gray mild

Odor threshold:

Not available.

pH:

Neutral

Vapor pressure:

Nit

Bolling point/range:

Not determined

Melting point/ range:

Not determined

IDH number: 944952

Product name: LOCTITE EA 9394 AERO PART A 50ML KIT known as EA 9394 PART A 50ML

SEMPAK

Specific gravity:

1.49

Vapor density:

> 1

Flash point:

> 93 °C (> 199.4 °F)

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Not determined Not determined Not determined

Autoignition temperature: Flammability:

Not applicable Not determined

Evaporation rate: Solubility in water:

Negligible

Partition coefficient (n-octanol/water):

Not determined

VOC content:

< 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Viscosity:

Not available.

Decomposition temperature:

Not available.

10 STABILITY AND REAGIIVITY

Stability:

Stable at normal conditions.

Hazardous reactions:

May occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

incompatible materials:

Strong acids and oxidizing agents. Amines.

Reactivity:

Not available.

Conditions to avoid:

To avoid thermal decomposition, do not overheat.

11 TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

inhalation:

May cause respiratory tract irritation.

Skin contact:

This product may cause irritation to the skin. Repeated or prolonged skin contact may result in

allergic sensitization.

Eye contact:

This product may cause irritation to the eyes. .

Ingestion:

ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Aluminum	None	Central nervous system, Irritant, Lung	
Tetraglycidyi diaminodiphenylmethane	None	Allergen, Blood, Central nervous system, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Nervous System	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Imitant	
Modified epoxy resin	None	No Data	
Treated furned silica	None	Irritant	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Aluminum	No	No	No
Tetraglycidyl diaminodiphenylmethane	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Modified epoxy resin	No	No	No
Treated fumed silica	No	No	No

IDH number: 944952

Product name: LOCTITE EA 9394 AERO PART A 50ML KIT known as EA 9394 PART A 50ML

SEMPAK

ECOLOGICAL INFORMATION

Ecological Information:

Toxic to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None None

Identification number: Packing group:

None

International Air Transportation (ICAO/IATA)

Proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (Tetraglycidyl

diaminodiphenylmethane, Bisphenol-A Epichlorhydrin resin)

Hazard class or division:

Identification number:

UN 3082

Packing group:

(II)

Water Transportation (IMO/IMDG)

Proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Tetraglycidyl

diaminodiphenylmethane, Bisphenol-A Epichlorhydrin resin)

Hazard class or division:

Identification number:

UN 3082 111

Packing group:

Tetraglycidyl diaminodiphenylmethane, Bisphenol-A Epichlorhydrin resin

Marine pollutant: Exceptions: Classified per IMDG Amendment 34; Effective Jan 1, 2010.

REGULATORY INFORMATION 7.00 13.5 14.5 14.5 15.

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

inventory

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

None above reporting de minimis.

CERCLA/SARA Section 311/312:

Immediate Health, Delayed Health

CERCLA/SARA Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372), Aluminum (CAS# 7429-90-5).

California Proposition 65:

IDH number: 944952

This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status:

One or more components are not listed on, and are not exempt from listing on either the


Domestic Substances List or the Non-Domestic Substances List.

Hazardous Materials Information

10743

Review Act:

-16: OTHER INFORMATION



Prepared by:

Mark Mau, Regulatory Affairs Specialist

Issue date:

IDH number: 944952

12/28/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.