Distributed By... Rudolph Bros. & Co. Call us at (800)-375-0605 Order Fax 1-800-600-9508 rbcsupport@rudbro.com

Safety Data Sheet



Revision Number: 003.1 Issue date: 10/24/2016

PRODUCT AND COMPANY IDENTIFICATION

Product name:

LOCTITE EA 9396 AERO PART B 80Z

known as EA 9396 PART B 80Z Adhesive for the Aerospace Industry

None identified

Product type: Restriction of Use: Company address:

Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

DANGER:

IDH number:

937084

Item number:

AB9280014 United States

Region: Contact information: Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HARMFUL IN CONTACT WITH SKIN.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE. MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY DERMAL	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



Precautionary Statements

Prevention:

Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, clothing, eye and face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest

in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse.

Storage: Disposal:

IDH number: 937084

Store locked up.

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Tetraethylene pentamine	112-57-2	40 - 50	
N,N'-Bis(3-aminopropyl)piperazine	7209-38-3	30 - 40	
3,6,9,12- tetraazatetradecamethylenediamine	4067-16-7	5 - 10	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention. If breathing is difficult, give oxygen.

If not breathing, give artificial respiration.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with scap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of pressure) when exposed to

extreme heat.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part B at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut, grind, weld, or drill on or near this container.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tetraethylene pentamine	None	None	(SKIN) Aerosol. 1 ppm (5 mg/m3) TWA Aerosol. (Skin sensitizer)	None
N,N'-Bis(3-aminopropyl)piperazine	None	None	None	None
3,6,9,12- tetraazatetradecamethylenediamine	None	None	None	None

Engineering controls:

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection:

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Color:

Odor: Odor threshold:

pH:

Vapor pressure: Boiling point/range:

Melting point/ range:

Specific gravity: Vapor density:

Flash point:

Flammable/Explosive limits - lower: Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability: Evaporation rate: Solubility in water:

Partition coefficient (n-octanol/water): VOC content:

liquid

Orange-red ammoniacal

Not available. Not applicable

< 0.1 mm hg (20 °C (68°F))

340 °C (644°F) Not determined

1.0 8.6

> > 93 °C (> 199.4 °F); Estimated Not determined

Not determined Not determined Not applicable

Not determined fully soluble

Not determined

< 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Not available.

Viscosity:

Decomposition temperature:

Not available.

STABILITY AND REACTIVITY

Stability:

Stable at normal conditions.

Hazardous reactions:

Not available.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials:

Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity:

Not available.

Conditions to avoid:

Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Do not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these

precautions may result in excessive heat build-up causing an exotherm.

11. TOXICOLOGICAL INFORMATION

Product toxicity data:

Henkel is not aware of any toxicity data on the specific mixture of chemical components

contained in this product.

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:

Mists, vapors or liquid may cause severe irritation or burns.

Skin contact:

This product is severely imitating to the skin and may cause burns. May cause ellergic skin

reaction. May be harmful if absorbed through skin.

Eye contact:

This product is severely initating to the eyes and may cause irreversible damage including

burns and blindness. May cause corneal injury. May cause burns of mouth and throat if swallowed.

Ingestion:

LD50s and LC50s Immediate and Delayed Health Effects Hazardous Component(s) Oral I D50 (Rat) = 3.99 o/kg

Tetraethylene pentamine	Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen
N,N'-Bis(3-aminopropyl)piperazine	None	No Records
3,6,9,12- tetraazatetradecamethylenediamine	None	Imitant, Altergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tetraethylene pentamine	No	No	No
N,N'-Bis(3-aminopropyl)piperazine	No	No	No
3,6,9,12- tetraazatetradecamethylenediamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

IDH number: 937084

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Amines, liquid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)

Hazard class or division:

8

Identification number:

UN 2735

Packing group:

International Air Transportation (ICAO/IATA)

Proper shipping name:

Amines, liquid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)

Hazard class or division:

8

Identification number:

UN 2735

Packing group:

161

Water Transportation (IMO/IMDG)

Proper shipping name:

AMINES, LIQUID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted

piperazine)

Hazard class or division:

8

Identification number:

UN 2735

Packing group: Marine pollutant:

Tetraethylene pentamine

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS:

CERCLA/SARA Section 311/312:

CERCLA/SARA Section 311/3
CERCLA/SARA Section 313:

None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.

California Proposition 65:

No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA D\$L/ND\$L Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Material Safety Data Sheet contains changes from the previous version in Section(s): 1,2,6,10

Prepared by:

Mark Mau, Regulatory Affairs Specialist

Issue date:

IDH number: 937084

10/24/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.