# Distributed By... Rudolph Bros. & Co. Call us at (800)-375-0605 Order Fax 1-800-600-9508 rbcsupport@rudbro.com

**Safety Data Sheet** 



Revision Number: 001.4

Issue date: 09/26/2014

#### 1 PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type: LOCTITE EA 9628 060K AERO known

as HYSOL EA 9628 .060 PSF K

Adhesive for the Aerospace Industry None identified

Restriction of Use: Nor

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

IDH number:

549774

Item number:

AT9004512 United States

Region: Contact Information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# HAZARDSIDENTIFICATION WAS A SECOND

#### **EMERGENCY OVERVIEW**

DANGER:

CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE GENETIC DEFECTS.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
GERM CELL MUTAGENICITY	1B

# PICTOGRAM(S)

#### **Precautionary Statements**

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust or furnes. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye and face

protection. Wear protective gloves. Use personal protective equipment as required.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. IF

exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

Storage:

IDH number: 549774

Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

# 3. COMPOSITION MEDICALION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Modified epoxy resin	Unknown	30 - 60
Epoxy resin	Proprietary	30 - 60
3-(P-chlorophenyl)-1,1-dimethylurea	150-68-5	1-5

Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST-AID MEASURES:

inhalation:

If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact:

Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

Eye contact:

In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion:

Get immediate medical attention. Do not induce vomiting.

Symptoms:

See Section 11.

Notes to physician:

Treat symptomatically and supportively.

#### 

Extinguishing media:

Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures:

Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards:

May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nilrogen.

# GÉ ACCIDENTA PRELEASE MEASURES

Use personal protection recommended in Section 8, Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods:

Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

#### HANDLING AND STORAGES

Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not breathe fumes or dust from this material. For industrial use only.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

Product name: LOCTITE EA 9628 060K AERO known as HYSOL EA 9628 .060 PSF K Page 2 of 5

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Modified epoxy resin	None	None	None	None
Epoxy resin	None	None	None	None
3-(P-chlorophenyl)-1,1-dimethylurea	None	None	None	None

Engineering controls:

Ventilation should effectively remove and prevent buildup of any dust

generated from the handling of this product.

Respiratory protection:

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved

respiratory protection must be provided.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

#### PHYSICAL AND TOHEMICAL PROPERTIES - 3

Solid, Film

Not available.

Not applicable

Not applicable

Not applicable

Not available. Not available.

Not determined

Not determined

Not determined

Cream

Slight Not available.

Nil

Physical state:

Color:

Odor: Odor threshold:

pH:

Vapor pressure: Boiling point/range:

Melting point/ range: Specific gravity:

Vapor density:

Flash point:

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper: Autoignition temperature:

Evaporation rate: Solubility in water:

Viscosity:

Partition coefficient (n-octanol/water):

Decomposition temperature:

VOC content:

**3**7.000 (2)

Not available.

< 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated) Not available.

Not miscible or difficult to mix

> 93 °C (> 199.4 °F); Estimated

#### 10. STABIBITY AND REACTIVITY

molecular weight hydrocarbons. Oxides of nitrogen.

Stability:

75 P

Stable at normal conditions.

Hazardous reactions:

Incompatible materials:

Hazardous decomposition

products:

Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity:

IDH number: 549774

Not available.

May occur.

Conditions to avoid:

Avoid heating masses of film greater than 1 pound (0.454 kg) total. Avoid heating unless curing surfaces to be bonded. Fallure to observe these precautions may result in excessive

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

heat build-up causing an exotherm.

#### 

Relevant routes of exposure:

Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation:

May cause respiratory tract imitation.

Skin contact:

This product may cause imitation to the skin. May cause allergic skin reaction.

Eye contact:

This product may cause irritation to the eyes.

Ingestion:

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Modified epoxy resin	None	No Data
Epoxy resin	None	Allergen, Irritant
3-(P-chlorophenyl)-1,1-dimethylurea	Oral LD50 (RAT) = 3,600 mg/kg	Blood, Imitant, Central nervous system, Mutagen, Kidney, Liver

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Modified epoxy resin	No	No No	No
Epoxy resin	No -	No	No
3-(P-chlorophenyl)-1.1-dimethylurea	No	No	No

# 12: ECOLOGICAL NEORMATION

Ecological Information:

Not available.

# 13. DISPOSAL CONSIDERATIONS

# Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number:

Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

#### 14. TRANSPORTINFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

Packing group:

None None

### International Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division:

None None

identification number:

None

# Water Transportation (IMO/IMDG)

Packing group:

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None None

Packing group:

None

IDH number: 549774 Product name: LOCTITE EA 9628 060K AERO known as HYSOL EA 9628 .060 PSF K
Page 4 of 5

#### \*M5 REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

inventory.

TSCA 12 (b) Export Notification:

None above reporting de minimis

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: None above reporting de minimis Immediate Health, Delayed Health

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). 3-(P-chlorophenyl)-1,1-dimethylurea (CAS# 150-68-5).

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer: This product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:

One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

# (6) OFFIER NEORNATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by:

Mark Mau, Regulatory Affairs Specialist

Issue date:

IDH number: 549774

09/26/2014

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the sulfability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Product name: LOCTITE EA 9628 060K AERO known as HYSOL EA 9628 .060 PSF K

Page 5 of 5