

# **EMPLOYEE OWNED SINCE 202**

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.com



Revision Number: 002.2 Issue date: 08/17/2023

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA 9845LA 020-016 AERO

known as HYSOL EA 9845LSA

0.020/0.016

Product type/use: Adhesive for the Aerospace Industry

Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 1771330

Item number:AL9025619Region:United States

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

# PICTOGRAM(S)



### **Precautionary Statements**

Prevention: Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated

work clothing should not be allowed out of the workplace. Wear protective gloves, eye

protection, and face protection.

**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Aluminum not powder, dust or fume	7429-90-5	30 - 60	
Silica, amorphous, fumed, crystfree	112945-52-5	5 - 10	
Epoxy resin	Proprietary	5 - 10	
Epoxy resin	Proprietary	5 - 10	

IDH number: 1771330 Product name: LOCTITE EA 9845LA 020-016 AERO known as HYSOL EA 9845LSA 0.020/0.016
Page 1 of 6

Epoxy resin	Proprietary	5 - 10
Modified Epoxy Resin	Proprietary	1 - 5
Epoxy resin	Proprietary	1 - 5
Epoxy Resin	Proprietary	1 - 5
Epoxy resin	Proprietary	1 - 5
Glass, oxide, chemicals	65997-17-3	1 - 5

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Immediately wash skin thoroughly with soap and water. If symptoms develop

and persist, get medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of aluminum.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal.

Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do

not breathe fumes or dust from this material. For industrial use only.

Storage: For safe storage, store between -999 °C (-1,766.2 °F) and -18 °C (0.4 °F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

IDH number: 1771330

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Aluminum not powder, dust or fume	1 mg/m3 TWA Respirable fraction.	None	None	None
Silica, amorphous, fumed, crystfree	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Epoxy resin	None	None	None	None
Epoxy resin	None	None	None	None
Epoxy resin	None	None	None	None
Modified Epoxy Resin	None	None	None	None
Epoxy resin	None	None	None	None
Epoxy Resin	None	None	None	None
Epoxy resin	None	None	None	None
Glass, oxide, chemicals	5 mg/m3 TWA Inhalable fraction. 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls: Ventilation should effectively remove and prevent buildup of any dust

generated from the handling of this product.

**Respiratory protection:** When dusts or thermal processing fumes are generated and ventilation is not

sufficient to effectively remove them, appropriate NIOSH/MSHA approved

respiratory protection must be provided.

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid Color: Blue Odor: Slight Not available. Odor threshold: Not applicable pH: Vapor pressure: Not applicable Boiling point/range: Not applicable Melting point/ range: Not applicable

Specific gravity: 1.6

Vapor density: Not applicable, Product is a solid.

Not applicable Flash point: Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not applicable Not applicable Flammability **Evaporation rate:** Not applicable Solubility in water: Negligible Partition coefficient (n-octanol/water): Not available. **VOC** content: Not applicable Viscosity: Not available. **Decomposition temperature:** Not available.

# 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of aluminum.

**Incompatible materials:** Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

products:

Inhalation: May cause respiratory tract irritation. Chronic exposure to respirable dust in excess of exposure

limits can cause aluminosis.

Skin contact: This product may cause irritation to the skin. This product may cause an allergic skin reaction.

**Eye contact:** This product may cause irritation to the eyes.

**Ingestion:** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Aluminum not powder, dust or fume	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l	Central nervous system, Irritant, Lung
Silica, amorphous, fumed, crystfree	None	No Data
Epoxy resin	None	Allergen, Irritant
Epoxy resin	None	Allergen, Irritant
Epoxy resin	None	Allergen, Irritant
Modified Epoxy Resin	None	No Data
Epoxy resin	None	No Data
Epoxy Resin	Oral LD50 (Rabbit) = 1,980 mg/kg Oral LD50 (Mouse) = 15,600 mg/kg Oral LD50 (Rat) = > 1,000 mg/kg Oral LD50 (Mouse) = > 500 mg/kg Dermal LD50 (Rabbit) = 20 mg/kg Dermal LD50 (Rat) = > 1,600 mg/kg Dermal LD50 (Mouse) = > 800 mg/kg	No Data
Epoxy resin	None	Allergen, Irritant
Glass, oxide, chemicals	None	Allergen, Respiratory

Hazardous Component(s)	NTP Carcinogen	IADC Carainagan	OSHA Carcinogen
		IARC Carcinogen	(Specifically Regulated)
Aluminum not powder, dust or fume	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
Epoxy resin	No	No	No
Epoxy resin	No	No	No
Epoxy resin	No	No	No
Modified Epoxy Resin	No	No	No
Epoxy resin	No	No	No
Epoxy Resin	No	No	No
Epoxy resin	No	No	No
Glass, oxide, chemicals	Reasonably Anticipated to be a Human Carcinogen.	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 1771330 Product name: LOCTITE EA 9845LA 020-016 AERO known as HYSOL EA 9845LSA 0.020/0.016
Page 4 of 6

## 13. DISPOSAL CONSIDERATIONS

#### Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

#### Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,13,15

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 08/17/2023

IDH number: 1771330 Product name: LOCTITE EA 9845LA 020-016 AERO known as HYSOL EA 9845LSA 0.020/0.016

Page 5 of 6

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.