

EMPLOYEE OWNED SINCE 2023

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.com



Revision Number: 004.0

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:LOCTProduct type/use:AdhesRestriction of Use:NoneCompany address:Henkel CorporationOne Henkel WayRocky Hill, Connecticut 06067

LOCTITE EA 9377 PT A 25GR AERO Adhesive for the Aerospace Industry None identified

2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE RESPIRATORY IRRITATION.
	SUSPECTED OF CAUSING GENETIC DEFECTS.
	MAY CAUSE CANCER.
	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED
	EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
GERM CELL MUTAGENICITY	2
CARCINOGENICITY	1A
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)

Precautionary Statements

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eve and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention, Take off contaminated clothing.
Storage: Disposal:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS). IDH number: 2516926 Product name: LOCTITE EA 9377 PT A 25GR AERO

Hazardous Component(s)	CAS Number	Percentage*
Silica, amorphous, naturally	60676-86-0	10 - 30
Triglycidyl-p-aminophenol	5026-74-4	10 - 30
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	10 - 30
Tetraglycidyl diaminodiphenylmethane	28768-32-3	5 - 10
Ceramic materials and wares, chemicals	66402-68-4	5 - 10
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	1675-54-3	5 - 10
Mica	12001-26-2	5 - 10
Neopentyl glycol diglycidyl ether	17557-23-2	1 - 5
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	1 - 5
Quartz (SiO2) respirable particulates (RCS) >=10%	14808-60-7	1 - 5
Titanium dioxide	13463-67-7	0.1 - 1

3. COMPOSITION / INFORMATION ON INGREDIENTS

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. F	IRST AID MEASURES
Inhalation:	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.
Skin contact:	Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively.
5. FIR	E FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

unidentified toxic gasses.

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

Unusual fire or explosion hazards:

Hazardous combustion products:

May liberate large quantities of dense, foul-smelling smoke which may contain

Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not breathe fumes or dust from this material. Use only with adequate ventilation. For industrial use only.

Storage:

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silica, amorphous, naturally	3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m3 TWA 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA	None	None
Total and a second second	News	Total dust.	News	News
Triglycidyl-p-aminophenol Epichlorohydrin-4,4'-isopropylidene	None	None	None	None
diphenol resin	None	None	None	None
Tetraglycidyl diaminodiphenylmethane	None	None	None	None
Ceramic materials and wares, chemicals	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	None	None	None	None
Mica	0.1 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 15 mg/m3 PEL Total dust. 5 mg/m3 PEL Respirable fraction.	None	None
Neopentyl glycol diglycidyl ether	None	None	None	None
Siloxanes and Silicones, di-Me, reaction products with silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Quartz (SiO2) respirable particulates (RCS) >=10%	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None
Titanium dioxide	0.2 mg/m3 TWA Respirable nanoscale particles 2.5 mg/m3 TWA Respirable finescale particles	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls:

Respiratory protection:

Eye/face protection:

Skin protection:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

Safety goggles or safety glasses with side shields.

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): **VOC content:** Viscosity: Decomposition temperature:

Solid Gray Epoxy Not available. Not applicable, Product is non-soluble (in water). < 0.1 hPa (20 °C (68°F)) > 200 °C (> 392°F) < -30 °C (< -22°F) 1.58 Not applicable, Product is a solid. Not applicable Not available. Not available. Not applicable The product is not flammable. Not applicable Not soluble Not available. < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated) Not available. > 200 °C

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	May occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	Strong acids and oxidizing agents. Amines.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:

Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	This product is irritating to the respiratory system.
Skin contact:	This product is irritating to the skin. This product may cause an allergic skin reaction.
Eye contact:	This product is irritating to the eyes.
Ingestion:	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silica, amorphous, naturally	None	Nuisance dust
Triglycidyl-p-aminophenol	None	Allergen, Irritant, Mutagen
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	Allergen, Irritant
Tetraglycidyl diaminodiphenylmethane	Inhalation LC50 (Rat, 4 h) = > 30 mg/m3	Allergen, Blood, Central nervous system, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Nervous System
Ceramic materials and wares, chemicals	Inhalation LC50 (Rat, 4 h) = > 3.5 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l	Lung
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	Oral LD50 (Rabbit) = 1,980 mg/kg Oral LD50 (Mouse) = 15,600 mg/kg Oral LD50 (Rat) = > 1,000 mg/kg Oral LD50 (Mouse) = > 500 mg/kg Dermal LD50 (Rabbit) = 20 mg/kg Dermal LD50 (Rat) = > 1,600 mg/kg Dermal LD50 (Mouse) = > 800 mg/kg	No Data
Mica	None	Lung
Neopentyl glycol diglycidyl ether	None	Allergen, Blood, Bone Marrow, Immune system, Irritant, Reproductive
Siloxanes and Silicones, di-Me, reaction products with silica	None	No Data
Quartz (SiO2) respirable particulates (RCS) >=10%	None	No Data
Titanium dioxide	Inhalation LC50 (Rat, 4 h) = > 6.82 mg/l Inhalation LC50 (Rat, 4 h) = > 2.28 mg/l Inhalation LC50 (Rat, 4 h) = > 3.56 mg/l	Irritant, Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silica, amorphous, naturally	No	No	No
Triglycidyl-p-aminophenol	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No
Tetraglycidyl diaminodiphenylmethane	No	No	No
Ceramic materials and wares, chemicals	No	No	No
2,2'-[(1-Methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxirane	No	No	No
Mica	No	No	No
Neopentyl glycol diglycidyl ether	No	No	No
Siloxanes and Silicones, di-Me, reaction products with silica	No	No	No
Quartz (SiO2) respirable particulates (RCS) >=10%	Known To Be Human Carcinogen.	Group 1	Yes
Titanium dioxide	No	Group 2B	No

12. ECOLOGICAL INFORMATION

Ecological information:

Toxic to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA) Proper shipping name:	Environmentally hazardous substance, solid, n.o.s. (Bisphenol-A Epichlorhydrin resin, Triglycidyl-p-aminophenol)
Hazard class or division:	9
Identification number:	UN 3077
Packing group:	III
Water Transportation (IMO/IMDG)	
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol-A Epichlorhydrin resin, Triglycidyl-p-aminophenol)
Hazard class or division:	9
Identification number:	UN 3077
Packing group:	
Marine pollutant:	Bisphenol-A Epichlorhydrin resin, Triglycidyl-p-aminophenol
Exceptions:	Classified per IMDG Amendment 34; Effective Jan 1, 2010.

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. Triglycidyl-p-aminophenol (CAS# 5026-74-4).
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
Canada Regulatory Information	

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Not available.

Fiepareu by. Fiouuci Salety and Regulatory Allans	Prepared by:	Product Safety and Regulatory Affairs
---	--------------	---------------------------------------

Issue date: 12/02/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.