


Revision Number: 001.2

Issue date: 12/02/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE EA 9377 AERO PART B 25GR	IDH number:	2773857
Product type/use:	Part B of 2-Component Epoxy Adhesive.	Item number:	AB9336307
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Do not breathe dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Tetraethylene pentamine	112-57-2	30 - 60
N,N'-Bis(3-aminopropyl)piperazine	7209-38-3	10 - 30
3,6,9,12-tetraazatetradecamethylenediamine	4067-16-7	5 - 10
Silica, amorphous, fumed, crystal-free	112945-52-5	5 - 10

IDH number: 2773857

Product name: LOCTITE EA 9377 AERO PART B 25GR

3,6-diazaoctanethylenediamine	112-24-3	1 - 5
Carbon black	1333-86-4	0.1 - 1
N-Aminoethylpiperazine	140-31-8	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self contained breathing apparatus.
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Do not heat Part B at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut, grind, weld, or drill on or near this container.
Storage:	Keep the container tightly closed and in a cool, well-ventilated place.
For information on product shelf life, please review labels on container or check the Technical Data Sheet.	

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Tetraethylene pentamine	None	None	1 ppm (5 mg/m ³) TWA Aerosol. (SKIN) Aerosol. (Skin sensitizer.)	None
N,N'-Bis(3-aminopropyl)piperazine	None	None	None	None
3,6,9,12-tetraazatetradecamethylenediamine	None	None	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m ³ TWA Inhalable dust. 3 mg/m ³ TWA Respirable fraction. 3 mg/m ³ TWA Respirable particles. 10 mg/m ³ TWA Inhalable particles.	20 MPPCF TWA 0.8 mg/m ³ TWA 50 MPPCF TWA Total dust. 5 mg/m ³ TWA Respirable fraction. 15 mg/m ³ TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
3,6-diazaoctanethylenediamine	None	None	1 ppm (6 mg/m ³) TWA (SKIN)	None
Carbon black	3 mg/m ³ TWA Inhalable fraction.	3.5 mg/m ³ PEL 5 mg/m ³ TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m ³ TWA Total dust.	None	None
N-Aminoethylpiperazine	None	None	None	None

Engineering controls:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

Respiratory protection:

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

Eye/face protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Black
Odor:	Slight
Odor threshold:	Not available.
pH:	11 - 13
Vapor pressure:	< 0.1 hPa (20 °C (68°F))
Boiling point/range:	> 200 °C (> 392°F)
Melting point/ range:	< -40 °C (< -40°F)
Specific gravity:	1.08
Vapor density:	Not applicable, Product is a solid.
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	The product is not flammable.
Evaporation rate:	Not available.
Solubility in water:	Soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	< 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)
Viscosity:	85,000 mPa.s
Decomposition temperature:	> 200 °C

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	May occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	Keep away from strong oxidizing agents, strong Lewis or mineral acids.
Reactivity:	Not available.
Conditions to avoid:	Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. Do not heat mixed adhesive unless curing surfaces to be bonded.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	Inhalation of dusts of this product may cause severe irritation and burns to the respiratory tract.
Skin contact:	This product is severely irritating to the skin and may cause burns. Repeated or prolonged skin contact may result in allergic sensitization.
Eye contact:	This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion:	May cause burns of mouth and throat if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Tetraethylene pentamine	Oral LD50 (Rat) = 3.99 g/kg Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen
N,N'-Bis(3-aminopropyl)piperazine	None	No Records
3,6,9,12-tetraazatetradecamethylenediamine	None	Irritant, Allergen
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
3,6-diazaoctanethylenediamine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity
N-Aminoethylpiperazine	None	Irritant, Corrosive, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Tetraethylene pentamine	No	No	No
N,N'-Bis(3-aminopropyl)piperazine	No	No	No
3,6,9,12-tetraazatetradecamethylenediamine	No	No	No
Silica, amorphous, fumed, crystal-free	No	No	No
3,6-diazaoctanethylenediamine	No	No	No
Carbon black	No	Group 2B	No
N-Aminoethylpiperazine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted piperazine)
Hazard class or division: 8
Identification number: UN 3259
Packing group: II
Marine pollutant: Tetraethylene pentamine

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: None above reporting de minimis.
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 12/02/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.