

EMPLOYEE OWNED SINCE 2023

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.com



Revision Number: 003.0 Issue date: 06/16/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA 934NA AERO PART B

40Z

Product type/use: Adhesive for the Aerospace Industry

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 **IDH number:** 936943

Item number:AB9174013Region:United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MAY CAUSE AN ALLERGIC SKIN REACTION.

TOXIC IF INHALED.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	3
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1

PICTOGRAM(S)







Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only

outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection. In case of inadequate

ventilation wear respiratory protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off

immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a poison center or physician. Wash contaminated

clothing before reuse.

Storage:Store in a well-ventilated place. Keep container tightly closed. Store locked up.Disposal:Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	68082-29-1	80 - 100
Diethylenetriamine	111-40-0	10 - 30
3,6-diazaoctanethylenediamine	112-24-3	1 - 5

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately wash skin

thoroughly with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting. Never give anything

by mouth to a victim who is unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: For the Part A plus Part B adhesive mixture, follow curing schedule as

recommended in product literature. Do not heat Part B at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut,

grind, weld, or drill on or near this container.

Storage: For safe storage, store between 0 °C (32°F) and 25 °C (77°F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	None	None	None
Diethylenetriamine	1 ppm TWA (SKIN)	None	None	None
3,6-diazaoctanethylenediamine	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Amber Color: amine-like Odor: Odor threshold: Not available.

pH: 10 - 12 Vapor pressure:

< 1.0 mm hg (20 °C (68°F)) < 0.1 hPa (20 °C (68°F)) 175 °C (347°F) Boiling point/range: Melting point/ range: Not determined

Specific gravity: 0.96 Vapor density: > 1

Flash point: > 93 °C (> 199.4 °F) Flammable/Explosive limits - lower: Not available.

Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not determined Flammability: Not applicable Evaporation rate: Not determined Solubility in water: low solubility Partition coefficient (n-octanol/water): Not determined

VOC content: < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Viscosity: Not available. > 200 °C **Decomposition temperature:**

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: May occur.

Hazardous decomposition

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials: Keep away from strong oxidizing agents, strong Lewis or mineral acids.

Reactivity: Not available.

Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Do Conditions to avoid:

not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these

precautions may result in excessive heat build-up causing an exotherm.

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Henkel is not aware of any toxicity data on the specific mixture of chemical components

contained in this product.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns.

Skin contact: This product is severely irritating to the skin and may cause burns. This product may cause an

allergic skin reaction.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness.

Ingestion: Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the

digestive tract.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	No Records	
Diethylenetriamine	Oral LD50 (Rat) Approximate 1,140 mg/kg Oral LD50 (Rat) = 1,080 mg/kg Oral LD50 (Rat) = 2.33 g/kg	Allergen, Irritant, Eyes	
3,6-diazaoctanethylenediamine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	No	No	No
Diethylenetriamine	No	No	No
3,6-diazaoctanethylenediamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Diethylenetriamine, Triethylenetetramine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Diethylenetriamine, Triethylenetetramine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Diethylenetriamine, Triethylenetetramine,

C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer)

Hazard class or division: 8

Identification number: UN 2735

Packing group:

Marine pollutant: C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Delayed Health
None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,9

Prepared by: Regulatory Affairs

Issue date: 06/16/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.