

EMPLOYEE OWNED SINCE 2023

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.com



Revision Number: 002.2

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product type/use:

Restriction of Use:

Company address:

Henkel Corporation

Rocky Hill, Connecticut 06067

One Henkel Way

LOCTITE EA 9396.6MD AERO PART B 6OZ Adhesive for the Aerospace Industry None identified 937128

Item number:AB9304313Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkelna.com


2. HAZARDS IDENTIFICATION

 EMERGENCY OVERVIEW

 DANGER:
 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

 MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1C - Corrosive
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1



Precautionary Statements

Prevention:	Do not breathe dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7	10 - 30
N,N'-Bis(3-aminopropyl)piperazine	7209-38-3	10 - 30
Glass, oxide, chemicals	65997-17-3	10 - 30

3,6,9,12- tetraazatetradecamethylenediamine	4067-16-7	5 - 10
Silica, amorphous, fumed, crystfree	112945-52-5	1 - 5
Tetraethylene pentamine	112-57-2	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.	
Skin contact:	Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.	
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.	
Ingestion:	Get immediate medical attention. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.	
Symptoms:	See Section 11.	
Notes to physician:	Treat symptomatically and supportively.	
5. FIRE	FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear protective equipment. Wear self contained breathing apparatus.	
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.	
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.	

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Avoid contact with eyes, skin and clothing. For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part B at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not take internally. Keep in a cool, well ventilated area. Keep container closed.

Storage:

Handling:

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Amines, polyethylenepoly-, tetraethylenepentamine fraction	None	None	None	None
N,N'-Bis(3-aminopropyl)piperazine	None	None	None	None
Glass, oxide, chemicals	5 mg/m3 TWA Inhalable fraction. 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.		None	None
3,6,9,12- tetraazatetradecamethylenediamine	None	None	None	None
Silica, amorphous, fumed, crystfree	20 MPPCF TWA 0.8 mg/m3 TWA 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Inhalable particles. 15 mg/m3 TWA 15 mg/m3 TWA 1		None	None
Tetraethylene pentamine None		None	1 ppm (5 mg/m3) TWA Aerosol. (SKIN) Aerosol. (Skin sensitizer.)	None

Engineering controls:

Eye/face protection:

Skin protection:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved

Respiratory protection:

Safety goggles or safety glasses with side shields.

respiratory protection must be provided.

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: paste Color: White Odor: amine-like Odor threshold: Not available. pH: 11 - 13 . Vapor pressure: < 0.1 hPa (20 °C (68°F)) Boiling point/range: 150 °C (302°F) < -40 °C (< -40°F) Melting point/ range: Specific gravity: Vapor density: Not applicable, Product is a solid. Flash point: Not applicable Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not determined The product is not flammable. Flammability: Evaporation rate: Not determined Solubility in water: Soluble Partition coefficient (n-octanol/water): Not available. VOC content: < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated) Viscosity: Not available. > 200 °C Decomposition temperature:

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous reactions:	May occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	Keep away from strong oxidizing agents, strong Lewis or mineral acids.
Reactivity:	Not available.
Conditions to avoid:	Avoid mixing resin (Part A) and curing agent (Part B) unless you plan to use immediately. Do not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. The exotherm has the potential for release of toxic gasses.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Skin contact:	Inhalation of dusts of this product may cause severe irritation and burns to the respiratory tract. This product is severely irritating to the skin and may cause burns. Repeated or prolonged skin contact may result in allergic sensitization.
Eye contact:	This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion:	Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Amines, polyethylenepoly-, tetraethylenepentamine fraction	None	No Data
N,N'-Bis(3-aminopropyl)piperazine	None	No Records
Glass, oxide, chemicals	None	Allergen, Respiratory
3,6,9,12- tetraazatetradecamethylenediamine	None	Irritant, Allergen
Silica, amorphous, fumed, crystfree	None	No Data
Tetraethylene pentamine	Oral LD50 (Rat) = 3.99 g/kg Oral LD50 (Rat) = 2.1 g/kg Dermal LD50 (Rabbit) = 0.66 g/kg	Irritant, Mutagen, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Amines, polyethylenepoly-, tetraethylenepentamine fraction	No	No	No
N,N'-Bis(3-aminopropyl)piperazine	No	No	No
Glass, oxide, chemicals	Reasonably Anticipated to be a Human Carcinogen.	No	No
3,6,9,12- tetraazatetradecamethylenediamine	No	No	No
Silica, amorphous, fumed, crystfree	No	No	No
Tetraethylene pentamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (Proper shipping name: Hazard class or division: Identification number: Packing group:	49 CFR) Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine) 8 UN 3259 III
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Amines, solid, corrosive, n.o.s. (Tetraethylene pentamine, Substituted piperazine)
Hazard class or division:	8
Identification number:	UN 3259
Packing group:	III
Water Transportation (IMO/IMDG)	
Proper shipping name:	AMINES, SOLID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Substituted piperazine)
Hazard class or division:	8
Identification number:	UN 3259
Packing group:	
Marine pollutant:	Tetraethylene pentamine

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,15

Prepared by: Regulatory Affairs

Issue date:

10/10/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.