

EMPLOYEE OWNED SINCE 202

1-800-375-0605 | rbcsupport@rudbro.com | www.rudolphbros.com



Revision Number: 003.7 Issue date: 07/12/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE EA 9258.1 GAL AERO known IDH number:

as HYSOL EA 9258.1 GAL

Product type/use: Primer
Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 IDH number: 832403

Item number:PR9041018Region:United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE CANCER.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	1A

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Water	7732-18-5	60 - 80

IDH number: 832403 Product name: LOCTITE EA 9258.1 GAL AERO known as HYSOL EA 9258.1 GAL Page 1 of 7

2-Propenoic acid, 2-methyl-, reaction products with bisphenol A-epichlorohydrin polymer, compds. with 2-(dimethylamino) ethanol	1799813-60-7	5 - 10
Epoxy resin	Proprietary	5 - 10
Epoxy resin	Proprietary	1 - 5
2-Butoxyethanol	111-76-2	1 - 5
Strontium chromate	7789-06-2	1 - 5
2-Dimethylaminoethanol	108-01-0	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention. Delayed effects possible after inhalation. Administer oxygen or artificial respiration as needed. Do not use mouth-to-mouth method if victim ingested or inhaled the substance.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Launder contaminated clothing before reuse. Discard any

shoes or clothing items that cannot be decontaminated.

Eye contact: Immediately flush affected eye with large amounts of gently flowing water or

0.9% sterile saline solution for at least 15 minutes. Hold eyelid wide open. Get immediate medical attention. Eye flushing should continue during

transportation to a doctor. Get medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting. If individual is

conscious, wash out mouth with water. Provide a glass of water to dilute the

material in the stomach.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: Not a fire hazard.

Hazardous combustion products: Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon

monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

Chromium oxide. Oxides of Strontium.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways. Wear appropriate

protective equipment and clothing during clean-up.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

IDH number: 832403

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Avoid breathing vapors or mists of this product. Use only with adequate ventilation. Launder work clothes frequently. Do not store or consume food, drink, or tobacco products in areas where they may become contaminated

with this material. Do not take internally. For industrial use only.

Storage: For safe storage, store between 5 °C (41°F) and 27 °C (80.6 °F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Water	None	None	None	None
2-Propenoic acid, 2-methyl-, reaction products with bisphenol A-epichlorohydrin polymer, compds. with 2-(dimethylamino) ethanol	None	None	None	None
Epoxy resin	None	None	None	None
Epoxy resin	None	None	None	None
2-Butoxyethanol	20 ppm TWA	50 ppm (240 mg/m3) PEL (SKIN)	None	None
Strontium chromate	0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. (Dermal sensitization) (Respiratory sensitization)	0.005 mg/m3 TWA 0.0025 mg/m3 OSHA_ACT 0.1 mg/m3 Ceiling 1 mg/m3 PEL (as Cr)	None	None
2-Dimethylaminoethanol	None	None	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection:Use chemical resistant, impervious gloves and clothing to prevent skin

contact. Gloves should be tested to determine suitability for prolonged contact.

Use of impervious boots is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:GreenOdor:NoneOdor threshold:Not available.

pH: 7 - 9

Vapor pressure: 1.0 mm hg (20 °C (68°F)) 25 hPa (20 °C (68°F))

Boiling point/range: 100 °C (212°F)

Melting point/ range: Not applicable, Product is a liquid

IDH number: 832403 Product name: LOCTITE EA 9258.1 GAL AERO known as HYSOL EA 9258.1 GAL

Page 3 of 7

Specific gravity: 1.04 Vapor density: > 1

Flash point: > 93 °C (> 199.4 °F); Aqueous solution

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not applicable

Flammability: The product is not flammable.

Evaporation rate: Slower than ether.

Solubility in water: Dispersible

Partition coefficient (n-octanol/water): Not determined

VOC content: 142 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated)

Viscosity: Not available. Decomposition temperature: > 200 °C

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 832403

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Chromium oxide. Oxides of Strontium.

Incompatible materials: This product may react with strong reducing agents. Keep away from organic and combustible

materials. Keep away from strong oxidizing agents, strong Lewis or mineral acids. Strong

bases. Metals.

Reactivity: Not available.

Conditions to avoid: Do not expose to extreme hot or cold temperatures.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May be harmful or fatal if inhaled. Nasal itch and soreness, perforation of the nasal septum,

dental erosion, and chronic asthmatic bronchitis may result from repeated exposure. This

product is irritating to the respiratory system.

A component in this product may be harmful or fatal if absorbed through the skin, especially if Skin contact:

skin is damaged. This product is irritating to the skin. Product contains chromium, which may cause an allergic skin sensitization reaction. Contact with broken skin may lead to formation of

firmly marginated "chrome sores".

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness.

Ingestion: Harmful or fatal if swallowed. Ingestion can cause gastrointestinal irritation, nausea, vomiting

and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Water	None	No Target Organs
2-Propenoic acid, 2-methyl-, reaction products with bisphenol A-epichlorohydrin polymer, compds. with 2-(dimethylamino) ethanol	None	No Data
Epoxy resin	None	Irritant, Allergen
Epoxy resin	None	No Data
2-Butoxyethanol	Oral LD50 (Rat) = 560 mg/kg Oral LD50 (Mouse) = 1.2 g/kg Oral LD50 (Rabbit) = 0.32 g/kg Oral LD50 (Rat) = 1.48 g/kg Oral LD50 (Mouse) = 1,519 mg/kg Dermal LD50 (Rabbit) = 400 mg/kg Inhalation LC50 (Rat, 4 h) = 523 ppm Inhalation LC50 (Rat, 4 h) = 545 ppm	Blood, Central nervous system, Irritant, Kidney, Liver
Strontium chromate	Oral LD50 (Rat) = 811 mg/kg Oral LD50 (Rat) = 3,118 mg/kg Oral LD50 (Rat) = 811 mg/kg Oral LD50 (Rat) = 3,118 mg/kg Inhalation LC50 (Rat, 4 h) = 0.27 - 0.51 mg/l	Irritant, Respiratory, Central nervous system, Allergen, Liver, Kidney, Developmental, Reproductive, Corrosive, Carcinogen, Mutagen, Blood
2-Dimethylaminoethanol	None	Central nervous system, Irritant, Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Water	No	No	No
2-Propenoic acid, 2-methyl-, reaction products with bisphenol A-epichlorohydrin polymer, compds. with 2-(dimethylamino) ethanol	No	No	No
Epoxy resin	No	No	No
Epoxy resin	No	No	No
2-Butoxyethanol	No	No	No
Strontium chromate	Known To Be Human Carcinogen.	Group 1	Yes
2-Dimethylaminoethanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

IDH number: 832403

Do not empty into drains / surface water / ground water.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

DOT Hazardous Substance(s): Strontium chromate

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

This product contains one or more components with a Polymer Exemption in accordance

with 40 CFR 723.250.

TSCA 12 (b) Export Notification: Strontium chromate (CAS# 7789-06-2).

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health CERCLA/SARA Section 313: This product contains the following

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 373) 2 Putament and CAS# 414 70 2) Street

CFR 372). 2-Butoxyethanol (CAS# 111-76-2). Strontium chromate (CAS# 7789-06-2).

CERCLA Reportable quantity: Strontium chromate (CAS# 7789-06-2) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 832403

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 07/12/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 832403