





6550 Oley Speaks Way Canal Winchester, OH 43110



www.rudolphbros.com rbcsupport@rudbro.com

## Safety Data Sheet



Revision Number: 003.1 Issue date: 10/04/2019

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:LOCTITE 567 BO350MLIDH number:2087072Product type/use:Adhesive/SealantItem number:2087072Restriction of Use:None identifiedRegion:United States

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (tollfree) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (tollfree) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	CAUSES SKIN IRRITATION.	
	MAY CAUSE AN ALLERGIC SKIN REACTION.	
	CAUSES SERIOUS EYE IRRITATION.	

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



#### **Precautionary Statements**

**Prevention:** Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated w ork clothing should not be allow ed out of the w orkplace. Wear protective

gloves, eye protection, and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*

3,3,5 Trimethylcyclohexyl methacrylate	7779-31-9	10 - 30
Ethene, homopolymer	9002-88-4	5 - 10
Ethene, tetrafluoro-, homopolymer	9002-84-0	5 - 10
Titanium dioxide	13463-67-7	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Propane-1,2-diol	57-55-6	1 - 5
Cumene hydroperoxide	80-15-9	0.1 - 1
Cumene	98-82-8	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

**Inhalation:** If inhaled, immediately remove the affected person to fresh air. If not

breathing, give artificial respiration. If breathing is difficult, give oxygen. If

symptoms develop and persist, get medical attention.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. If skin irritation persists, call

a physician.

Eye contact: IF IN EYES: Rinse cautiously with waterfor several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a specialist.

**Ingestion:** DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical

attention.

Symptoms: See Section 11.

# 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. In case of fire, keep containers cool with water spray.

Uncontrolled polymerization may occur at high temperatures resulting in

explosions or rupture of storage containers.

**Hazardous combustion products:** Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics.

Toxic fluorine compounds. Ketones.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, is olate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sew er or waterways.

Clean-up methods: Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to

prevent entry into w ater system; w earfull protective equipment during cleanup. Soak up w ith inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, saw dust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure

Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed. Refer to Section 8.

Storage: Keep in a cool, well ventilated area away fromheat, sparks and open flame.

Keep container tightly closed until ready for use. Store frost-free.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

 $\label{lem:property} \textbf{Employers should complete} \ an \ as \ sessment \ of \ all \ workplaces \ to \ determine \ the \ need \ for, \ and \ selection \ of, \ proper \ exposure \ controls \ and \ protective \ equipment \ for \ each \ task \ performed.$ 

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
3,3,5 Trimethylcyclohexyl methacrylate	None	None	None	None
Ethene, homopolymer	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Silica, amorphous, fumed, crystal-free	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 0.8 mg/m3 TWA	None	None
Propane-1,2-diol	None	None	10 mg/m3 TWA Aerosol.	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) PEL (SKIN)	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Safety

show ers and eye wash stations should be available.

**Skin protection:** Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Neoprene gloves.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:Not available.Color:Not available.Odor:Not available.Odor threshold:Not available.pH:Not available.Vapor pressure:Not available.

Boiling point/range: > 149 °C (> 300.2 °F)no method

Melting point/ range: Not available.

Specific gravity: 1.15

Vapor density: Not available. Flash point: > 93 °C (> 199.4 °F) Not available. Flam mable/Explosive limits - lower: Flam mable/Explosive limits - upper: Not available. Not available. Autoignition temperature: Flam mability: Not applicable Not available. Evaporation rate: Solubility in water: Not available. Partition coefficient (n-octanol/water): Not available.

**VOC content:** 0.13 % (ASTM D5403)

Viscosity:Not available.Decomposition temperature:Not available.

# 10. STABILITY AND REACTIVITY

**Stability**: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing. Polymerization may occur at elevated temperature or in the

presence of incompatible materials.

Hazardous decomposition

products:

Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics. Toxic fluorine

compounds. Ketones.

Incompatible materials: Strong oxidizing agents. Strong reducing agents. Free radical initiators. Inert gases. Oxygen

scavengers.

Reactivity: Not available.

Conditions to avoid: Evated temperatures. Heat, flames, sparks and other sources of ignition. Store away from

incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of vapors or mists of the product may be irritating to the respiratory system.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** May cause gastrointestinal tract irritation if sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
3,3,5 Trimethylcyclohexyl methacrylate	None	No Records
Ethene, homopolymer	None	No Target Organs
Ethene, tetrafluoro-, homopolymer	None	No Target Organs
Titanium dioxide	None	Irritant, Respiratory, Some evidence of carcinogenicity
Silica, amorphous, fumed, crystal-free	None	Nuisance dust
Propane-1,2-diol	Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg	Irritant
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Cumene	Oral LD50 (Rat) = 2.91 g/kg Oral LD50 (Rat) = 1,400 mg/kg	Central nervous system, Irritant, Lung

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
3,3,5 Trimethylcyclohexyl methacrylate	No	No	No
Ethene, homopolymer	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Titanium dioxide	No	Group 2B	No
Silica, amorphous, fumed, crystal-free	No	No	No
Propane-1,2-diol	No	No	No
Cumene hydroperoxide	No	No	No
Cumene	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No

### 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082

Packing group:

**DOT Hazardous Substance(s)**: alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

**Propershipping name:** RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9
Identification number: UN 3082
Packing group:

Water Transportation (IMO/IMDG)

Propershipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: 9
Identification number: UN 3082
Packing group:

## 15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene (CAS# 98-82-8).

CERCLA Reportable quantity: Cumene hydroperoxide (CAS#80-15-9) 10 lbs. (4.54 kg)

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 4

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 10/04/2019

**DISCLAIM ER:** The data contained herein are furnished for information only and are believed to be reliable. How ever, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all w arranties, express or implied, including w arranties of merchantability and fitness for a particular purpose, arising fromsale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 2087072 Product name: LOCTITE 567 BO350ML

Page 6 of 6







6550 Oley Speaks Way Canal Winchester, OH 43110



www.rudolphbros.com rbcsupport@rudbro.com