



Safety Data Sheet



Revision Number: 007.0

Issue date: 08/23/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE LB 771 NICKEL GRADE ANTI-SEIZE known as Nickel Grade Anti-Seize	IDH number:	135543
Product type/use:	Lubricant	Item number:	77164
Restriction of Use:	None identified	Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MAY CAUSE AN ALLERGIC SKIN REACTION.
SUSPECTED OF CAUSING CANCER.
CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN SENSITIZATION	1
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 60
Nickel	7440-02-0	10 - 30

Graphite	7782-42-5	5 - 10
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	1 - 5
Lard, oil, polymd., oxidized	68082-79-1	1 - 5
Aluminum not powder, dust or fume	7429-90-5	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention. Wash clothing before reuse.
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
Symptoms:	See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of carbon. Oxides of Metals in Section 3. Toxic and irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Scrape up as much material as possible. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Keep container closed. Prevent contact with eyes, skin and clothing. Do not breathe the vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation.
Storage:	Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m ³ TWA Inhalable fraction.	5 mg/m ³ PEL Mist. 500 ppm (2,000 mg/m ³) PEL	None	None
Nickel	1.5 mg/m ³ TWA Inhalable fraction.	1 mg/m ³ PEL (as Ni)	None	None
Graphite	2 mg/m ³ TWA Respirable fraction.	5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust. 5 mg/m ³ PEL Respirable fraction. 15 mg/m ³ PEL Total dust.	None	None
Distillates (petroleum), hydrotreated heavy paraffinic	5 mg/m ³ TWA mist 10 mg/m ³ STEL mist	5 mg/m ³ TWA mist 5 mg/m ³ PEL Mist.	None	None
Lard, oil, polymd., oxidized	None	None	None	None
Aluminum not powder, dust or fume	1 mg/m ³ TWA Respirable fraction.	None	None	None

Engineering controls:	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Eye/face protection:	Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.
Skin protection:	Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Gray
Odor:	Petroleum
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	< 5 mm hg (80 °F (26.7 °C))
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	1.1
Vapor density:	Not available.
Flash point:	> 93 °C (> 199.4 °F)
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Negligible
Partition coefficient (n-octanol/water):	Not available.
VOC content:	2.47 %; 27 g/l
Viscosity:	Not available.
Decomposition temperature:	Not available.



10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Oxides of carbon. Oxides of Metals in Section 3. Irritating organic vapours.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, spark and flame. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation.
Skin contact:	May cause skin irritation. May cause allergic skin reaction.
Eye contact:	May cause eye irritation.
Ingestion:	Not expected under normal conditions of use. May cause gastrointestinal tract irritation if sw allowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l	Irritant
Nickel	None	No Data
Graphite	Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3 Inhalation LC50 (Rat, 4 h) = > 2,000 mg/m3	Lung
Distillates (petroleum), hydrotreated heavy paraffinic	Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = 9.6 mg/l Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l Inhalation LC50 (Rat, 4 h) = > 5 mg/l Inhalation LC50 (Rat, 4 h) = > 5.53 mg/l	Irritant
Lard, oil, polymd., oxidized	None	No Records
Aluminum not powder, dust or fume	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l	Central nervous system, Irritant, Lung

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Nickel	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Graphite	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No
Lard, oil, polymd., oxidized	No	No	No
Aluminum not powder, dust or fume	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.



13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis.
CERCLA/SARA Section 311/312:	Delayed Health, Immediate Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Nickel (CAS# 7440-02-0).
CERCLA Reportable quantity:	Nickel (CAS# 7440-02-0) 100 lbs. (45.4 kg)
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
-----------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/23/2021



DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 135543

Product name: LOCTITE LB 771 NICKEL GRADE ANTI-SEIZE known as Nickel Grade Anti-Seize
Page 6 of 6



1-800-375-0605
Option 8 for 24/7 Service



www.rudolphbros.com
rbcsupport@rudbro.com