

**BONDERITE®****BONDERITE S-AD 6**Known as Turco STRIP ADDITIVE 6  
January 2014**PRODUCT DESCRIPTION**

BONDERITE S-AD 6 provides the following product characteristics:

<b>Technology</b>	Metal Pre-Treatment
<b>Product Type</b>	Paint Stripper
<b>Application</b>	Immersion

BONDERITE S-AD 6 is a concentrate of active ingredients which in combination with potassium hydroxide or as an additional component to optimize hot paint strippers is assembled for removing paint of iron and steel in the immersion process.

**Application Areas**

BONDERITE S-AD 6

- significantly improves paint stripping performance
- shortens the critical paint stripping time
- significantly extends the life of the baths

**TECHNICAL DATA**

Appearance	clear liquid
Density, g/ml	1.1
pH-Value (0.1%, DI-water)	6.5 to 7.5

**DIRECTION OF USE****Preliminary Statement**

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

**Use instructions**

BONDERITE S-AD 6 is a special additive for paint strippers.

BONDERITE S-AD 6 is always then added to the paint stripper bath, if the paint stripping performance despite compliance of the paint stripper concentration by the consumption of organic paint stripping ingredients.

The consumption depends on the type of the paint layer, plant technology and the available paint stripping time and should therefore be determined in practice.

We recommend to add BONDERITE S-AD 6 in portions of 2 % relative to the volume of the bath till the paint stripping performance is restored.

After the addition of BONDERITE S-AD 6 the paint stripper bath should be homogenized.

In practice, the regular addition of BONDERITE S-AD 6 with a frequency of 1 to 2 times per week is proven.

**Storage**

Temperature, °C	5 to 40
Shelf-life (in unopened original packaging), months	24

**Classification**

Please refer to the corresponding **Material Safety Data Sheets** for details on:

**Hazardous Information**  
**Transport Regulations**  
**Safety Regulations**



## ADDITIONAL INFORMATION

### Disclaimer

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

#### **In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0