# SAFETY DATA SHEET



# 1. Identification

Product identifier KE-347-W

Other means of identification

Sales Code 1882S0

Recommended use RTV rubbers

RTV rubber for electrical, electronic and general industry (gluing and sealing)

Recommended restrictions Industrial use only.

Manufacturer/Importer/Supplier/Distributor information

Name Shin-Etsu Silicones of America, Inc.
Address 1150 Damar Drive, Akron, OH 44305 USA

**Contact** Regulation compliance group

**Telephone Number** +1-330-630-9860 **Fax Number** +1-330-630-9855

Emergency Phone Number Chemtrec: +1-800-424-9300 (Within US)

Chemtrec: +1-703-527-3887 (Outside US)

# 2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

\*Hazards not stated here are "Not classified", "Not applicable" or "Classification not possible".

#### Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary

measures against static discharge. Wear protective gloves/protective clothing/eye protection/face

protection. Wash thoroughly after handling.

Response In case of fire: Use water fog, foam, dry chemical powder or carbon dioxide(CO2) to extinguish. IF

ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash it before reuse.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Substance(s) formed under the

condition of use

This product reacts with water, moisture or humid air to evolve following compounds:

Acetone

The following material is embedded in the product and not available as respirable dusts. When

used as intended or as supplied, the product will not pose hazards.

Titanium oxide.

Material name: KE-347-W SDS US

11357 Version #: 01 Issue date: 03-26-2015

Health: 2 Flammability: 3 Physical hazard: 0

# 3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Alkenoxysilane*		Proprietary*	5 - < 10
Titanium oxide		13463-67-7	1 - < 3
Alkoxysilane*		Proprietary*	< 1
Organosilane*		Proprietary*	< 1
Decomposition			
Chemical name		CAS number	%
Acetone		67-64-1	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4.	H	rei	i-ai	n	m	P:	25	Пľ	'ם	3

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. For minor skin

contact, avoid spreading material on unaffected skin. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact Rinse immediately with plenty of water for at least 15 minutes. Remove contact lenses, if present

vision. Skin irritation. May cause redness and pain.

and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Rinse mouth. Get medical attention immediately. Ingestion

Most important symptoms/effects, acute and

delayed

Treat symptomatically.

Indication of immediate medical attention and special treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

None known.

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions General fire hazards

By heating and fire, harmful vapors/gases may be formed.

Nitrogen oxides. (corrosive)

Water fog. Foam. Carbon dioxide (CO2).

Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots, and self-contained breathing apparatus.

Move containers from fire area if you can do so without risk.

Flammable liquid and vapor.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Local authorities should be advised if significant spillages cannot be contained. Do not touch or walk through spilled material. Ventilate closed spaces before entering them. Wear appropriate personal protective equipment.

# Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

## **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Provide adequate ventilation.

Use care in handling/storage. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Take precautionary measures against static discharges. Use personal protective equipment as required. Wash hands thoroughly after handling.

Do not breathe mist or vapor. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure.

# Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in cool place. Store in a well-ventilated place. Keep container tightly closed. Keep out of the reach of children. Store in a cool, dry place out of direct sunlight. Keep in original container.

# 8. Exposure controls/personal protection

# Occupational exposure limits

Components	Type	Value	Form
Titanium oxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Decomposition	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
US. ACGIH Threshold Limit Values Components	Type	Value	
Titanium oxide (CAS	TWA	10 mg/m3	

13463-67-7)	IVVA	10 mg/m3
Decomposition	Туре	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm

US. NIOSH: Pocket Guide to Chemical Hazards				
Decomposition	Туре			

Acetone (CAS 67-64-1) TWA 590 mg/m3 250 ppm

## **Biological limit values**

ACGIH Biological Exposure Indices

Decomposition	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

# US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

TOLUENE; TOLUOL (CAS 108-88-3)

Can be absorbed through the skin.

US. Minnesota Hazardous Substances List (Minn. Rules 5206.0400).

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Provide eyewash station.

Pay attention to ventilation such as local exhaust, mechanical and/or door open for at least 24

Value

hours after application.

Material name: KE-347-W

Individual protection measures, such as personal protective equipment

Eye/face protection Tightly sealed safety glasses according to EN 166.

Skin protection

Hand protection Wear protective gloves.

Wear suitable protective clothing. Other

If airborne concentrations are above the applicable exposure limits, use NIOSH approved Respiratory protection

respiratory protection.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Avoid contact with skin. Avoid contact with eyes. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Handle in accordance with good industrial hygiene and

safety practice.

# 9. Physical and chemical properties

**Appearance** 

**Form** Paste. White. Color

Acetone odor Odor **Odor threshold** Not available. Not available. pН Melting point/freezing point Not applicable Initial boiling point and boiling Not applicable

range

Flash point 77 °F (25 °C) Closed Cup < 1 (Butyl Acetate=1) **Evaporation rate** 

Not applicable. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

2.1 % v/v [Acetone]

(%)

Flammability limit - upper

13.0 % v/v [Acetone]

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Negligible (25 °C) Vapor pressure

Vapor density > 1 (air=1) Relative density 1.04 (25 °C)

Solubility(ies)

Solubility (water) Not soluble Partition coefficient

(n-octanol/water)

Not applicable

None known.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** 55 Pa·s (25 °C)

Other information

Molecular weight Not applicable

## 10. Stability and reactivity

No hazardous reaction known under normal conditions of use, storage and transport. Reactivity

Chemical stability Stable at normal conditions.

Possibility of hazardous

reactions

**Conditions to avoid** Incompatible materials

Strong oxidizing agents. Water, moisture.

Hazardous polymerization does not occur.

11357 Version #: 01 Issue date: 03-26-2015

Hazardous decomposition products

This product reacts with water, moisture or humid air to evolve following compounds:

Acetone.

Thermal breakdown of this product during fire or very high heat condition may evolve the following

hazardous decomposition product:

Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen

oxides. Formaldehyde.

# 11. Toxicological information

Information on likely routes of exposure

**Ingestion** Expected to be a low ingestion hazard.

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

## Information on toxicological effects

# **Acute toxicity**

Components	Species	Test Results
Alkenoxysilane (CAS Proprietary)		
Acute		
Oral		
LD50	Rat	> 20 ml/kg
Alkoxysilane (CAS Proprietary)		
Acute		
Dermal		
LD50	Rabbit	4290 mg/kg
Oral		
LD50	Rat	1570 - 3650 mg/kg
		1780 mg/kg
Organosilane (CAS Proprietary)		
Acute		
Oral		
LD50	Rat	3.67 ml/kg
Decomposition	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Inhalation		
LC50	Rat	50.1 mg/l, 8 Hours
Oral		
LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Skin corrosion/irritation	Causes visible necrosis of the skin tissue (Rabbit/60 SKIN-RABBIT : 5mg/24Hr SEVERE [Alkoxysilane]	) Minutes) [Organosilane]
Serious eye damage/eye irritation	Causes serious eye damage. [Organosilane] EYE-RABBIT: 0.75mg/24Hr SEVERE [Alkoxysilane Causes serious eye irritation. [Acetone]	•]
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not available.	
Skin sensitization	Positive (Guinea pig) [Alkoxysilane]	
Germ cell mutagenicity	Negative(Ames Test) [Alkoxysilane]	

# Carcinogenicity

The following material is embedded in the product and not available as respirable dusts. When

used as intended or as supplied, the product will not pose hazards.

Titanium oxide.

## IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium oxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Not available.

Specific target organ toxicity -

May cause damage to the following organs.

single exposure

Narcotic effects. [Acetone]

Specific target organ toxicity -

repeated exposure

Not available.

**Aspiration hazard** 

Not available.

**Further information** 

This product reacts with water, moisture or humid air to evolve following compounds:

Acetone

# 12. Ecological information

		12. Ecological illiorillation	
otoxicity			
Components		Species	Test Results
Alkoxysilane (CAS Proprieta	ıry)		
Aquatic			
Fish	LC50	Oryzias latipes	> 1000 mg/l, 48 hr
Titanium oxide (CAS 13463-	-67-7)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Decomposition		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
sistence and degradability	Causes easily	hydrolysis in water or atmosphere. [Alkox	ysilane]
accumulative potential	Not available.		
bility in soil	Not available.		
ner adverse effects	Not available.		

# 13. Disposal considerations

Follow applicable Federal, State and Local regulations. **Disposal instructions** 

# 14. Transport information

DOT

UN1993 **UN** number

**UN** proper shipping name Flammable liquids, n.o.s. (Alkenoxysilane)

Transport hazard class(es)

3 **Class** Subsidiary risk 3 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T4, TP1, TP29 Special provisions

150 Packaging exceptions 203 Packaging non bulk 242 Packaging bulk

#### **IATA**

**UN number** UN1993

**UN** proper shipping name Flammable liquid, n.o.s. (Alkenoxysilane)

Transport hazard class(es)

Class 3 Subsidiary risk Ш Packing group **Environmental hazards** No. 3L **ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Allowed. Cargo aircraft only

**IMDG** 

UN1993 **UN** number

FLAMMABLE LIQUID, N.O.S. (Alkenoxysilane) **UN proper shipping name** 

Transport hazard class(es)

3 **Class** Subsidiary risk Ш Packing group **Environmental hazards** 

Marine pollutant No. F-E. S-E\* **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

This product is not intended to be transported in bulk.

#### DOT



IATA; IMDG



# 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 313 (TRI reporting)

## **US state regulations**

#### **US. Massachusetts RTK - Substance List**

Titanium oxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

# US. New Jersey Worker and Community Right-to-Know Act

Titanium oxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Titanium oxide (CAS 13463-67-7)

Toluene (CAS 108-88-3)

#### **US. Rhode Island RTK**

Toluene (CAS 108-88-3)

## **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

The following material is embedded in the product and not available as respirable dusts. When used as intended or as supplied, the product will not pose hazards.

Titanium oxide.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium oxide (CAS 13463-67-7) Listed: September 2, 2011

## US - California Proposition 65 - CRT: Listed date/Developmental toxin

Toluene (CAS 108-88-3)

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

Toluene (CAS 108-88-3)

Listed: August 7, 2009

## **International Inventories**

Country(s) or region	Inventory name On invento	ry (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
*A "Voo" indicates that all somes		(-)

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 03-26-2015

Version # 0

NFPA ratings Health: 2

Flammability: 3 Instability: 0

Material name: KE-347-W SDS US

## NFPA ratings



#### Disclaimer

This information is offered in good faith as typical values and not as a product specification. No warranty, expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

This product has been designed, manufactured and developed solely for general industrial use only. This product is not designed for, intended for use as, or suitable for, medical, surgical or other particular purposes. Users have the sole responsibility and obligation to determine the suitability of this product for any application, to make preliminary tests, and to confirm the safety of this product for their use. Users must never use this product for the purpose of implantation into the human body and/or injection into humans.

Distributed by: Rudolph Bros. & Co. 6550 Oley Speaks Way Canal Winchester, OH 43110 Phone: 614-833-0707

Fax: 800-600-9508

e-mail: rbcsupport@rudbro.com

www.rudbro.com