

# tesa® 64662



## product information

### Industrial Grade Poly-coated Cloth Duct Tape

tesa® 64662 offers excellent tensile strength and hand-tearability. tesa® 64662 is available in a variety of colors. Excellent for draping, and securing as well as for demanding packaging, bundling, holding, seaming, sealing, protecting, wrapping and repairing applications.

### Main Application

- Patching
- Packaging
- Seaming
- Sealing

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	PE laminated cloth	• Tensile strength	42 N/cm
• Total thickness	230 µm	• Temperature resistance (30 min)	93 °C
• Type of adhesive	natural rubber	• Mesh	27 count per square inch
• Elongation at break	16 %		

#### Adhesion to

- steel 5.5 N/cm  
50.2 oz/in

#### Properties

- |                       |     |                       |    |
|-----------------------|-----|-----------------------|----|
| • Hand tearability    | ●●● | • Abrasion resistance | ●● |
| • Straight tear edges | ●●● | • Water resistance    | ●● |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

# tesa<sup>®</sup> 64662

## product information



### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=64662>